

No.	DATE	DESCRIPTION	REV	REMARK : RoHS REQUIREMENT APPLIED (符合RoHS)	DATE	DRAWING NO.

Electrical Specification:

- 1.Impedance : 50 ohm
- 2.Frequency Range : DC ~ 40 GHz
- 3.VSWR : 1.20 max.

LOGO : LASER

THE ACTUAL DIRECTION AND POSITION OF THE LOG, WHICH WILL NOT ALIGN WITH TOP AREA SAME AS THE DRAWING IMAGE.

S 1 : 1

-	shell	2	SUS303	passivated		DIMENSIONS ARE IN MILLIMETERS UNLESS OTHRWISE PECIFIED TOLERANCES (一般公差) 0.5~6 = ±0.2 >6~30 = ±0.4 >30~120 = ±0.6 >120~315 = ±1 >315~1000 = ±1.6 ANGLES(角度) = ±5°	CHECKED	 雅鈦企業有限公司 Aec Connectors Co., Ltd.
-	gasket	2	silicone	red				
-	c ring	2	steel	none				
-	contact pin	1	beryllium copper	gold (3u")			DRAWN <i>Jordan</i>	TITLE 2.92mm Male TO Male ADAPTOR
-	body b	1	SUS303	passivated				DRAWING NO. ADT-3013S-KS15IP-KS15IP
-	insulator	1	PEI	nature			DATE 2022. 02. 08	FILE NO. DRAWING\RF\ADTPTOR\ADT-3013S-KS15IP-KS15IP
-	body a	1	SUS303	passivated				
NO.	Description	Unit	Materials	Finish	Drawing No.	SCALE 5 : 1	UNIT	MM