

No.	DATE	DESCRIPTION	REV	REMARK : RoHS REQUIREMENT APPLIED (符合RoHS)	DATE	DRAWING NO.

P.C.B. MOUNTING PATTERN
(印刷电路板模式)

Electrical Specification:
1.Impedance : 50 ohm
2.Frequency Range : DC ~40 GHz
3.VSWR : 1.35:1 max.

NOTE : The specifications is only for connector.
Performance will very baesd on PCB layout.

Top view dimensions: 5.10, 7.37±0.05, 0.38±0.03.

Side view dimensions: 5.10, 7.37±0.05.

Front view dimensions: 4.16±0.10, 3.18, 4.06, 2-1.89, 2-0.19, 2-0.38, 2-1.14, Ø6.35.

S 1 : 1

-						DIMENSIONS ARE IN MILLIMETERS UNLESS OTHRWISE PECIFIED TOLERANCES (一般公差) 0.5~6 = ±0.2 >6~30 = ±0.4 >30~120 = ±0.6 >120~315 = ±1 >315~1000 = ±1.6 ANGLES(角度) = ±5°	CHECKED	雅鈦企業有限公司 Aec Connectors Co., Ltd.
-								
-								
-								
-	contact pin	1	brass	gold(3u")			DRAWN Owen	TITLE SMP MALE EDGE MOUNT (FULL DETENT)
-	insulator	1	PTFE	white				DRAWING NO.
-	body	1	brass	gold			DATE 2024. 12. 26	SP-1004GTG-SL0015
NO.	Description	Unit	Materials	Finish	Drawing No.	SCALE 6 : 1		FILE NO. DRAWING\RF\SP\SP-1004GTG-SL0015
						UNIT		
						MM		