

No.	DATE	DESCRIPTION	REV	REMARK : RoHS REQUIREMENT APPLIED (符合RoHS)	DATE	DRAWING NO.

Electrical Specification:

- 1.Impedance : 50 ohm
- 2.Frequency Range : DC ~ 40 GHz
- 3.VSWR : < 1.25

S 1 : 1

-						DIMENSIONS ARE IN MILLIMETERS	CHECKED	 雅鈦企業有限公司 Aec Connectors Co., Ltd.			
-											
-	c ring	1	beryllium copper	gold		UNLESS OTHRWISE PECIFIED TOLERANCES (一般公差) 0.5~6 = ±0.2 >6~30 = ±0.4 >30~120 = ±0.6 >120~315 = ±1 >315~1000 = ±1.6 ANGLES(角度) = ±5°	DRAWN <i>Owen</i>	TITLE			
-	contact pin	1	beryllium copper	gold (3u")				2.92mm Female TO SMP Female ADAPTOR			
-	body b	1	beryllium copper	gold			DRAWING NO.				
-	insulator	1	PEI	nature			ADT-3017S-KS25IP-SP25IG				
-	body a	1	SUS303	passivate			FILE NO. DRAWING\RF\ADTPTOR\ADT-3017S-KS25IP-SP25IG				
NO.	Description	Unit	Materials	Finish	Drawing No.	SCALE	5 : 1	UNIT	MM	DATE	2021. 07. 08