



28' MOBILE DISHWASHING TRAILER

D024

The 28' Mobile Dishwashing Trailer is a fully equipped, high-capacity mobile unit designed to handle commercial dishwashing needs in temporary, remote, or off-site locations. Engineered for efficiency, reliability, and compliance with industry standards, this unit features a Hobart high-temp conveyor dishwasher, stainless steel prep areas, and a tankless hot water system to ensure continuous operation. Built with premium insulation, LED lighting, and triple 7,000 lb axles, this trailer is both durable and easy to deploy. With NSF, UL, NFPA, and DOT approvals, the 28' Mobile Dishwashing Trailer is ideal for disaster relief, special events, military field operations, and commercial catering setups requiring large-scale dishwashing capabilities.

See back for specifications





SPECIFICATIONS

TRAILER SPECIFICATIONS

Overall Length: 28'
Overall Width: 8.5'
Deck Height: 35"
Tongue Weight: Approx. 4,200 lbs
Axles: Triple 7,000 lb axles with aluminum rims
Insulation: Full insulation in floors, walls, and ceiling

Full LED trailer lighting
(5) vapour-sealed fluorescent lights
Doors: Two exit doors
Electrical Features:
(2) 5,000-watt wall heaters
Fire exit lights
Wall-mounted 20-amp circuits above work tables
Certifications: ESA, NFPA, UL, NSF, DOT Approved

PRODUCTION EQUIPMENT

Dishwasher: Hobart CL44E high-temp conveyor dishwasher with booster heater
Workstations: (2) Stainless steel work tables

Sinks:

Three-compartment sink
Hand wash sink with towel and soap dispenser
Water System: Tankless "On Demand" hot water system

UTILITY REQUIREMENTS

Electrical Requirements:

Power Panel: 400A, 3-phase, 120/208V*
*Actual draw for the unit is between at full load.
Connection: Cam Connection

Connection Requirements:

Fresh Water: ¾" food-grade fresh water line
Grey Water Disposal: 3" grey water disposal line
Propane Connection

