

PREMIUM GROUNDCOVERS
POLYPROPYLENE WOVEN FABRIC

TECHNICAL PARAMETERS	STANDARD	UNIT	
Square weight	EN 965	G/M ²	100
Tensile strength Warp / Weft direction	EN ISO 10319	KN/M	20 / 14
Elongation at break Warp / Weft direction	EN ISO 10319	%	13 / 12
CBR – puncture resistance	EN ISO 12236	N	2350
Construction per 10cm in Warp / Weft direction			109 / 37
HYDRAULIC PROPERTIES			
Opening size O ₉₀	EN ISO 12956	MM	0,2
Water permeability h = 100 mm (10°C)	EN ISO 11058	L/M ² .S	20

ROLLS SIZES

Length of roll	As requested – standard lengths 100 lm or 1000 lm
Width of roll	50, 105, 130, 150, 165, 210, 330, 420 and 525 cm

UV STABILIZATION

Color / kLy	BLACK 750KLY	BLACK-GREEN 650KLY	BLACK-BROWN 650KLY	WHITE 650KLY
Central Europe - years	6	5	5	5

Above technical data are mean values based on production and independent institute tests for guidance only.

PLEASE BE ADVISED OF THE FOLLOWING RECOMMENDATIONS;

- The fabric must be installed on a surface cleaned of rocks and weeds.
- Use of certain pesticides, herbicides, fungicides and other chemicals containing sulphur-, iron-, bromine and chlorine in addition to copper sulphates will affect the above-mentioned characteristics.



JUTA Holland
Grafietstraat 11, 8472 EB, Wolvega
The Netherlands

+31 (0) 561 613 114
info@juta-holland.nl
JUTA-HOLLAND.NL

PREMIUM GROUNDCOVERS POLYPROPYLENE WOVEN FABRIC

TECHNICAL PARAMETERS	STANDARD	UNIT	
Square weight	EN 965	G/M ²	130
Tensile strength Warp / Weft direction	EN ISO 10319	KN/M	21 / 21
Elongation at break Warp / Weft direction	EN ISO 10319	%	13 / 12
CBR – puncture resistance	EN ISO 12236	N	3000
Construction per 10cm in Warp / Weft direction			109 / 48
HYDRAULIC PROPERTIES			
Opening size O ₉₀	EN ISO 12956	MM	0,2
Water permeability h = 100 mm (10°C)	EN ISO 11058	L/M ² .S	20

ROLLS SIZES

Length of roll	As requested – standard lengths 100 lm or 1000 lm
Width of roll	330, 420 and 525 cm

UV STABILIZATION

Color / kLy	BLACK 750KLY	BLACK-GREEN 650KLY	BLACK-BROWN 650KLY	WHITE 650KLY
Central Europe - years	6	5	5	5

Above technical data are mean values based on production and independent institute tests for guidance only.

PLEASE BE ADVISED OF THE FOLLOWING RECOMMENDATIONS;

- The fabric must be installed on a surface cleaned of rocks and weeds.
- Use of certain pesticides, herbicides, fungicides and other chemicals containing sulphur-, iron-, bromine and chlorine in addition to copper sulphates will affect the above-mentioned characteristics.



JUTA Holland
Grafietstraat 11, 8472 EB, Wolvega
The Netherlands

+31 (0) 561 613 114
info@juta-holland.nl
JUTA-HOLLAND.NL