

Product leaflet

# Hose Reel 889 Stainless

Medium sized open stainless steel hose reel.



## Hose Reel 889 Stainless





- ✓ All components in stainless steel and chemically resistant composite.
- ✓ Open design for ease of cleaning.
- ✓ Outlet position can be adjusted through 120° for optimum pull-out and pull-in angle.

Fitted with slightly larger drums and are therefore able to take a little longer hose than Series 888. These reels are ideal in environments with high humidity, where hygiene is of the utmost importance or where there is a risk of chemical attack. Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

## Hose Reel 889 Stainless

Certifications	CE
Connection hose length (m)	1
Colour	Stainless
Corrosion resistance	Stainless steel
Electric/Spring driven	Spring














## Models

	Item no	Media	Delivered with hose	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	Type of hose	Distribution hose length (m)	Diameter, connection hose (mm)
	30803589	Water	No	12.5	2	14	15			
	30803689	Water	Yes	12.5	2	18		E	15	12.5
	30803789	Water high pressure	No	10	25	11	20			
	30803889	Water high pressure	Yes	10	25	18		G	20	10




## Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone

## Accessories

	Accessory	Item no
	Roller guide	30341550
	Pivoting bracket.	30372407
	Pivoting bracket ss.	30372408
	Water gun in chromium plated brass. Max. temperature 95°C	30400110
	Water gun in stainless steel 316. Max. temperature 95°C	30400210
	Watergun EX in stainless steel 316. Max. temperature 95°C	30400211
	Water gun in stainless steel 316. Max. temperature 95°C	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710

## Accessories

	Accessory	Item no
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl. coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl. coupl. 1/2(m)-3/4(f) SS	30432010

