

Specification:

Payload: 3000 kg

Gross Engine Power: 32.4 kW (43.2 hp)
Max Skip Capacity: 1950/1870 Litres


Features:

- Perfectly sized for small or congested civil and commercial work sites.
- Economical earthmoving solution.
- 4WD for the worst ground conditions.
- Large heaped skip capacities.
- Tough designs and fabrications to keep you working in the toughest of conditions.
- High ground clearance, low centre of gravity for superb stability and site accessability.
- Power Swivel (PS) enables effective placement of load to either side useful for trench filling or small sites.

Specifications

Performance	
Payload (kg)	3000
Unladen weight (kg)	2550
Skip capacity - Water (Itr)	1000
- Struck (Itr)	1500
- Heaped (ltr)	1870
Engine	Hubota V2203M
- Net power - HW (hp)	32.4 [43.2]
- Capacity	2197cc
- Maximum Torque	145 Nm
Tyre Size	11.5/80x15.3x8plq
Drive	3/1 Manual - permanent 4WD
Max travel speed - kph	19.0
Gradeability	257.
Fuel tank capacity	37 Litres
Hydraulic tank capacity	37 Litres

Dimension (mm)



Dimension (mm)		PS3000
A	Total length	3850
В	Total width (not shown)	1860
C	Height to top of steering wheel	1860
D	Wheelbase	1950
E	Height to front lip of skip (untipped)	1500
F	Ground clearance	300
G	Height to top of ROPS (raised)	2680
H	Height to front lip of skip (tipped)	1100
	Turning radius to outside of skip	4665mm
	Steering angle	+/- 30°
	Oscillation	+/-10.5°
	Tipping type	Sшivel

Other sizes available

Sizes from left to right: 1000kg, 3000 kg, 6000kg and 9000 kg (not shown)

