NATURE

INDOOR & OUTDOOR CARPETS by balta

# Pampas Herringbone 1522/1529

| | |
|---|---|
| Construction | Flatweave - Felt Slip Resistant |
| Pile Content | 100% PP |
| Pile Weight | 1100 gr/m² |
| Total Weight | 1800 gr/m² |
| Total Height | 7.5 mm |
| Points | 95400/m² |
| Widths available | 4 metres |
| Pattern repeat | 26,10(W) x 2,33(H) cm |
| Light Fastness | ≥ 5-6 |
| Sound Insulation | ≥ 22 dB |
| Tog Rating | 1,2 |
| Fire Class | EFL-s1 (EN 13501-1) |

EN14041

CE UK CA

26

Balta Carpets - Wakkensteenweg 2
BE - 8710 Sint-Baafs-Vijve

**DOP: 1010#BC0AEL**

Textile Floor Covering EN 1307

En DL PCP NA HCHO DS

22

OEKO TEX® STANDARD 100 1803035 Centexbel

ANTI-SKID FELT BACKING · 20 YEAR WEAR PROMISE · EASY TO CLEAN · LIFETIME STAIN PROMISE

NATURAL FLOOR WEATHER SAFE® INSIDE & OUTSIDE · UNDERFLOOR HEATING · WOVEN QUALITY & DESIGN

**INDOOR/OUTDOOR**

**INSTALLATION** : The Weathersafe yarn of NATURE carpets means that it can be installed indoors or outdoors. When installing Nature Carpets outdoors, you should follow the same rules and make sure the surface on which your installing should be dry, smooth, clean, sound and without cracks or dust. NATURE carpets cannot be installed directly onto patio or paving stones, decking or other unprepared outdoor surfaces.

**MAINTENANCE** : Outdoor carpets attract a lot of dirt, especially in an area that's used often. While vacuuming and professional cleaning are the best methods for cleaning carpets indoors, NATURE carpets can withstand all-types of cleaning, including pressure washing and hosing. Remember these helpful tips for caring for your Nature carpet outdoors:
https://www.naturecarpet.com/fitting-care

**THE COMPANY RESERVES THE RIGHT TO MODIFY SPECIFICATIONS AND ALTER RAW MATERIALS RELATIVE TO IMPROVING PERFORMANCE WITHOUT NOTICE.**

**Wakkensteenweg 2, 8710 Sint-Baafs-Vijve, Belgium, T +32 (0)56 62 22 11, info@baltagroup.com, www.baltagroup.com**

07/2026

balta

# Pampas
## Herringbone 1522/1529




▲ 1522 / 1020



▲ 1522 / 1020



▲ 1529 / 1022



▲ 1529 / 1025