



your best alliance for compliance™

Fire & Safety Products

Construction Range



2025-2026

 Fire Safety

 Call Systems

 Access & Security

 DDA Compliance

Welcome

Welcome to the 2025-26 Edition Fixfire® Fire & Safety Products Construction Range catalogue

Fixfire® provides a complete range of specialist products and services to facilitate Construction Site Fire & Life Safety. This latest edition is packed with proven rugged products from Fire Extinguishers and ancillaries to Passive Fire Protection Products including Fire & Smoke Seals and Intumescent Pipe Collars. Most items are available for next day delivery or installation/maintenance by our engineers. Our helpful Sales Team is always available to provide advice and product support. We look forward to serving you.

The Fixfire® Sales Team



FIRE ALARM RENTAL

HireAlarm™ is a Fire Alarm rental service from Fixfire® for Construction/Interiors Contractors.

Based on the FireSentry range (see page 14), systems can be configured to suit your specific requirements including Fire Detection and Control Panel options.

HireAlarm™ includes initial site delivery/installation and training and additional visits to carry out maintenance or system modifications eg. during construction phases. On completion the equipment is decommissioned and removed.

So, for cost effective reliable Fire Alarm hire choose HireAlarm™ from Fixfire®!

SECTION ONE

FIRE FIGHTING EQUIPMENT

3 Fire Extinguishers

6 Fire Blankets

7 Fire Buckets & Fire Beaters

8 Fire Extinguisher Mounting, Storage & Protection

8 Brackets

9 Extinguisher Cabinets

10 IDENTiStand Extinguisher Stands

11 IDENTiPlate Extinguisher Backplates

12 TuffStands™

13 Extinguisher Stands

14 Extinguisher Trolleys

15 Sanitiser Station Trolleys

16 Extinguisher & Hose Reel Covers

17 Fire Detection & Warning

17 Fire Sentry Site Alarms

22 Self Contained Alarms



To view our complete range, ask for a copy of our 2025-2026 Fire & Safety Products catalogue

SECTION TWO

MEANS OF ESCAPE PRODUCTS

23 Escape Door Furniture

23 Panic hardware

25 Fire Resistant/Intumescent Products

25 Fire & Smoke Seals

26 Batwing® Seals

27 Glazing Seals

29 Air Transfer Grilles

30 Mastic, Expanding Foam & Fire Retardant Spray

31 Pipe Seals

32 Intumescent Fire Pillows & Downlighter Covers

33 Fire & Safety Signs

33 Standard Signs - Non-Photoluminescent

35 Standard & Post Mounting Signs - Non-Photoluminescent

36 Fire Extinguisher Type Signs - Photoluminescent

37 TuffSigns™ Non-Photoluminescent

38 Sign Mounting Accessories

40 Building Evacuation Products

40 Evacuation Chairs

41 Fire Log Book & Cabinet



Tried and trusted, the Ultimex™ range of fire extinguishers by Fixfire® is built to exacting and stringent standards for reliability, longevity and superior performance.



Guaranteed for
ten years (Subject to T's & C's)



Fitted with
pressure gauge



Polyester
coated



Kite Mark Certified
& CE marked



Easy to understand
instructions



Fitted with robust
plastic skirts
(freestanding versions)

Water

Part No.	Fire Rating	H (Mm)	Overall W (Inc. Hose) (mm)	Weight (Kg)
X/W9	21A	522	320	13.29

X/W9

- Internal polythene lining
- Squeeze grip operation
- Approved to BS EN3
- Supplied complete with bracket.



Product Technical Tip



As with all of the larger portable Fire Extinguishers, you should consider whether the wall construction is adequate to withstand the weight of the appliance. Extinguisher stands should be considered for cavity wall applications.



X/W9

YOU MAY ALSO
REQUIRE ...

FIND ON
P6

Fire Blankets



Foam

Part No.	Fire Rating	H (Mm)	Overall W (Inc. Hose) (mm)	Weight (Kg)
X/F2	8A 55B	395	150	3.81
X/SF3	13A 89B	426	150	3.81
X/F6	21A 144B	560	300	9.65
X/F9	271 183B	522	340	13.24

- Spray nozzle
- Internal polythene lining
- Squeeze grip operation
- Approved to BS EN3 including 35kV dielectric test
- Supplied complete with bracket
- X/F2 supplied with transport bracket.



X/F2

X/SF3

X/F6

X/F9



Tried and trusted, the Ultimex™ range of fire extinguishers by Fixfire® is built to exacting and stringent standards for reliability, longevity and superior performance.



Guaranteed for
ten years (Subject to T's & C's)



Fitted with
pressure gauge



Polyester
coated



Kite Mark Certified
& CE marked



Easy to understand
instructions



Fitted with robust
plastic skirts
(freestanding versions)

ABC Dry Powder

Part No.	Fire Rating	H (mm)	Overall W (inc. hose) (mm)	Weight (Kg)
X/P1	8A 55B	340	135	1.67
X/P2	13A 70B	370	150	3.62
X/P4	21A 113B	420	293	6.4
X/P6	34A 233B	503	260	8.94
X/P9	43A 233B	582	317	12.98

- Multi purpose application
- Squeeze grip operation
- Approved to BS EN3
- Supplied complete with bracket
- X/P1 & X/P2 supplied complete with transport bracket.



X/P1

X/P2

X/P4

X/P6

X/P9

CO₂

Part No.	Fire Rating	H (mm)	Overall W (inc. hose) (mm)	Weight (Kg)
X/C2	34B	490	180	4.91
X/C5	70B	750	310	11.43

- Aluminium alloy construction
- Harmless to machinery
- Squeeze grip operation
- Approved to BS EN3
- X/C2 supplied with frost free horn
- X/C5 supplied with hose and horn
- Supplied complete with bracket.



X/C2


X/C5



YOU MAY ALSO
REQUIRE ...

FIND ON
P8

Transport Brackets





Tried and trusted, the Ultimex™ range of fire extinguishers by Fixfire® is built to exacting and stringent standards for reliability, longevity and superior performance.



Guaranteed for
ten years (Subject to T's & C's)



Fitted with
pressure gauge



Polyester
coated



Kite Mark Certified
& CE marked



Easy to understand
instructions

CO₂

Part No.	Fire Rating	H (mm)	Overall W (inc. hose) (mm)	Weight (Kg)
X/C2	34B	490	180	4.91
X/C5	70B	750	310	11.43

- Aluminium alloy construction
- Harmless to machinery
- Squeeze grip operation
- Approved to BS EN3
- X/C2 supplied with frost free horn
- X/C5 supplied with hose and horn
- Supplied complete with bracket.



X/C2



X/C5

YOU MAY ALSO
REQUIRE ...

FIND ON
P7

Fire Buckets



Wet Chemical

Part No.	Fire Rating	H (mm)	Overall W (inc. hose) (mm)	Weight (Kg)
X/WC6	13A 133B 75F	662	310	12.13

- Internal polythene lining
- High performance fire rating
- Squeeze grip operation
- Approved to BS EN3
- Supplied complete with bracket.



Product Technical Tip



We recommend the installation of a 6 litre Wet Chemical extinguisher, 2Kg CO₂ extinguisher and a suitably sized Fire Blanket to provide protection for Commercial Kitchens.



X/WC6

TYPICAL COMMERCIAL
KITCHEN APPLICATION





Fire Blankets Portable

Fixfire® offers premium quality Fire Blankets which are Kite Marked and BAFE Certified.



5 year
guarantee



Kite
Marked



One piece
construction



Made
in UK

Portable

Part No.	Description
FB/110	1.1M x 1.1M
FB/120	1.2M x 1.2M
FB/175	1.75M x 1.75M
FB/180	1.2M x 1.8M

- Durable Single piece moulded plastic cover
- Ideal for use in kitchens and workshops
- High quality long life cloth
- Easy to use
- Kitemark certified to BSEN 1869:1997
- Wide range of sizes available.

Product Technical Tip



Fire Blankets should be mounted so as to position the hand hold device approximately 1.5 m from the floor.

YOU MAY ALSO
REQUIRE ...

FIND ON
P36

ID Signs



FB/110
FB/120



FB/175
FB/180



Fire Buckets & Fire Beaters

Fire Buckets & Accessories

Our range of fire buckets and beaters provide a traditional tried and tested method of fire fighting.

Metal Fire Bucket

Part No.	Description
X/MFB	Metal Fire Bucket
X/MFBL	Metal Fire Bucket Lid
X/FBB	Fire Bucket Bracket

- Suitable for wide range of applications, from garage forecourts to science labs
- Choice of bucket style to meet every requirement
- 10 Litre capacity
- Hanging bracket available separately
- Bucket lid supplied separately to bucket.



X/MFB

YOU MAY ALSO REQUIRE ...

FIND ON
P14

Site Trolleys




Plastic Fire Bucket

Part No.	Description
X/FB	Plastic Fire Bucket
X/FBL	Plastic fire bucket Lid
X/FBB	Fire Bucket Bracket

- Suitable for wide range of applications, from garage forecourts to science labs
- Choice of bucket style to meet every requirement
- 10 Litre capacity
- Hanging bracket available separately
- Bucket lid supplied separately to bucket.



X/FB



X/FBB

Fire Sand Bin

Part No.	Description
X/FSB	Fire Sand Bin

- Designed for bulk storage of fire sand and other fire fighting compounds
- Robust moulded plastic construction
- Corrosion proof
- Dimensions: H570 x W655 x D500.



X/FSB

Flamezorb

Part No.	Description
X/FZS	Flamezorb Fire Sand, 2Kg Bag

Flamezorb Fire Sand

- Superior absorbent properties to sand
- Lightweight - 2kg bag fills a 10L bucket
- Easy to clear up and dispose of
- Fully conforms to BS476 part 7 class 2t



X/FZS

Fire Beater

Part No.	Description
X/FBT	Fire Beater, 2kg Bag

Fire Beater

- Solid hardwood handle
- Industrial grade rubber beater for excellent knockdown
- 1200mm long handle.
- Beater size 310mm x 450mm



X/FBT



Fire Extinguisher Mounting, Storage & Protection Brackets

Our range of extinguisher brackets offers a simple, effective method of safely locating all types of fire extinguishers.

Standard Extinguisher Brackets

Part No.	Description
X/JB	J Bracket
X/LB2	2Kg CO ₂ Size Lug Bracket
X/LB5	5Kg CO ₂ Size Lug bracket

J Bracket


- Universal style
- Galvanised finish.

2Kg CO₂ Size lug Bracket

- Suits all makes of 2Kg CO₂ extinguisher
- Galvanised finish.

5Kg CO₂ size lug bracket

- Suits all makes of 5Kg CO₂ extinguisher
- Galvanised finish.



Transport Extinguisher Brackets

Part No.	Description
X/TB/JB	Transport J Bracket
X/TB/LB2	2Kg CO ₂ Size Transport Bracket
X/TB/LB5	5Kg CO ₂ Size Transport Bracket

Transport J bracket

- Universal style
- powder coated finish
- Supplied complete with webbing strap and quick release buckle

2Kg CO₂ size transport bracket

- Suits all makes of 2Kg CO₂ extinguisher
- Galvanised finish
- Supplied complete with webbing strap and quick release buckle

5Kg CO₂ size transport bracket

- Suits all makes of 5Kg CO₂ extinguisher
- Galvanised finish
- Supplied complete with webbing strap and quick release buckle



Product Technical Tip



In order to comply with BS 5306 part 8 extinguishers should be so mounted that the carrying handle is 1 metre above the floor. Smaller extinguishers of under 4kg total weight should be mounted with the handle at 1.5 metres above the floor.

X/TB/LB2 TRANSPORT BRACKET IN WALL MOUNTING APPLICATION





Fire Extinguisher Mounting, Storage & Protection

Extinguisher Cabinets

TuffCabinets™ is a complete range of fire equipment cabinets designed to be strong, lightweight, and weatherproof. Ideal for storage of all types of fire extinguishers and other associated equipment.



Robust &
Durable



Weatherproof



High
Visibility



User-
friendly



Made in
UK

tuffCABINETS™

...safe, secure & protected

Wall Mounting Cabinets

Part No.	Description	Dimensions
X/SEC/M	Single Extinguisher Cabinet Up to 6 Kg/litre Extinguisher Capacity	700H x 320W x 255D
X/SEC/L	Single Extinguisher Cabinet Up to 9 Kg/litre Extinguisher Capacity	830H x 330W x 265D
X/DEC	Double Extinguisher Cabinet	720H x 585W x 270D
X/TEC	Double/Triple Extinguisher Cabinet	850H x 565W x 375D
X/QEC	Quad Fire Equipment Cabinet	900H x 930W x 420D
/K	Keylock	

- Totally corrosion resistant design
- Can be wall, post or vehicle mounted
- Clear polypropylene vision panels in door
- Complete with internal equipment retaining straps
- Robust rotationally moulded construction for high impact resistance.



X/DEC



X/DEC/K



X/QEC

Vehicle Mounting Cabinets

Part No.	Description	Dimensions
X/VEC/M	Medium Vehicle Extinguisher Cabinet Up to 6 Kg/litre Extinguisher Capacity	650H x 260W x 275D
X/VEC/L	Large Vehicle Extinguisher Cabinet 9 Kg/litre Extinguisher Capacity	750H x 300W x 300D
X/FKM	Fixing Kit for X/VEC/M, 30° or 60°	N/A
X/FKL	Fixing Kit for X/VEC/L, 30° or 60°	N/A


- Totally corrosion resistant design
- Kits available for easy vehicle mounting
- Complete with internal equipment retaining spring or strap.
- Robust rotationally moulded construction for high impact resistance.



X/VEC/L



X/VEC/L mounted on lorry



Fire Extinguisher Mounting, Storage & Protection

Extinguisher Stands

Not sure how to mount your extinguishers? - unsuitable walls or no wall space?

The IDENTiRange™ achieves a consistent installation whatever the situation.



Robust &
Durable



High
Visibility



Obvious if extinguisher
is missing




Made
in UK

IDENTiStand™

Extinguisher Stands

Part No.	Description
X/IS1	Single Stand
X/IS2	Double Stand

- All metal construction robust extinguisher stand
- Holes in feet for floor mounting
- Ideal for any situation where there is no suitable wall surface.



X/IS2 DOUBLE IDENTISTAND
INSTALLED ON MEZZANINE



X/IS2

IDENTiRange™ - the success story...

When a major American Automotive Manufacturer approached Fixfire® in 1994 to mount Fire Extinguishers in awkward locations at their factory; Fixfire® rose to the challenge and set to work to develop the IdentিRange.

The outcome exceeded all expectations - not only were IdentিRange™ products installed throughout the factory - the IdentিRange™ quickly gained popularity and today, 1000's of IdentিRange™ products are installed in Industrial, Commercial and Healthcare premises throughout the UK.

IMPORTANT ORDERING INFORMATION



When Ordering Identি Range products, remember to order the appropriate IdentিLabel extinguishant ID sign and Brackets separately.



Fire Extinguisher Mounting, Storage & Protection

Extinguisher Stands

Extinguishers missing / moving? The IDENTIrange™ is the solution for you...



Robust &
Durable



High
Visibility



Obvious if fire
extinguisher is missing





Made
in UK

IDENTIPlate™

Extinguisher Backplates

Part No.	Description
X/MSBP	Midi Single Backplate
X/MDBP	Midi Double Backplate
X/SBP	Single Backplate
X/DBP	Double Backplate

- Wall mounting backplate
- Double/Single versions
- Standard and midi size where height is restricted.



X/DBP DOUBLE IDENTIPLATE MOUNTED ON BRICK WALL



IDENTILabel™

- Extinguisher type label
- Fits in dedicated section.

All 135H x 135W (mm)

Part Number	Description
S/IL/W	Identilabel Water Extinguisher Label
S/IL/F	Identilabel AFFF Foam Spray Extinguisher Label
S/IL/P	Identilabel Dry Powder Extinguisher Label
S/IL/C	Identilabel CO ₂ Extinguisher Label
S/IL/WC	Identilabel Wet Chemical Extinguisher Label





Fire Extinguisher Mounting, Storage & Protection

TuffStands™

TuffStands™ are available in a choice of styles and finishes, TuffStands™ overcome the problems associated with wall-mounting appliances.



Architecturally
pleasing



Moulded well in base to
support extinguisher



Skirting board recess
at rear of base



Dedicated extinguisher
ID sign panel



Made
in UK

tuffSTANDS™
...better looking, longer lasting!

Single / Double TuffStand

Part No.	Description	Dimensions
X/TS1/?	2 Part Single Extinguisher TuffStand	654H x 290W x 300D
X/TS2/?	2 Part Double Extinguisher TuffStand	654H x 290W x 300D
Colours	Add: /R/2 Red, /MG/2 Marble Grey, C/2 Cream	

- Suitable for all shop and office environments
- Ideal for use where wall mounting of extinguishers is not suitable
- Robust rotationally moulded construction
- Lightweight 2 part construction for ease of installation and storage
- Range of signs available to suit
- Can accommodate up to 9Kg size extinguishers
- Available in red, marble grey or cream finishes.



X/2P/TS1MG



X/2P/TS2R

Midi TuffStand

Part No.	Description	Dimensions
X/MTS1/?	Single Midi Tuffstand	620H x 310W x 265D
X/MTS2/?	Double Midi Tuffstand	620H x 310W x 265D
Colours	Add: /R/2 Red, /MG/2 Marble Grey, C/2 Cream	

- Compact design suitable for all shop and office environments
- Ideal for use where wall mounting of extinguishers is not suitable
- Skirting board recess built in
- Robust rotationally moulded construction
- Single stand designed to accommodate 1 x 6L/Kg size extinguisher
- Double stand designed to accommodate 1 x 6L/Kg size extinguisher and 1 x 2Kg CO₂ extinguisher
- Range of signs available to suit
- Available in red, marble grey or cream finishes.



X/MTS1/R



X/MTS2/C

Standard Colours		
Cream	Red	Marble Grey



RECEPTION
APPLICATION




YOU MAY ALSO
REQUIRE ...

FIND ON
P36

Photoluminescent
Signs





Fire Extinguisher Mounting, Storage & Protection

Extinguisher Stands

Fixfire® offer a range of high quality versatile and durable site safety stands and fire points, designed to provide a focal safety point. Add fire safety signs and site alarms to create a full fire safety point for any building site.



Robust &
Durable



High
Visibility



Made in
UK



Obvious if extinguisher
is missing

Site Safety Stand

Part No.	Description
X/SS2	Fire Safety Stand

- Can accommodate up to 3 extinguishers
- Heavy duty steel construction
- Powder coated finish for greater corrosion resistance
- 750x600mm rigid foamboard sign area
- Creates a central fire safety point for all building sites and factories



X/WMFP Wheeled Mobile Fire Point

Product Technical Tip
<p>Extinguishers should be sited in such a way that it is not necessary to travel from the site of any fire to reach an extinguisher further than 30 Metres in the case of a class A risk.</p>

Identipoint

Part No.	Description
X/IP2	Identipoint Double Extinguisher Stand

- All metal construction robust extinguisher stand
- Holes in feet for floor mounting
- Incorporates 'Boxer Alarm' self contained fire alarm call point
- 600mm W x 1340mm H.



X/IP2

IMPORTANT ORDERING INFORMATION
<p>When Ordering Identipoint products, remember to order the appropriate Identilabel extinguishant ID sign and Brackets separately</p>



Fire Extinguisher Mounting, Storage & Protection

Extinguisher Trolleys

Our range of site trolleys complements the site safety stand range, offering a durable and versatile fire point solution where more mobility is called for. Site alarms can also be incorporated to create a full safety point.



Robust & Durable



High Visibility



Made in UK



Obvious if extinguisher is missing

Extinguisher Trolleys

Part No.	Description
X/DET	Double Extinguisher Trolley
X/TETB	Triple Extinguisher Trolley With Bucket Bracket
X/DCT	Double Extinguisher Tuffcabinet Trolley
X/FKMT	Rotationally Molded Fire Point Trolley

Double & Triple Extinguisher Trolley

- Accommodates 2 extinguishers
- Robust Steel frame construction
- Heavy duty site wheels built in
- Corrosion resistant powder coated finish
- Mounting available for rotary hand bell (supplied separately)
- Integral bucket bracket available (optional extra)
- Versatile and mobile fire point for all building sites.

Extinguisher TuffCabinet Cabinet Trolley

- Robust site trolley and cabinet
- Can accommodate 2 extinguishers up to 9kg size each
- Lockable door with integral keybox for added security
- Excellent weatherproofing for extinguishers.

FireKart Double Fire Extinguisher Trolley

- Robust rotationally moulded trolley.
- Can accommodate 2 extinguishers up to 9 Kg size each
- And a Fire Bucket.
- Top Panel section to fix site Fire Alarm Device and extinguisher ID signs.



X/DET



X/TETB



X/FKMT



X/FKMT FireKart shown with Fire Extinguishers, Fire Bucket and FireSentry Fire Alarm fitted (order these items separately)



X/DCT



Fire Extinguisher Mounting, Storage & Protection

Sanitiser Station Trolleys

Our Sanitiser Station Trolleys offer a durable and versatile combined Fire and Safety solution. These units can be customised with your branding, different signage and alternative Fire Alarm devices. Please enquire for more information.



Robust & Durable



High Visibility



Made in UK



Customisable



COVID-19 Product

Sanitiser Station Trolleys


Part No.	Description
X/SHG05	Mobile First Aid Point with Sanitiser Station complete with secure, lockable Storage Cabinet
X/SH05	Mobile Double Fire Extinguisher Point complete with Sanitiser Station

Mobile First Aid Point with Sanitiser Station

- Large secure cabinet with shelf for equipment/supplies storage
- 2-year manufacturer's warranty
- Can be customised with your branding
- Optional backboard for Fire Alarm device
- Highly mobile – fits through a standard doorway

Mobile Double Fire Extinguisher Point complete with Sanitiser Station

- Fits through a standard doorway
- 2-year manufacturer's warranty
- Can be customised with your branding
- Optional backboard for Fire Alarm device



Ask for a copy of our
COVID-19 Safety
Signage Catalogue
or download here:

[DOWNLOAD](#)



X/SHG05



X/SH05



Fire Extinguisher Mounting, Storage & Protection

Extinguisher & Hose Reel Covers

Fixfire® equipment covers are a simple and cost effective method of protecting extinguishers and hose reels from tampering, damage and corrosion.



High
Visibility



Made in
UK



East to
Fit

Extinguishers Covers

Part No.	Description
X/FEC/S	Small Cover
X/FEC/L	Large Cover

- Easily visible
- Full length vision panel
- 2 sizes to suit all types of extinguisher
- Velcro straps for ease of fitting.



X/FEC/S



X/FEC/L

Hose Reel Cover

Part No.	Description
X/HRC	Hose Reel Cover

- Designed to fit most 19mm and 25mm fire hose reels
- Easy and quick to install
- Printed with fire hose decal for high visibility.



X/HRC



Fire Detection & Warning

Fire Sentry Site Alarms

Fixfire® offer a comprehensive range of battery operated fire alarms suitable for building sites where temporary installation is required.



Loud!



Simple installation



Battery operated



Robust Construction



Made in UK

Fire Sentry Self-contained/hardwire interlinkable

Hardwired, standalone or interlinkable site alarms

Part No.	Description
X/FS/MCP	Fire Sentry Manual Call Point

Fire Sentry Manual Call Point

- Easy Cable Free Installation
- Call Point Activated
- Resettable Call Point
- Call Point Key Supplied
- IP55 rated
- 110db Output
- 9v PP3 Battery Supplied
- Combined Sounder Strobe
- Link Upto 25 units using Bell Wire
- CE & LVD Approved
- Low maintenance costs



YOU MAY ALSO REQUIRE ...

FIND ON P32

Fire Exit Signs



Part No.	Description
X/FS/PB	Fire Sentry Push Button

Fire Sentry Push Button

- Easy Cable Free Installation
- Push Button Activated
- IP55 rated
- 110db Output
- 9v PP3 Battery Supplied
- Combined Sounder Strobe
- Link Upto 25 units using Bell Wire
- CE & LVD Approved
- Low maintenance costs

X/FS/MCP

X/FS/PB





Fire Detection & Warning

Fire Sentry Site Alarms

The versatile battery powered site Fire Alarm System.



108-119dB sounder



Wireless



Robust Construction



Made in UK



Available for Hire

Fire Sentry Wireless Control Units

The Fire Sentry wireless system provides a single expandable solution which is suitable for the smallest to the largest construction site. Individual Fire Sentry wireless devices can be connected together with or without a central monitor panel.

Part No.	Description
X/FS/BS	FireSentry™ Base Station
X/FS/BS/FKMT	FireSentry™ Combined Manual Call Point and Alarm Sounder/Beacon mounted on FireKart Double Extinguisher trolley

Fire Sentry Wireless Monitor

- Category 1 radio module
- Independently tested to ETSI-300-220-1
- CE, RoHs, EMC & RED Compliant
- 25mm Bright LED display unit
- Scratch resistant UV Decals
- Status LED
- 85dB Buzzer
- 40 Addressable Devices
- Automatic battery low indication
- Completely wireless operation
- "Plug & Play" simple self installation
- Low maintenance costs
- Silent range test facility
- IP55 Enclosure

FireKart Double Fire Extinguisher Trolley

- Robust rotationally moulded trolley.
- Can accommodate 2 extinguishers up to 9 Kg size each and a Fire Bucket.
- Top Panel section supports FireSentry device and extinguisher ID signs.



Part No.	Description
X/FS/MPLUS	Fire Sentry Wireless MonitorPlus

Fire Sentry Wireless MonitorPlus

This innovative and powerful Touch screen, full data-logging Base Station, is sure to offer the user unparalleled quality coupled with Fire Sentry's proven track record for reliability and uncomplicated operation. Informative data transfer, including full system history reporting, is available as standard at the touch of a button. Each device installed around your site can be configured to display its unique identity and location in Alpha Numeric format.

- Full Alpha Numeric device Identification
- First Aid monitoring function, as standard
- Innovative Touch Screen Operation
- Automatic Real Time system monitoring
- Fully printable system reporting
- On board real time Clock, with back up
- Five year on board SD card
- Standard USB export
- Mains with the option of Battery Back-up
- Compact unique desk top or wall mounting design
- Wipe down scratch resistant decals
- 85dB Buzzer

X/FS/MPLUS





Fire Detection & Warning

Fire Sentry Site Alarms

The versatile battery powered site Fire Alarm System.



108-119dB sounder



Wireless



Robust Construction



Made in UK



Available for Hire

Fire Sentry Wireless Field Devices

Part No.	Description
X/FS/CP/SB	FireSentry™ Combined Manual Call Point and Alarm Sounder/Beacon
X/FS/CP/SB/FKMT	FireSentry™ Combined Manual Call Point and Alarm Sounder/Beacon mounted on FireKart Double Extinguisher trolley
X/FSIP+/SK/SB	Site Alarm with Strike Knob actuator

Fire Sentry Wireless Call Point

- Manual Call Point with integral push button and lift up cover flap
- Easy to install
- Loud 118dB Siren
- Durable and robust construction
- Long lasting PP9 battery supplied with unit
- Suitable for use outside with IP65 rated switch
- 50mm Diameter switch makes for quick emergency operation
- 2 year manufacturers guarantee.

Fire Sentry IP+ Wireless Call Point

- Strike knob actuator
- Easy to install
- Loud 118dB Siren
- Durable and robust construction
- Long lasting PP9 battery supplied with unit
- Suitable for external use
- 50mm Diameter switch makes for quick emergency operation
- 2 year manufacturers guarantee.

FireKart Double Fire Extinguisher Trolley

- Robust rotationally moulded trolley.
- Can accommodate 2 extinguishers up to 9 Kg size each and a Fire Bucket.
- Top Panel section supports FireSentry device and extinguisher ID signs.



X/FS/CP/SB



X/FSIP+/SK/SB

Part No.	Description
X/FS/CP/SB/FA	FireSentry™ Combined Manual Call Point, Alarm Sounder/Beacon & First Aid Call button
X/FS/CP/SB/FA/FKMT	FireSentry™ Combined Manual Call Point, Alarm Sounder/Beacon & First Aid Call button mounted on FireKart Double Extinguisher trolley



X/FS/CP/SB/FA/FKMT



Fire Sentry RF Call Point with First Aid Function

- Category 1 radio module
- Independently tested to ETSI-300-220-1
- CE, RoHS, EMC & RED Compliant
- 108dB Sounder and LED strobe
- Scratch resistant UV Decals
- Status LED
- 40 Addressable Devices
- Automatic battery low indication
- Completely wireless operation
- "Plug & Play" simple self installation
- Low maintenance costs
- Silent range test facility
- IP55 Enclosure
- "First Aid Call" feature

FireKart Double Fire Extinguisher Trolley

- Robust rotationally moulded trolley.
- Can accommodate 2 extinguishers up to 9 Kg size each and a Fire Bucket.
- Top Panel section supports FireSentry device and extinguisher ID signs.

X/FS/CP/SB/FA



Fire Detection & Warning

Fire Sentry Site Alarms

The versatile battery powered site Fire Alarm System.



108-119dB sounder



Wireless



Robust Construction



Made in UK



Available for Hire

Fire Sentry Wireless Field Devices

Part No.	Description
X/FS/DS	Fire Sentry RF Automatic Smoke Detector

Fire Sentry RF Automatic Smoke Detector

- Automatic Smoke Detection
- Category 1 radio module
- Independently tested to ETSI-300-220-1
- CE, RoHS, EMC & RED Compliant
- New Easy-fix mounting
- IP68 Rated Antenna
- Link 40 Addressable Devices
- External lug for ceiling fixing
- Automatic battery low indication
- Completely wireless operation
- "Plug & Play" simple self installation
- Low maintenance costs
- Battery Supplied



X/FS/DS



NEW DESIGN

Part No.	Description
X/FS/DH	Fire Sentry RF Automatic Heat Detector

Fire Sentry RF Automatic Heat Detector

- Automatic Heat Detection
- Category 1 radio module
- Independently tested to ETSI-300-220-1
- CE, RoHS, EMC & RED Compliant
- New Easy-fix mounting
- IP68 Rated Antenna
- Link 40 Addressable Devices
- Automatic battery low indication
- Completely wireless operation
- "Plug & Play" simple self installation
- Low maintenance costs
- Battery Supplied



X/FS/DH



NEW DESIGN



Fire Detection & Warning

Fire Sentry Site Alarms

The versatile battery powered site Fire Alarm System.



108-119dB sounder



Wireless



Robust Construction



Made in UK



Available for Hire

Fire Sentry Text Master

	Description
X/FSR/GSM	Fire Sentry GSM "Text Master"

Fire Sentry GSM "Text Master"

- 15 Character Site description
- Text Upto 5 Mobile Phone Numbers
- O2 or Orange sim card is required
- Full Size SIM Card required
- Wireless connection to other "Synergy" Units
- Requires 110-240v AC supply
- IP67 Transformer Included
- IP65 Enclosure
- IP67 Antenna
- Indoor Use Only



X/FSR/GSM



Fire Sentry Accessories

Part No.	Description
X/FSR/RF	Fire Sentry Reset Fob

Fire Sentry Reset Fob

Suitable for:

- Fire Sentry TG Call Point
- Fire Sentry RF Call Point



X/FSR/RF

Part No.	Description
X/FSR/BAT1	Fire Sentry Wireless Battery Pack

Fire Sentry Wireless Battery Pack

Suitable for:

- Fire Sentry Wireless Call Point Monitors
- Fire Sentry Wireless Base Station Monitors
- Fire Sentry Wireless Sounder Strobe Monitors



X/FSR/BAT1

Part No.	Description
X/FSR/BAT2	?

Fire Sentry Detection Battery pack

Suitable for:

- Fire Sentry Smoke Detector
- Fire Sentry Heat Detector



X/FSR/BAT2



Fire Detection & Warning

Self Contained Alarms

Our comprehensive range of site alarms is designed to be robust and easy to use. From hand held to fixed alarms, stand alone to portable systems, we provide an evacuation alarm for every application.



Loud



High
Visibility



User
Friendly



Robust

Air Horns

Part No.	Description
X/PHE	Pump Action Air Horn
X/GHE	Gas Air Horn
X/GHR	Gas Air Horn Refill

Easy to use, portable horns with a wide range of applications.

Pump Action Air Horn

- Easy to use hand pump action
- No need for refills
- Always ready to go in an emergency.

Gas Air Horn

- Ideal for providing temporary alarm cover for building sites
- 200ml can - allows for multiple uses
- 110dB loud horn
- Non flammable gas
- Refills available.

Gas Air Horn Refill

- 200ml can
- Fits X/GHE



X/GHE



X/PHE

Rotary Hand Bell

Part No.	Description
W/1200	Rotary Hand Bell

Tried and tested means of raising the alarm.

Rotary Hand Bell

- Tried and tested robust design
- Bell sounds at 60dB at up to 35M
- Red coated diecast aluminium dome
- Diecast aluminium base plate
- Pre-drilled flange for simple installation.



W/1200

Boxer Alarm

Part No.	Description
X/BA	Boxer Alarm

Simple and cost effective site alarm.

Boxer Alarm

- Combined call point and sounder
- Battery operated, no mains required
- Resets with a simple key
- Use individually or link up to 12 units
- No glass to replace or spares required
- Drop down flag, illuminated LED and 85 dB sounder
- Light, compact, industry standard format



X/BA



Escape Door Furniture

Panic Hardware

The Fixfire® range of fire door panic hardware is designed with ease of use and high security in mind. Conforming to all relevant standards, to ensure you meet health and safety requirements without compromising building security.



Robust &
Durable



EN
Certified



User
Friendly



High
Security



Architecturally
Pleasing

Panic Hardware

Part No.	Description
H/297	Push Pad Door Rim Latch
H/296	Push Bar Door Panic Latch
H/294	Push Bar Single Door Panic Bolt
H/285	Push Bar Double Door Panic Bolt Set

Push Pad Door Rim Latch

- For single or double doors
- Non-handed
- Fire rated for use on timber and steel doors
- Surface mounted
- Adapter supplied for operating with a rim cylinder.



H/297



H/296

Push Bar Door Panic Latch

- For single or double doors
- Non-handed
- Fire rated for use on timber and steel doors
- Surface mounted
- Adapter supplied for operating with a rim cylinder
- Closed arm design.



H/294



H/285

Push Bar Single Door Panic Bolt

- For single or double doors
- Non-handed
- Fire rated for use on timber and steel doors
- Surface mounted
- Closed arm design.


Push Bar Double Door Panic Bolt Set

- For rebated doors
- 3 and 4 point locking available
- Non-handed
- Fire rated for use on timber and steel doors
- Surface mounted
- Closed arm design.

YOU MAY ALSO
REQUIRE ...

FIND ON
P34

Emergency Escape Signage





Escape Door Furniture

Panic Hardware

The Fixfire® range of fire door panic hardware is designed with ease of use and high security in mind. Conforming to all relevant standards, to ensure you meet health and safety requirements without compromising building security.



Robust & Durable



EN Certified



User Friendly



High Security



Architecturally Pleasing

Panic Hardware

Part No.	Description
H/284	Push Bar Double Door Panic Bolt Set (Non Rebated Doors)
H/298	Outside Access Device

Push Bar Double Door Panic Bolt Set (non rebated doors)

- For non rebated doors
- 4 point locking
- Non-handed
- Fire rated for use on timber and steel doors
- Surface mounted
- Closed arm design.

Outside Access Device

- Supplied with 2 keys and a 5 pin cylinder
- Suitable for use with our complete range of bolts and latches
- Non-handed
- Fire rated for use on timber and steel doors
- Surface mounted on the outside of the door using concealed machine screws
- Supplied as standard for doors up to 60mm thick
- Longer spindles and screws are available on request for door thicknesses over 60mm.



H/284

H/298

Panic Bolt Alarm Unit

Part No.	Description
H/304	Panic Bolt Alarm Unit

Panic Bolt Alarm Unit

- For use with the panic bolt, the alarm is activated when the panic device is operated, or an attempt is made to remove the cover, and de-activated by a key. The unit is operated by a 9V battery.

Product Technical Tip



You should check that your Fire Exit mechanisms are in good working order as part of a routine maintenance regime.



H/304




Fire Resistant/Intumescent Products

Fire & Smoke Seals

Fire & Smoke Seals are required around the edge of Fire Doors to achieve typically a 30 minute or 60 minute Fire Rating.

Fire & Smoke Seals

- Ultimate quality
- Installation friendly design
- Certifire Approved



Combined Acoustic, Smoke and Fire Seals			To order Fire and Smoke Seal add /TS, /AS or /SS to relevant Fire Seal Code. Eg. I/LP1004/SS	
Seal Section Size	DS	Finesse™	Fire Seal	Fire & Smoke Seals
10 x 3mm & 10 x 4mm seals Can provide 30 minutes fire resistance. Two parallel seals can provide 60 minutes fire resistance in hardwood constructions, subject to manufacturers test evidence		 The complete solution for acoustic, smoke and fire protection with superior aesthetics		 Intumescent fire seal for use where no smoke sealing is required TS (Elastomeric fins 4mm or 6mm) AS (Elastomeric fins 4mm or 6mm) SS (Polypropylene brush pile 4mm)
15 x 4mm seals Suitable for softwood constructions or where the gap between the door and the frame is greater than usual.		 I/LP1504FS 15 x 4mm (Finesse™)	 I/LP1004 10 x 4mm	Available in TS, AS and SS profiles AS to special order
20 x 4mm seals Can provide 60 minutes fire resistance. Can be notched to fit around hinges.		 I/LP2004FS 20 x 4mm (Finesse™)	 I/LP2004 20 x 4mm	Available in TS, AS and SS profiles AS to special order
25 x 4mm seals These large seals help control door distortion.			 I/LP2504 25 x 4mm	Available in I/TS, AS and SS profiles AS to special order
Smoke seal material	Elastomeric fins 4mm or 6mm	Elastomeric fins 4mm	N/A	TS – Elastomeric fins 4mm or 6mm, AS – Elastomericfin 4mm or 6mm, SS – Polypropylene brush pile 4mm
Min/max gap size	3mm / 4mm*	3mm / 4mm*	3mm / 4mm*	3mm / 4mm*
Nominal seal sizes	All seals are available in standard length of 2.1m. Other lengths are available to special order.			
Fitting	All Lorient intumescent fire seals have a self-adhesive backing. The adhesive used has been specially selected to provide excellent adhesion on a wide range of materials, including MDF on which it is usually difficult to obtain an effective bond.			
Finish	All Lorient acoustic, smoke and fire seals are available in a range of standard and special colours including woodgrain and metallic finishes.			

*Seals suitable for larger gaps available on request



Fire Resistant/Intumescent Products

Batwing® seals

The Lorient Batwing® Seal is a simple to install retrofit Cold Smoke Seal which is fitted into the rebate of the door frame.

Batwing® Seals

The Curved Fin Batwing® acoustic and smoke seal minimises the opening and closing resistance of the door leaf due to its unique, curved fins.



LORIENT

Flexible elastomeric fin material springs back to original shape to provide ongoing performance and durability in service.

Symmetrical design ensures fins are always in contact with two surfaces of the door leaf, creating an air chamber to provide excellent acoustic properties.

Acoustically tested in accordance with BS EN ISO 10140-1: 2010 +A1: 2012 and proven to meet the requirements of Approved Document E. Will achieve a rating of 31dB Rw when tested on a typical FD30 door assembly, in conjunction with a I/LAS8001 si threshold seal - no additional perimeter seal required.

Effective smoke seal up to 200°C.

Aggressive self-adhesive backing tested on many surfaces, including MDF. Variety of colours to blend with door designs. Fully tested for performance and durability under the third party certification schemes CERTIFIRE and British Board of Agrément. Tested to 1,000,000 opening and closing cycles on a full size door assembly, without failure.



Lorient Batwing® Seal fitted in door rebate in conjunction with plain Fire Seal

PART NUMBER	I/LAS1206	I/LAS1007	I/LAS1212K	I/LAS1010	I/LAS1212	I/LAS1015
DESCRIPTION	Single Batwing®	Single Batwing®	Batwing®-on-a-Stick	Batwing®	Batwing®	Batwing®
LENGTH	2100mm	2100mm	2100mm	2100mm	2100mm	2100mm
SECTION DETAIL						

Colours available: Black (I/BLK), White (I/WH), Dark Brown (I/DB), Light Brown (I/LB), Grey (I/GR), Silver (I/SI), Cream (I/CR) & Clear(I/CLR).

*Single Batwing® is not Certifire accredited



Fire Resistant/Intumescent Products

Glazing seals

The Lorient range of glazing seals are designed to provide Fire Rated glazed panels in wall and doors. Each system is designed for simple installation and effective performance.

System-36 PLUS

Part No.	Product Reference	Lengths
I/LG1512	LG1512 System-36/6 PLUS Gasket For 6-7mm Glass	60m roll
I/LG1513	LG1513 System-3617 PLUS Gasket For 7mm Glass	60m roll
I/LG1717	LG1717 System-36/10 PLUS Gasket For 9-11mm Glass	30m roll
I/LG2022	LG2022 System-36/15 PLUS Gasket For 14-16mm Glass	30m roll

System-36 consists of a flexible U-shaped intumescent gasket used with a range of standard fixing beads, for use in 30 minute fire resistant doors and screens.

- Available in sizes to suit different thicknesses of glass from 4mm to 23mm
- Supplied on a reel so it's easily dispensed and cut to length without wastage in off-cuts
- Flexible enough to be fitted to curved corners and circular vision panels.



System-63Ø

Part No.	Product Reference	Lengths
I/LG2715	System 63Ø Gasket For 6mm Georgian Wired or Pyran-S® Glass Only	50m coils, black
I/LX4002	Intumescent Liner 40Mm Wide	1m length
I/LX5002	Intumescent Liner 50Mm Wide	1m length

System-63Ø is a variant of System-36 which has been designed for use in circular apertures in 60 minute fire resistant doors.

- A cost-effective solution to the problem of incorporating circular glazed apertures
- Use with an intumescent liner
- Easy to fit.





Fire Resistant/Intumescent Products

Glazing seals


The Lorient range of glazing seals are designed to provide Fire Rated glazed panels in walls and doors. Each system is designed for simple installation and effective performance.

Flexible Figure 1 (FF1)

Part No.	Product Reference	Lengths
I/FF1	Flexible Figure 1 Intumescent Strip	50m Coils, 5 per box
Colours	Cream, white, black, light brown, dark brown, as standard colour matching to special order	

Flexible Figure 1 is designed for use with glazed apertures in 30 minute fire resistant doors.

- Comprises a pair of bead applied intumescent strips
- Flexible, quick and easy to install
- Available in a choice of colours
- Suitable for use with a variety of fire resistant glass types
- Unique design which enables tolerances between door, bead and glass thicknesses to be accommodated
- Glazing Beads for 44mm doors can be provided.




System-90 PLUS

Part No.	Product Reference	Lengths
LG2727	System-90 PLUS Channel	1m & 2.1m
I/		
LG2727/IL	54 x 2mm Intumescent Liner	1050mm

System-90 PLUS is designed for 60 minute fire resistant doors and screens. Contact our Technical Services team for more information. When using a suitable door and screen construction (such as Georgia-Pacific system for high performance fire door assemblies which requires a specific beading system) it provides 90 minute fire resistance. 120 minute fire resistance can be attained when a suitable door only construction is used.

- Comprises a U-shaped PVC profile containing an intumescent core and an intumescent liner, and beads of wood or metal
- Tested with a range of glass types
- Glazing beads for 44mm and 54mm doors can be provided.





Fire Resistant/Intumescent Products

Air Transfer Grilles

Fire resistant air transfer grilles permit ventilation through fire rated compartments. Applications include vents to fire doors and within ducts which penetrate fire break walls or floors.

LV Fire Resistant Air Transfer Grilles

The LV Range of Air Transfer Grilles achieves a fire rating of up to 60 minutes subject to the installation type.

LVN Range

Grille Thickness	Width (mm)	Height (mm)
I/LVN20 (2 pieces x 20mm)	100mm - 600mm (in 25mm increments)	100mm - 600mm (in 25mm increments)
I/LVN25 (2 pieces x 25mm)	100mm - 600mm (in 25mm increments)	100mm - 600mm (in 25mm increments)

Part Code is formulated as follows; Prefix I/LVN20/ or I/LVN25/ followed by Width and Height eg I/LVN20/100100



LVV40 Range - Square Edge

Grille Thickness	Width (mm)	Height (mm)
I/LVV40 (40mm)	100mm - 600mm (in 25mm increments)	100mm - 600mm (in 25mm increments)

Part Code is formulated as follows; Prefix I/LVV40/ followed by Width and Height eg I/LVV40/100100


Cover Plates

Grille Finish	Grille Width (mm)	Grille Height (mm)
I/CP/S (Silver)	100mm - 600mm (in 50mm increments)	100mm - 600mm (in 50mm increments)
I/CP/WH (White)	100mm - 600mm (in 50mm increments)	100mm - 600mm (in 50mm increments)

Part Code is formulated as follows; Prefix I/CP/SA followed by Width and Height eg I/CP/SA/100100

LVC40 Range - Circular


Part Code	Grille Finish	Actual Diameter (mm)	Suitable for nominal duct size
I/LVC40/100	40mm	98	100
I/LVC40/125	40mm	123	125
I/LVC40/150	40mm	148	150
I/LVC40/200	40mm	198	200



LVC40 Range
Grille fitted in duct



LVV40 Range
Grille fitted
with Cover
Plates



LVN Range
Grille



Fire Resistant/Intumescent Products

Mastic, Expanding Foam & Fire Retardant Spray

Fixfire® provides a range of products to prevent the spread of fire in buildings.

Nullifire Fire Resistant Acrylic Sealant

Part No.	Description
I/M701/WH	White Fire Resistant Acrylic Sealant, 310ml Cartridge
I/M701/GR	Grey Fire Resistant Acrylic Sealant, 310ml Cartridge

Features

- Up to 5 hours fire resistance
- Suitable for gaps up to 50mm wide
- No insulating backing material required for fire performance, PE backing rod for depth gauge only
- Maintains substrate acoustic rating
- Reduces air leakage
- Excellent toolability and low slump characteristics, can be smoothed
- Width to depth ratio of 2:1
- Accommodates movement of up to 10%
- Over paintable with most water based and oil based top seals
- Low shrinkage.

Fire performance

- Tested in accordance with EN 1366-4
- Up to 5 hours fire resistance
- Classification EN 13501.

Acoustic performance

- Tested in accordance with EN ISO 140-3:1995.

Air permeability performance

- Tested in accordance with EN 1026.



I/M701/WH /
I/M701/GR

Fire Rated PU Foam

Part No.	Description
I/FFI77	Fire Rated PU Foam, 880ml Aerosol Can With Nozzle

Features

- Suitable for gap widths up to 30mm
- Up to 4 hours fire resistance
- Easy to use ergo-cap system
- Quick and easy to install
- Sets tack free in 10 minutes
- Sets in a semi ridged structure, yields to vibration.

Fire performance

- Tested in accordance with EN 1366-4
- Up to 4 hours fire resistance
- Classification EN 13501 and DIN 4102: Part 1, B1.

Acoustic performance

- Tested in accordance with EN ISO 140-3:1995.

Air permeability performance

- Tested in accordance with EN 1026.



I/FFI77

Flame Retardant Spray

Part No.	Description
X/FRS1	750mL Flame Retardant Spray
X/FRS5	5L Flame Retardant Spray Refill

- Available in 750ml trigger spray and 5L refill sizes
- Water based fire proofing spray
- Will treat any water absorbent material, including natural and synthetic materials and fabrics
- Has passed BS5852:1990 and BS5867: part 2: 1980 standards
- Easy to apply
- 1L will treat 10-15m².



X/FRS1



X/FRS5



Fire Resistant/Intumescent Products

Pipe Seals

Fixfire® provides a range of products designed to maintain the integrity of fire compartments where services penetrate through walls, floors and ceilings.




Intumescent Pipe Collars

Part No.			Size	
Fire Rating				
2 Hour	3 Hour	4 Hour		
-	-	I/AFPC32/4P	32mm	
-	-	I/AFPC40/4P	40mm	
I/AFPC55/2E	-	I/AFPC55/4P	55mm	
-	-	I/AFPC63/4P	63mm	
-	-	I/AFPC75/4P	75mm	
-	-	I/AFPC82/4P	82mm	
-	-	I/AFPC90/4P	90mm	
I/AFPC110/2E	-	I/AFPC110/4P	110mm	
I/AFPC125/2E	-	I/AFPC125/4P	125mm	
-	-	I/AFPC160/4P	160mm	
-	-	I/AFPC200/4P	200mm	
-	-	I/AFPC225/4P	225mm	
-	-	I/AFPC250/4P	250mm	
-	I/AFPC275/3E	-	275mm	
-	I/AFPC300/3E	-	300mm	
-	I/AFPC315/3E	-	315mm	
I/AFPC355/2E	-	-	355mm	

- Fire Resistance testing to BS476: Part 20: 1987, and EN1366-3
- Suitable for UPVC, ABS, MDPE, HDPE and PP pipes
- Up to 4 hours fire resistance
- Surface mounted, cast or semi-cast applications.




Wall Installation




Floor Installation

Intumescent Pipe Wraps

Part No.		Size	
Fire Rating			
2 Hour	4 Hour		
-	I/AFIPW32/4	32mm	
-	I/AFIPW40/4	40mm	
-	I/AFIPW55/4	55mm	
-	I/AFIPW63/4	63mm	
-	I/AFIPW75/4	75mm	
-	I/AFIPW82/4	82mm	
-	I/AFIPW90/4	90mm	
-	I/AFIPW110/4	110mm	
-	I/AFIPW125/4	125mm	
-	I/AFIPW160/4	160mm	
I/AFIPW200/2		200mm	



Floor Installation



Wall Installation



Fire Resistant/Intumescent Products

Intumescent Fire Pillows & Downlighter Covers

Fixfire® provides a range of products designed to maintain the integrity of fire compartments where services penetrate through walls, floors and ceilings.


Intumescent Fire Pillows

Part No.	Size	Dimensions
I/AFFPL	Large	300mm x 200mm x 40mm
I/AFFPM	Medium	300mm x 150mm x 40mm
I/AFFPS	Small	300mm x 100mm x 40mm
I/AFFPSAS	Sausage	300mm x 50mm x 40mm

- Fire tested to BS476: Part 20:1987
- EN1366-3 E120
- EN13501-2 Fire Resistance Classification
- EN1026 Air Permeability
- EN10140 Acoustic Reduction
- Up to 4 hours fire integrity
- Available in 4 standard sizes
- Easy to install & re-locate
- Removable for re-use
- For wall floor & ceiling penetrations
- Dustproof - safe for the work environment
- Protects cable trays & ducts
- Certifire Approval



Floor Installation



Wall Installation

Intumescent Downlighter Covers

Part No.	Size Reference	Maximum Fitting Size	Cutout Size Diameter mm
I/AFDLCOVS	Small	150x150	50-75
I/AFDLCOVM	Medium	200x200	75-100
I/AFDLCOVL	Large	250x250	100-140
I/AFDLCOVXL	X-Large	300x170	145x270
I/AFDLCOVXXL	XX-Large	350x230	145x250

- Fire rated to BS EN 1365-2:2000/BS476 Part 23:1987
- 30 or 60 minute fire rating
- Covers a wide range of mains & low voltage downlighters
- Choice of 5 sizes
- Provides a highly insulating stable char when exposed to fire
- Prevents fire from penetrating the ceiling void and retains ceiling's fire protection integrity
- Acoustic Rated BS EN 150 140 : BS EN ISO 717
- Ventilated to reduce heat build up
- Installed in seconds
- No screws, drilling or additional support required
- Maintenance free
- Can be used in suspended, plasterboard or concrete ceilings
- Lightweight & flexible cover can be fitted from below or above the ceiling
- Downlighter can be fitted as normal.



Standard Cone Version



Large Version



Fire & Safety Signs

Standard Signs - Non-Photoluminescent

The Fixfire® range of signs is available in several different materials, and in varying sizes to suit all applications. We can even produce bespoke signs to your exact requirements.



Robust & Durable



High Visibility



Easy to Install

Fire Door Notices



1 1606 F N B
2 1606 F N B
7 1606 F



1 1609 B
2 1609 B



1 1610 B U
2 1610 B U
7 1610 B



Ask for a copy of the latest Signs & Safety Products Catalogue



1 1616 B
2 1616 B



1 1618 B U
2 1618 B U



1 1621 B
2 1621 B



1 1635 U
2 1635 U



1 1636 U
2 1636 U

Emergency Escape Door Notices



1 2047 G L
2 2047 G L




1 2034 C F U
2 2034 C F U



1 2037 C F U
2 2037 C F U

HOW TO ORDER



CHOOSE YOUR SIGN ➔

CHOOSE MATERIAL CODES ➔

CHOOSE SIZE CODES ➔

- 1 Rigid Plastic
- 2 Self Adhesive Vinyl
- 3 Photoluminescent Rigid Plastic
- 4 Photoluminescent Self Adhesive
- 5 Miscellaneous Products*
- 6 Aluminium
- 7 Polycarbonate
- 8 Double Sided Hanging Version of Sign
- 9 Single Sided Hanging Version of Sign
- 10 Stainless Steel
- 11 Brass

A	75 x 100 mm	J	400 x 200 mm	S	75 x 200 mm
B	80 x 80 mm	K	300 x 400 mm	T	210 x 210 mm
C	150 x 150 mm	L	450 x 150 mm	U	100 x 100 mm
D	150 x 100 mm	M	600 x 200 mm	V	300 x 150 mm
E	150 x 200 mm	N	400 x 400 mm	W	600 x 000 mm
F	200 x 200 mm	P	600 x 400 mm	X	200 x 100 mm
G	300 x 100 mm	Q	600 x 450 mm	Y	70 x 70 mm
H	250 x 300 mm	R	178 x 203 mm	Z	76mm diameter



Fire & Safety Signs

Standard Signs - Non-Photoluminescent

The Fixfire® range of signs is available in several different materials, and in varying sizes to suit all applications. We can even produce bespoke signs to your exact requirements

Robust & Durable

High Visibility

Easy to Install

Emergency Escape Signage



1 2003 G L M
2 2003 G L M
7 2003 G L
8 2003 G L M
9 2003 G L M



1 2004 G L M
2 2004 G L M
7 2004 G L
8 2003 G L M
9 2003 G L M



1 2001 G L M
2 2001 G L M
8 2003 G L M
9 2003 G L M



1 2002 G L M
2 2002 G L M
8 2003 G L M
9 2003 G L M



1 2007 G L M
2 2007 G L M
7 2007 G L
8 2003 G L M
9 2003 G L M



1 2008 G L M
2 2008 G L M
7 2008 G L
8 2003 G L M
9 2003 G L M



1 2005 G L M
2 2005 G L M
8 2003 G L M
9 2003 G L M



1 2006 G L M
2 2006 G L
8 2003 G L M
9 2003 G L M



1 2011 G L M
2 2011 G L M
8 2003 G L M
9 2003 G L M



1 2012 G L M
2 2012 G L M
8 2003 G L M
9 2003 G L M



1 2009 G L M
2 2009 G L
8 2003 G L M
9 2003 G L M



1 2010 G L M
2 2010 G L
8 2003 G L M
9 2003 G L M



1 2015 G L M
2 2015 G L M
8 2003 G L M
9 2003 G L M



1 2013 G L M
2 2013 G L
8 2003 G L M
9 2003 G L M



1 2014 G L M
2 2014 G L
8 2003 G L M
9 2003 G L M



1 2016 G L M
2 2016 G L M
8 2003 G L M
9 2003 G L M

8 2004 L FIRE EXIT SIGN SUSPENDED
USING JET SET WIRES



PRODUCT TECHNICAL TIP



BS5499 PART 4

WHEN SIGNING AN ESCAPE ROUTE FOR A STRAIGHT ON APPLICATION NOTE THAT AN UPWARD ARROW SHOULD BE USED. AN UPWARD ARROW IS DEFINED AS 'STRAIGHT ON FROM HERE' OR 'STRAIGHT ON AND UP FROM HERE'. A DOWNWARD ARROW IS DEFINED AS 'STRAIGHT ON AND DOWN FROM HERE'.



Fire & Safety Signs

Standard & Post Mounting Signs - Non-Photoluminescent

The Fixfire® range of signs is available in several different materials, and in varying sizes to suit all applications. We can even produce bespoke signs to your exact requirements



Robust &
Durable



High
Visibility




Easy to
Install

Fire Action Notices



1 1439 E H
2 1439 E H



1 1401 E H
2 1401 E H




1 1432 E H
2 1432 E H

Assembly Point Signage



1 2509 H Q 6 2509 H Q
2 2509 H Q 7 2509 H Q

Wall and Fence Mounting



1 2055 H Q
2 2055 H Q
6 2055 H Q

Post Mounting

- Aluminium
- Includes channel for post mounting
- Order Channel Clips separately



5 2112 250x300mm
5 2113 450x600mm

Post Mounting Brackets



S/CH1339 50mm channel clip
S/CH1340 60mm channel clip
S/CH1341 76mm channel clip
S/CH1342 89mm channel clip
S/CH1343 102mm channel clip
S/CH1344 114mm channel clip
S/CH1345 140mm channel clip

HOW TO ORDER

CHOOSE YOUR SIGN ➔		
	Your Sign	
1	1234	G L
MATERIAL ▲	SIGN ▲	SIZE ▲

CHOOSE MATERIAL CODES ➔

- 1 Rigid Plastic
- 2 Self Adhesive Vinyl
- 3 Photoluminescent Rigid Plastic
- 4 Photoluminescent Self Adhesive
- 5 Miscellaneous Products*
- 6 Aluminium
- 7 Polycarbonate
- 8 Double Sided Hanging Version of Sign
- 9 Single Sided Hanging Version of Sign
- 10 Stainless Steel
- 11 Brass

CHOOSE SIZE CODES ➔

A	75 x 100 mm	J	400 x 200 mm	S	75 x 200 mm
B	80 x 80 mm	K	300 x 400 mm	T	210 x 210 mm
C	150 x 150 mm	L	450 x 150 mm	U	100 x 100 mm
D	150 x 100 mm	M	600 x 200 mm	V	300 x 150 mm
E	150 x 200 mm	N	400 x 400 mm	W	600 x 000 mm
F	200 x 200 mm	P	600 x 400 mm	X	200 x 100 mm
G	300 x 100 mm	Q	600 x 450 mm	Y	70 x 70 mm
H	250 x 300 mm	R	178 x 203 mm	Z	76mm diameter



Fire & Safety Signs

Fire Extinguisher Type Signs - Photoluminescent

Our range of photoluminescent identification signs is designed to complete ant fire point installation. High visibility glow in the dark finish to aid location and identification of fire equipment in any emergency.



Robust &
Durable



High
Visibility



Easy to
Install



Glow in the
Dark

YOU MAY ALSO
REQUIRE ...

FIND ON
P12

Extinguisher Stands



S/FIX-01




S/6387M/R



S/FIX-04



S/FIX-03



S/FIX-02



S/6267M/R



S/6266M/R



S/FIX-05

ID SIGNS FITTED TO
X/MTS2/MG TUFFSTAND™



S/FIX-01/L



S/6387ID/R



S/FIX-04/L



S/FIX-03/L



S/FIX-02/L



S/6407ID/R



S/6408ID/R



S/FIX-05/L



Fire & Safety Signs

TuffSigns™ Non-Photoluminescent

TuffSigns™ is a high performance and robust range of fire signs developed by Fixfire® for maximum visual impact in applications such as warehouses and factories where greater viewing distances are involved.



Robust &
Durable



Weatherproof



High
Visibility



User-friendly
fixings



Made in UK



Bespoke signs
to your design



...signs that shout

Extra Large Fire Exit Signs

Part No.	Description	Dimensions (mm)
S/FE/D	Fire Exit - Downward Directional Arrow	300 x 900
S/FE/L	Fire Exit - Leftward Directional Arrow	300 x 900
S/FE/R	Fire Exit - Rightward Directional Arrow	300 x 900
S/FE/DS	Fire Exit - Horizontal Directional Arrow - Double Sided Hanging	300 x 900
S/FE/D/DS	Fire Exit - Downward Directional Arrow - Double Sided Hanging	300 x 900
S/FE/D/SS	Fire Exit - Downward Directional Arrow - Single Sided Hanging	300 x 900
S/FE/L/SS	Fire Exit - Leftward Directional Arrow - Single Sided Hanging	300 x 900
S/FE/R/SS	Fire Exit - Rightward Directional Arrow - Single Sided Hanging	300 x 900



S/FE/L



S/FE/R



S/FE/D

Fire Procedure Notices

Part No.	Description	Dimensions (mm)
S/FA/N1	N1 Fire Action Notice Inc. All Point Symbol	240 x 190
S/FA/NH	Nursing Home Fire Action Notice Inc. Call Point Symbol	240 x 190
Prestige Frame Options	Add: /SA (Satin Aluminium), /PB (Polished Brass), /PC (Polished Chrome)	

- Bespoke logos can be incorporated.



S/FA/NH/PB SIGN
IN POSITION



S/FA/N1



S/FA/NH



Project that corporate
image with your own
customised signs

S/FA/N1/SPEC



Fire & Safety Signs



Sign Mounting Accessories

Fixfire® provide a full range of accessories to allow easy and secure mounting of all types of signs in any situation.

Ceiling Tee Clip

Part No.	Description
S/522	Ceiling Tee Clip

- Clear polypropylene with loop
- Clips securely to suspended ceiling tee bars
- 19x19mm.




S/522

Rotating Ceiling Button

Part No.	Description
S/527	Rotating Ceiling Button

- White polypropylene ceiling button with eyelet that rotates 360° and self adhesive for fast application
- 25x25mm.
- Magnetic Ceiling Hook




S/527

Magnetic Ceiling Hook

Part No.	Description
S/535	Magnetic Ceiling Hook

- White plastic cased magnet with hook
- Supports pull loads up to approx 2.5kg
- 35mm Ø.




S/535

Oval Mobile Button

Part No.	Description
S/580	Oval Mobile Button

- White polypropylene ceiling button with loop and self adhesive finger tab for fast application
- 40x19mm





S/580

'S' Hook

Part No.	Description
S/7065-SM	Bright Metal Finish

- Bright metal finish
- 48mm long



S/7065-SM



Fire & Safety Signs


Sign Mounting Accessories

Fixfire® provide a full range of accessories to allow easy and secure mounting of all types of signs in any situation.

Metal Clasp Ring

Part No.	Description
S/2309-25M	25mm Ø
S/2309-38M	38mm Ø
S/2309-50M	50mm Ø

- Bright metal hinged clasp ring for heavy duty signs or bright metal aesthetic
- Other sizes available to order.





S/2309

Jet Set Wires

Part No.	Description
S/7020	17cm to 110cm Long. Load up to 0.35kg
S/7040	20cm to 140cm Long. Load up to 2.5kg
S/7060	31.5cm to 400cm Long. Load up to 2.5kg

- Pull to length hanging wires
- Simply pull to required length and it stays.





S/7020/40/60

Double Ended Hooks

Part No.	Description
S/7065/10	10Cm Long
S/7065/15	15Cm Long
S/7065/20	20Cm Long
S/7065/25	25Cm Long
S/7065/30	30Cm Long
S/7065/40	40Cm Long
S/7065/50	50Cm Long
S/7065/76	76Cm Long
S/7065/90	90Cm Long

- Bright galvanised 2mm thick wire double ended hooks for suspending and connecting signs



S/7065

Silicone

	Description
S/SIL/310	Silicone, 310ml Cartridge



S/SIL/310

Cartridge Gun

Part No.	Description
S/CG1	Cartridge Gun



S/CG1



Building Evacuation Products

Evacuation Chairs

Our range of premium evacuation chairs is designed for ease and speed of deployment.

With a wide range of features available, there is a chair to suit every requirement.



Made in
UK



Robust &
Durable



Lightweight



12 Month
Warranty



50% Less Staff
Required

Ego Evacuation Chair

Part No.	Description
E/EGO	Ego Evacuation Chair

- Easy to open, load and evacuate
- Single operator technology
- Slim Storage
- Wheels auto brake when folded
- Up to 180Kg capacity
- Fitted with Stairblade self braking track belt for greater control on stairs
- Built in safety belt
- Supplied with wall mounting bracket, and cover.

PLEASE ENQUIRE
ABOUT...



We also offer training on how
to use evacuation chairs.



Versa Evacuation Chair

Part No.	Description
E/VER	Versa Evacuation Chair

- Easy to open, load and evacuate
- Single operator technology
- Slim Storage
- Four wheel chair for greater stability
- Up to 180Kg capacity
- Fitted with Stairblade self braking track belt for greater control on stairs
- Suitable for upstairs travel
- Integral stored passenger safety harness and headband
- Supplied with wall mounting bracket, operating handbook and cover.



Product Technical Tip



You should carry out a periodic evacuation of your premises at least yearly for industrial and commercial premises and six monthly for shops and residential premises. The results should be recorded in a site fire log book.

Using an escape chair effectively...





Fire Log Book & Fire Document Holder

Every organisation needs one! The Fixfire® log book is a 'must have' tool to aid the compliance with the Regulatory Reform (Fire Safety) order 2005 (RRO).



Keep your evidence in one place



Demonstrates diligence to inspecting authorities



Robust, built to last



Clearly tabbed



Separate Events & Actions and Planned Maintenance Sections

Fire Log Book

Part No.	Description
CS/LB1	Fire Log Book
CS/LBC	Fire Log Book Cabinet

- Heavy duty ring binder
- Rigid tabbed dividers
- Simple and easy to follow layout
- Based on latest BS regulations with clear explanatory notes
- Capacity to store over 5 years worth of entries

Fire records need to be kept on hand for easy accessibility. Our Fire Log Book cabinet ensures your Fire Safety Records are kept secure and accessible.



CS/LBC



TERMS AND CONDITIONS OF SUPPLY

1 Definitions

In this Agreement, the following words shall have the following meanings:
 'Completion Date' means any date agreed in writing by the Supplier and the Client by which time the Work is to be completed.
 'Client' means the person, partnership or company identified on the Purchase Order Form
 'Conditions' has the meaning given in Clause 12.4.
 'Goods' means the goods identified in the Quotation or as further notified to the Client to be purchased by the Supplier, after agreement between the Parties.
 'Quotation' means the document to which these Terms and Conditions of Sale are attached together with any correspondence sent by the Supplier prior to the Client accepting the Supplier's quote.
 'Services' means the services identified in the Quotation or as further notified to the Client.
 'Supplier' means Avansys LLP registered in England No OC384483, registered office address: Mayflower House, Bodmin Road, Coventry CV2 5DB, Coventry and Firing is a trade mark of Avansys LLP. Allan Fire is a trading style of Avansys LLP.
 'Survey' has the meaning given in Clause 2.3.
 'Work' means the Services and the Goods that the Supplier shall provide for and to the Client.

2 Work and materials

2.1 The Supplier agrees to provide:
 2.1.1 the Services; and
 2.1.2 the Goods
 to the Client subject to the provisions of these Terms and Conditions of Sale.

2.2 By accepting the Supplier's Quotation (with or without amendment) the Client agrees to be bound by these Terms and Conditions of Sale.

2.3 The Supplier may need to carry out a survey and inspection of the buildings, electrical supply, water supply, computer equipment and other facilities of the Client ('the Survey'). The Client acknowledges and agrees that the matters detailed in the Survey ('Client Action') which require action on the part of the Client shall be carried out before any Work is carried out.

2.4 This agreement may be varied, or added to, from time to time, in writing and signed by both Parties. The changes shall be clearly identified, together with the additional or different sums to be paid by the Parties.

3 Performance of the Work

3.1 Goods. On receiving confirmation from the Client that they want the Supplier to carry out the Works, the Supplier shall order the Goods.

3.2 Services. The Parties shall agree the time and place when the Services shall be performed, subject to the availability of the Supplier's staff and agents and the availability and delivery of the Goods.

3.3 The Supplier shall use reasonable endeavours to complete the Services by the Completion Date or meet such other dates as agreed by the Parties.

3.4 Time shall not be of the essence:
 3.4.1 for ordering of the Goods;
 3.4.2 for the delivery of the Goods;
 3.4.3 for any times for when the Services are to be performed, whether given or agreed to by the Supplier; or
 3.4.4 for the length of time that any of the Services are to take, whether specified in the Specification Document or otherwise; or
 3.4.5 for the Completion Date or such other date as agreed by the Parties.

4 Sums to be paid and payment

4.1 Goods. When the Goods are ordered, the Supplier shall invoice the Client for the price specified by the supplier of the Goods plus the cost of any insurance, packaging, transportation and delivery charges. Except where otherwise agreed in writing the Client shall pay the invoice within 30 days of the date of the invoice.

4.2 Services. Except where otherwise agreed in writing payment for sums due for the Services shall be made within 30 days of the date of invoice.

4.3 All amounts stated are exclusive of VAT and/or any other applicable taxes or levy, which shall be charged in addition at the rate in force at the date any payment is required from the Client.

4.4 If payment of any sum due under this Agreement is not received by any due date specified for that sum, the Supplier shall be entitled to:
 4.4.1 charge interest on the outstanding amount at the rate of 8% per annum above the Bank of England base rate, accruing daily; or
 4.4.2 require that the Client make a payment in advance of any Services or part of the Services not yet supplied; or
 4.4.3 not provide any further Services or part of the Services; or
 4.4.4 terminate this Agreement as provided for in Clause 15.

4.5 Without prejudice to any other right available to the Supplier, the Supplier shall be entitled to charge to the Client all legal and other costs reasonably incurred in the recovery of any debts and any bank charges made due to cheques offered in payment which are dishonoured.

4.6 All payments shall quote the Supplier's invoice number and other reference numbers.

5 Delivery of the Goods

5.1 The Supplier shall deliver the Goods to the address specified by the Client on the date that the Supplier shall specify for the delivery ('the Delivery Date').

5.2 For the avoidance of doubt, the Delivery Date or other date given under this Agreement is no more than an estimate, and shall not be of the essence.

6 Risk

The risk in the Goods shall pass to the Client on the Delivery Date.

7 Property

The property in the Goods shall not pass to the Client until the Supplier has received the payment of the sums due in regard to the Goods (and any other sums that are due or owing to the Supplier) in full, whether or not delivery has made.

8 Time limit for claims

8.1 The Client acknowledges and agrees that:
 8.1.1 the Supplier has not given any warranty or condition as to the quality or fitness for any purpose of the Goods; and
 8.1.2 all conditions or warranties, express or implied (whether by statute or otherwise), are expressly excluded;

8.2 Any claim by the Client which is based on any defect in the quality or condition of the Goods shall (whether or not delivery is refused by the Client) be notified to the Supplier within 7 days from the date of delivery or (where a defect or failure was not apparent on reasonable inspection) within a reasonable time after discovery of the defect or failure. If delivery is not refused, and the Client does not notify the Supplier accordingly, the Client shall not be entitled to reject the Goods and the Supplier shall have no liability for such defect or failure, and the Client shall be bound to pay the price as if the Goods had been delivered in accordance with this Agreement.

8.3 Where Goods are despatched to the Client by carrier, non-delivery must be advised in writing within 14 days of the invoice date for the Goods, failing which the Client shall be deemed to have received the Goods and shall be bound to pay the price as if the Goods had been delivered in accordance with this agreement.

8.4 Any shortage in Goods delivered to the Client must be advised to the Supplier within 3 days of the date of delivery, failing which the Client shall be deemed to have received the Goods and shall be bound to pay the price as if the Goods had been delivered in accordance with this agreement.

9 The Client's obligations

9.1 The Client acknowledges and agrees that for the Supplier to be able to provide the Services the Client shall:
 9.1.1 permit the Supplier, its employees and agents to carry out the Survey if required at such times as the Supplier may reasonably specify;

9.1.2 carry out the Client Action by the time and date agreed between the Supplier and the Client;

9.1.3 co-operate with the Supplier as the Supplier reasonably requires;

9.1.4 provide to the Supplier such information and documentation as the Supplier reasonably requires;

9.1.5 obtain all permissions, consents (including, but not limited to, planning permission), and health and safety approvals from such organisations and authorities which are required for the Goods to be installed and for the Services to be carried out;

9.1.6 make available to the Supplier the facilities, resources, working space and staff as the Supplier reasonably requires from time-to-time; and

9.1.7 instruct the Client's staff and agents to co-operate and assist the Supplier.

9.2 The Supplier may charge the Client for any additional reasonable costs and expenses incurred by the Supplier caused by the Client's instructions, failure to provide instructions, or failure to comply with Clause 9.1.

10 Services

10.1 The Parties shall agree the time and place when the Services shall be performed, subject to the availability of the Supplier's staff and agents.

10.2 The Supplier shall use reasonable endeavours to complete the Services by the Completion Date or meet such other dates as agreed by the Parties.

10.3 Time shall not be of the essence:

10.3.1 for any times for when the Services are to be performed; or

10.3.2 for the length of time that any of the Services are to take; or

10.3.3 for the Completion Date or such other date as agreed by the Parties.

11 Defects in the Goods

11.1 The Supplier will, at its option, either make good by repair or by the supply of a replacement, where defects which, under proper use, appear in the Goods within a period of 12 months after the Goods have been delivered and installed, provided that:

11.1.1 the Client notifies the Supplier in writing of the claimed defect immediately on their appearance; and

11.1.2 the Supplier is satisfied that the defects arise solely from faulty design (other than a design made, furnished or specified by the Client for which the Supplier has disclaimed responsibility in writing), materials or workmanship; and if received by the Supplier, any part of the Goods claimed to be defective are returned to the Supplier at the expense of the Client.

11.2 The repaired or replacement Goods will be delivered to the Client to the original place of delivery, but otherwise subject to the provisions of this Agreement.

11.3 As an alternative to Clause 11.1, the Supplier shall, in its absolute discretion, entitled to return the sums paid by the Client for the Goods to the Client if the Client has already paid such sums when the claimed defect is notified by the Client to the Supplier.

11.4 The remedy provided in this Clause 11 is without prejudice to the other provisions of this Agreement, including, without limitation, Clause 12 below.

12 Liability for the Goods

12.1 The Supplier shall not incur or accept any liability concerning any representation made by the Supplier (or made on the Supplier's behalf) to the Client (or any person acting on behalf of the Client) prior to the making of this Agreement where such representation was made or given in relation to the Conditions;

12.2 The Supplier shall not accept any liability to the Client concerning any express term or provision of this Agreement relating to the Goods where such a term relates to the Conditions;

12.3 All terms, conditions or warranties implied by statutory or common law relating to the Conditions concerning the Goods are excluded from the Agreement to the fullest extent permitted by law;

12.4 'The Conditions' means:

12.4.1 the correspondence of the goods with any description; and/or

12.4.2 the quality of the goods; and/or

12.4.3 the fitness of the goods for any purpose(s) whatsoever (whether made known to the Supplier or not).

13 Warranties, liability and indemnities for the Services

13.1 The Supplier warrants that it will use reasonable care in performing the Services.

13.2 If any part of the Services is performed negligently or in breach of the provisions of this Agreement then, at the request of the Client (if the request is given within six months of the Completion Date), the Supplier will re-perform the relevant part of the Services, always subject to Clause 14.1 and Clause 14.2 below.

13.3 The Supplier expressly does not warrant that any result or objective, whether stated in this Agreement or not, shall be achieved, be achievable or be attained at all or by a given Completion Date or any other date.

14 Liability generally

14.1 Except in the case of death or personal injury caused by the Supplier's negligence, the Supplier's liability under or in connection with this Agreement, whether arising in contract, tort, negligence, breach of statutory duty or otherwise howsoever, shall be limited in respect of any claim to the greater of:

14.1.1 the sum for which the Supplier carries insurance cover regardless of whether such insurance is sufficient to cover the claim giving rise to the liability; or

14.1.2 the sum of £50,000.

14.2 The Supplier will not be responsible for the following:

14.2.1 Loss in relation to systems installed at the Client's premises prior to the date of this agreement arising:

14.2.1.1 before the completion of the Supplier's first routine inspection visit to the Client's premises; or

14.2.1.2 during the first 12 months from the start date of this agreement as a result of that part of a fire system which has not yet been inspected.

14.2.2 Loss due to the acts or neglect of any other person including the Client, the provider of any telephone line, redcar or other form of communication technology, police, fire or other authority or individual. None of these is the Supplier's agent for any purpose.

14.2.3 Delays, interruptions or suspensions in providing the Services, which are due to any other person (including the Client), thing or event which we could not reasonably be expected to prevent;

14.2.4 Loss due to the fact that equipment or cabling not supplied by the Supplier is connected to or installed near to any equipment or system installed by the Supplier.

14.2.5 Loss resulting from:

14.2.5.1 the police or other authority failing to act in accordance with a proper emergency response;

14.2.5.2 a signal transmitted to the Supplier's alarm receiving centre not being received by the Supplier for reasons beyond the Supplier's control;

14.2.5.3 the failure of any cables or wiring installed within the fabric of the Client's Premises or buried underground prior to the start date; or

14.2.5.4 the activation of a circuit breaker which affects the power supply to any part of the system installed by the Supplier; or

14.2.5.5 any other cause beyond the Supplier's reasonable control and not caused by our lack of reasonable care.

14.2.6 Losses due to the Client failing to follow the Supplier's recommendations given for additions, repairs or any work required to the system supplied by the Supplier.

14.2.7 Where equipment is damaged or lost in transit, unless the Client notifies the Supplier in writing within 10 days from the date of despatch of the equipment to the Client's premises.

14.2.8 Damage unavoidably caused to decorations, fittings and the like at the Client's premises as a result of any installation by the supplier or the provision by the Supplier of any services.

14.3 Neither Party shall be liable to the other Party in contract, tort, negligence, breach of statutory duty or otherwise for any loss, damage, costs or expenses of any nature whatsoever incurred or suffered by that other Party of an indirect or consequential nature including without limitation any economic loss or other loss of turnover, profits, business or goodwill.

14.4 The Client shall indemnify and hold harmless the Supplier from and against all Claims and Losses arising from loss, damage, injury, liability to the Supplier employees and third parties, infringement of third party intellectual property, or third party losses by reason of or arising out of any information supplied to or supplied by the Supplier, its employees or suppliers by the Client within or without the course of the Client's business (including all claims, claims, proceedings, penalties, fines and liability (whether criminal or civil, in contract, tort or otherwise); and 'Losses' shall mean all losses including without limitation financial losses, damages, legal costs and other expenses of any nature whatsoever.

14.5 Each of the Parties acknowledges that, in entering into this Agreement, it does not do so in reliance on any representation, warranty or other provision except as expressly provided in this Agreement, and any conditions, warranties or other terms implied by statute or common law are excluded from this Agreement to the fullest extent permitted by law.

14.6 Where the Goods or Services are sold under a consumer transaction (as defined by the Consumer Transactions (Restrictions on Statements) Order 1976) the statutory rights of the Client are not affected by these Terms.

15 Termination

15.1 The Supplier may terminate this Agreement if:

15.1.1 the Client does not pay the amount(s) specified in the invoice(s) for the Goods or Services and upon the Supplier giving the Client 14 days' notice following the date specified for the payment of the invoice(s) in Clause 4.1;

15.1.2 the Client fails to carry out the Client Action and upon the Supplier giving the Client 14 days' notice following the end of the period specified by the Supplier under Clause 9.1.2.

15.2 Without prejudice to Clause 15.1 and any other remedies or rights, either Party may terminate this Agreement at any time by written notice to the other Party ('Other Party') and the notice taking effect as specified in the notice:

15.2.1 if the Other Party fails to perform any of its obligations under this Agreement, and where a breach is capable of remedy within 14 days, the breach is not remedied with 14 days by the Other Party receiving notice which specifies the breach and requiring the breach to be remedied; or

15.2.2 if the Other Party becomes insolvent or if an order is made or a resolution is passed for the winding up of the Other Party (other than voluntarily for the purpose of solvent amalgamation or re-construction), or if an administrator, administrative receiver or receiver is appointed in respect of the whole or a part of the Other Party's assets or business, or if the Other Party makes any composition with its creditors or takes or suffers any similar or analogous action in consequence of debt.

15.3 If this Agreement is terminated because of the reason specified in Clause 16.1 above, then the Client shall pay for all Work carried out up to the date of termination and all sums due for payment after the date of termination which arise from commitments entered by the Supplier for the performance of the Work prior to the date of termination.

16 General

16.1 Force majeure

Neither Party shall have any liability under or be deemed to be in breach of this Agreement for any delays or failures in performance of this Agreement which result from circumstances beyond the reasonable control of that Party. The Party affected by such circumstances shall promptly notify the other Party in writing when such circumstances cause a delay or failure in performance and when they cease to do so. If such circumstances continue for a continuous period of more than six months, either Party may terminate this Agreement by written notice to the other Party.

16.2 Entire agreement

This Agreement contains the whole agreement between the parties in respect of the sale and installation of the Goods and supersedes and replaces any prior written or oral agreements, representations or understandings between them relating to such subject matter. The parties confirm that they have not entered into this Agreement on the basis of any representation that is not expressly incorporated into this Agreement. Nothing in this Agreement excludes liability for fraud.

16.3 Waiver

No failure or delay by the Supplier in exercising any right, power or privilege under this Agreement shall impair the same or operate as a waiver of the same nor shall any single or partial exercise of any right, power or privilege preclude any further exercise of the same or the exercise of any other right, power or privilege. The rights and remedies provided in this Agreement are cumulative and not exclusive of any rights and remedies provided by law.

16.4 Severance

If any provision of this Agreement is prohibited by law or judged by a court to be unlawful, void or unenforceable, the provision shall, to the extent required, be severed from this Agreement and rendered ineffective as far as possible without modifying the remaining provisions of this agreement, and shall not in any way affect any other circumstances or of the validity or enforcement of this Agreement.

16.5 Interpretation

In this Agreement unless the context otherwise requires:

16.5.1 words importing any gender include every gender;

16.5.2 the singular number includes the plural number and vice versa;

16.5.3 words importing persons include firms, companies and corporations and vice versa;

16.5.4 references to numbered clauses are references to the relevant clause in this Agreement;

16.5.5 any obligation on any Party not to do or omit to do anything is to include an obligation not to allow that thing to be done or omitted to be done;

16.5.6 the headings to the clauses of this Agreement shall not affect the interpretation;

16.5.7 any reference to an enactment includes reference to that enactment as amended or replaced from time to time and to any subordinate legislation or bylaw made under that enactment;

16.5.8 where the word 'including' is used in this Agreement, it shall be understood as meaning 'including without limitation'.

16.6 Notices

16.6.1 Any notice to be given under this Agreement shall be in writing and shall be sent by first-class mail, or by facsimile or email confirmed by first class mail to the address or facsimile number of the relevant Party set out in the Quotation, or such other address or facsimile number as that Party may from time to time notify to the other Party in accordance with this clause 17.11.

16.6.2 Notices sent as above shall be deemed to have been received three working days after the day of posting (in the case of inland first class mail), or on the next working day after transmission (in the case of facsimile messages, but only if a transmission report is generated by the sender's facsimile machine recording a message from the recipient's facsimile machine, confirming that the facsimile was sent to the number indicated above and confirming that all pages were successfully transmitted).

16.6.3 In proving the giving of a notice it shall be sufficient to prove that the notice was left, or that the envelope containing the notice was properly addressed and posted, or that the applicable means of telecommunication was addressed and despatched and despatch of the transmission was confirmed and/or acknowledged as the case may be.

16.7 Law and jurisdiction

The validity, construction and performance of this Agreement shall be governed by English law and shall be subject to the exclusive jurisdiction of the English courts to which the Parties submit.

16.8 Third parties

For the purposes of the Contracts (Rights of Third Parties) Act 1999 and notwithstanding any other provision of this Agreement this Agreement is not intended to, and does not, give any person who is not a party to it any right to enforce any of its provisions.

17 Cancellation Rights-Consumer Contracts

17.1 This clause shall apply where the client is dealing as a consumer and the Consumer Protection (Distance Selling) Regulations 2000 apply.

17.2 Your right of cancellation

17.2.1 The Client has the right to cancel the contract at any time up to the end of seven working days after it receives the goods or, in the case of services, the date the Supplier sends its order confirmation (see below). A working day is any day other than weekends and banks and other public holidays.

17.2.2 To exercise its right of cancellation the Client must give written notice to the Supplier by hand or post, fax or email, at the address or telephone number or email address shown below, giving details of the goods ordered and (where appropriate) their delivery.

17.2.3 If the Client exercises its right of cancellation after the goods have been delivered to it, the Client will be responsible for returning the goods to the Supplier at its own cost. The goods must be returned to the address shown below. The Client must take reasonable care to ensure the goods are not damaged in the meantime or in transit.

17.2.4 Once the Client has notified the Supplier that it is cancelling the contract, the Supplier will refund or recredit the Client within 30 days for any sum that has been paid by it or debited from its credit card for the goods or services.

17.2.5 If the Client does not return the goods as required, the Supplier may charge the Client a sum not exceeding the direct costs of recovering the goods.

17.2.6 You do not have the right to cancel the contract if the order is for audio or video recordings or computer software which have been unsealed by you, or for goods which by their nature cannot be returned or are liable to deteriorate or expire rapidly. The Supplier will notify you at the time your order is accepted if this applies.

All images and descriptions including dimensions are approximate and are only intended to provide a general idea of the goods to which they refer and will not form part of the contract. All colours shown are representations. Although we make every effort to show our products in their original colours, due to photography, printing methods and individual monitors, actual colours may vary. The Company's policy is one of continuous improvement and it reserves the right to make reasonable changes to products specifications at its discretion. When placing an order with the Company, the Buyer must be satisfied that the Company's then specification is appropriate for its (or its customer's) requirements.

Visit our website
www.fixfire.co.uk



Head Office
Mayflower House
Bodmin Road
Wyken, Coventry
CV2 5DB

National Sales & Technology Centre
Jubilee House
Stenson Road
Coalville
LE67 4JP

Fixfire
LIFE & PROPERTY PROTECTION

your best alliance for compliance™

Visit our website www.fixfire.co.uk

linkedin.com/company/fixfire



Main Switchboard: 024 7661 6699 • Freephone: 08000 891999

E-mail: sales@fixfire.co.uk • Website: www.fixfire.co.uk

Fixfire® is a trade mark of Avansys LLP registered in UK No OC384483

© Fixfire® 2026