

# Domes - Mobiles

| Dome Diameter | Weight        | Power | Light Output      |
|---------------|---------------|-------|-------------------|
| 8"            | 2 lbs / 1 kg  | 12W   | Up to 800 lumens  |
| 10"           | 4 lbs / 2 kg  | 18W   | Up to 1200 lumens |
| 12"           | 5 lbs / 2 kg  | 30W   | Up to 2100 lumens |
| 14"           | 8 lbs / 4 kg  | 35W   | Up to 2400 lumens |
| 18"           | 14 lbs / 6 kg | 42W   | Up to 2900 lumens |
| 22"           | 20 lbs / 9 kg | 49W   | Up to 3400 lumens |

|              |                                                                                                                                                                                                                                                                             |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Finishes     | See <a href="#">Porcelain &amp; Metal Finishes</a> .                                                                                                                                                                                                                        |
| Mounting     | Standard junction box. Sloped ceiling by request.                                                                                                                                                                                                                           |
| Light Bulbs  | 120V or 230V G8 LED Bulbs by Emery Allen. Bulbs are included.<br>Color accuracy 90+ CRI.<br>Choose from 2700K or 3000K light temperature.<br>Compatible with most standard LED dimmers (ELV forward/reverse phase).<br><b>POWER:</b> 120V or 230V. No transformer required. |
| Light Output | See <a href="#">Dome Light Output</a> guide. Darker porcelain finishes diminish light output. Colored gloss porcelain finishes cast colored light. You may specify a reflector to increase light output and restore color. See <a href="#">Dome Reflector</a> guide.        |
| Production   | Handmade in Boulder, Colorado.<br>10-12 week lead time. Rush by request.                                                                                                                                                                                                    |
| UL Listing   | Available by request.                                                                                                                                                                                                                                                       |
| Motion       | We build true mobiles that are individually balanced. The domes and arms can undulate up and down but cannot move side to side. Arm angles are locked in order to prevent domes from contacting one another.                                                                |

## ADVANCED CUSTOMIZATIONS

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting          | Custom canopies including recessed and mud-in are available by request. See <a href="#">Canopy Options</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Dim-To-Warm Light | 12V GY6.35 Bulbs by Emery Allen.<br>Color accuracy 90+ CRI.<br>1800K-2700K CCT light temperature. <a href="#">See details</a> .<br>Light output reduced by up to 35%.<br><b>POWER:</b> 12V LED transformer required.<br>Choose from the following: <ul style="list-style-type: none"> <li>Emery Allen Integrated Driver (installed in j-box)</li> <li>Remote Driver (installed in attic, basement, or closet)</li> </ul> See <a href="#">Domes LED Drivers &amp; Dimmers</a> for driver details.                                                                                                                                         |
| Premium Light     | 24V LED Strip by ElementalLED or QTL.<br>Color accuracy 95+ CRI.<br>Light output is equivalent to Standard Light.<br>50K+ hour lifetime (17+ years at 8 hr/day).<br>Choose from light temperatures 2400K to 5000K.<br>Inquire for premium Dim-To-Warm options (reduced output)<br>LEDs are electrician replaceable at end of life.<br><b>POWER:</b> 24V LED transformer required.<br>Choose from the following: <ul style="list-style-type: none"> <li>SwitchEX+ Driver/Dimmer Wall Unit</li> <li>Remote Driver (installed in attic, basement, closet)</li> </ul> See <a href="#">Domes LED Drivers &amp; Dimmers</a> for driver details |
| Custom Light      | You may optionally specify your own LED strip and driver.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

# Mobile 5 - Spiral - 18, 14, 12, 10, 8




## 65"L x 47"W

AS SHOWN ON WEBSITE

Minimum Overall Drop Height : 21"



You may specify the number of domes, dome sizes, overall shape (round or linear), dimensions (length and width, or diameter), and overall drop height. Each sculpture is designed to specification.



# Mobile 5 - Spiral - 22, 18, 14, 12, 10 77"L x 56"W

Minimum Overall Drop Height : 25"



You may specify the number of domes, dome sizes, overall shape (round or linear), dimensions (length and width, or diameter), and overall drop height. Each sculpture is designed to specification.

