

Domes - Constellation

Dome Diameter	Weight	Power	Light Output
8"	2 lbs / 1 kg	12W	Up to 800 lumens
10"	4 lbs / 2 kg	18W	Up to 1200 lumens
12"	5 lbs / 2 kg	30W	Up to 2100 lumens
14"	8 lbs / 4 kg	35W	Up to 2400 lumens
18"	Not available		
22"	Not available		

Dome Constellation sculptures require an integrated, remote, or dimmer style driver.

Finishes	See Porcelain & Metal Finishes .
Mounting	Standard junction box. Sloped ceiling by request.
Light Bulbs	12V G4 Bulbs by Emery Allen. Bulbs are included. Color accuracy 90+ CRI. Choose from light temperatures 2700K or 3000K. POWER: 12V LED transformer required. Choose from the following: - Emery Allen Integrated Driver (installed in junction box) (60W or less) - Emery Allen Integrated Driver (installed in "Dome" style canopy) (61-300W) - Emery Allen Remote Driver (installed in attic, basement, etc) (300W or less) See Domes LED Drivers & Dimmers for driver details.
Light Output	See Dome Light Output guide. Darker porcelain finishes diminish light output. Colored gloss porcelain finishes cast colored light. You may specify a reflector to increase light output and restore color. See Dome Reflector guide.
Production	Handmade in Boulder, Colorado. 10-12 week lead time. Rush by request.
UL Listing	Available by request.

ADVANCED CUSTOMIZATIONS

Mounting	Custom canopies including recessed and mud-in are available by request. See Canopy Options .
Dim-To-Warm Light	12V GY6.35 Bulbs by Emery Allen. Color accuracy 90+ CRI. 1800K-2700K CCT light temperature. See details . Light output reduced by up to 35%. POWER: 12V LED transformer required. Choose from the following: - Emery Allen Integrated Driver (installed in j-box) - Remote Driver (installed in attic, basement, or closet) See Domes LED Drivers & Dimmers for driver details.
Premium Light	24V LED Strip by ElementalLED or QTL. Color accuracy 95+ CRI. Light output is equivalent to Standard Light. 50K+ hour lifetime (17+ years at 8 hr/day). Choose from light temperatures 2400K to 5000K. Inquire for premium Dim-To-Warm options (reduced output) LEDs are electrician replaceable at end of life. POWER: 24V LED transformer required. Choose from the following: - SwitchEX+ Driver/Dimmer Wall Unit - Remote Driver (installed in attic, basement, closet) See Domes LED Drivers & Dimmers for driver details
Custom Light	You may optionally specify your own LED strip and driver.

Round

Constellation 4 - Round - 4x8


37"D

AS SHOWN ON WEBSITE

Minimum Overall Drop Height : 12"



You may specify the number of domes, dome sizes, diameter and overall drop height. Each sculpture is designed to specification.





Constellation 4 - Round - 4x10 42"D

Minimum Overall Drop Height : 12"



You may specify the number of domes, dome sizes, diameter and overall drop height. Each sculpture is designed to specification.





Constellation 4 - Round - 12, 12, 10, 8 43"D

Minimum Overall Drop Height : 13"



You may specify the number of domes, dome sizes, diameter and overall drop height. Each sculpture is designed to specification.





Constellation 4 - Round - 12, 12, 10, 8 48"D

Minimum Overall Drop Height : 13"



You may specify the number of domes, dome sizes, diameter and overall drop height. Each sculpture is designed to specification.



Constellation 4 - Round - 12, 12, 10, 8 52"D

AS SHOWN ON WEBSITE

Minimum Overall Drop Height : 13"



You may specify the number of domes, dome sizes, diameter and overall drop height. Each sculpture is designed to specification.

