



# Murano Glass Orb 4 Surface Mount




|                          |                                                                                                                                                                                                                                                             |                                                          |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|
| Technical Specifications | Materials                                                                                                                                                                                                                                                   | Brass, glass                                             |
|                          | Product weight                                                                                                                                                                                                                                              | 1.25 lbs                                                 |
|                          | Lead time                                                                                                                                                                                                                                                   | 8 weeks                                                  |
|                          | Integrated LED                                                                                                                                                                                                                                              | 545 lm / 1800 K - 3000 K / 6.2 W / 95+ CRI / warm on dim |
|                          | Input Voltage                                                                                                                                                                                                                                               | 120 V, 240 V or 277V                                     |
|                          | Dimmer                                                                                                                                                                                                                                                      | TRIAC, ELV or 0-10 V                                     |
|                          | Certifications                                                                                                                                                                                                                                              | cULus listed, cETLus listed, damp-rated                  |
|                          |    |                                                          |


|       |    |                                                                                                                                                                                                                                                                               |
|-------|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes | 1. | This fixture can be installed on a wall or ceiling.                                                                                                                                                                                                                           |
|       | 2. | The LED lifetime is 50,000 hours.                                                                                                                                                                                                                                             |
|       | 3. | The driver, (class 2 power unit) is included with the fixture and can be installed inside of the J-box with a minimum depth of 1 1/2" or remotely.                                                                                                                            |
|       | 4. | This fixture is designed so the LED board can be replaced when it reaches its lifetime.                                                                                                                                                                                       |
|       | 5. | This fixture has handmade elements and may exhibit variability within the same piece. These variations are inherent in the production process and are not to be considered as defects. We do our best to maintain a consistent product while honoring handmade craftsmanship. |

|         |                |
|---------|----------------|
| Updated | April 10, 2026 |
|---------|----------------|


Front View




Side View



Front View: Ceiling Installation



Isometric View



# Murano Glass Orb 8 Surface Mount




|                          |                                                                                                                                                                                                                                                             |                                                          |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|
| Technical Specifications | Materials                                                                                                                                                                                                                                                   | Steel or brass, glass                                    |
|                          | Product weight                                                                                                                                                                                                                                              | 2.75 lbs                                                 |
|                          | Lead time                                                                                                                                                                                                                                                   | 8 weeks                                                  |
|                          | Integrated LED                                                                                                                                                                                                                                              | 545 lm / 1800 K - 3000 K / 6.2 W / 95+ CRI / warm on dim |
|                          | Input Voltage                                                                                                                                                                                                                                               | 120 V, 240 V or 277V                                     |
|                          | Dimmer                                                                                                                                                                                                                                                      | TRIAC, ELV or 0-10 V                                     |
|                          | Certifications                                                                                                                                                                                                                                              | cULus listed, cETLus listed, damp-rated                  |
|                          |    |                                                          |


|       |    |                                                                                                                                                                                                                                                                               |
|-------|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes | 1. | This fixture can be installed on a wall or ceiling.                                                                                                                                                                                                                           |
|       | 2. | The LED lifetime is 50,000 hours.                                                                                                                                                                                                                                             |
|       | 3. | The driver, (class 2 power unit) is included with the fixture and can be installed inside of the J-box with a minimum depth of 1 1/2" or remotely.                                                                                                                            |
|       | 4. | This fixture is designed so the LED board can be replaced when it reaches its lifetime.                                                                                                                                                                                       |
|       | 5. | This fixture has handmade elements and may exhibit variability within the same piece. These variations are inherent in the production process and are not to be considered as defects. We do our best to maintain a consistent product while honoring handmade craftsmanship. |

|         |                |
|---------|----------------|
| Updated | April 10, 2026 |
|---------|----------------|


Front View




Side View



Front View: Ceiling Installation



Isometric View



# Finish Options


Brass, glass, and ceramic samples made or finished by hand may exhibit variability. Available for purchase at

---

## Murano Hand Blown Glass



Goto Bianco



Daisy



Chamomile



Aster

---

## Brass



Brass



Patina Brass



Blackened Brass



Pewter



Polished Nickel