




ECO Lighting Technology and Solutions



LED Driver

Model No. MJ-30-2500



FG/ $\perp$ (Green)
AC/N(White)
AC/L(Black)
+V(Gray)
-V(White)


UL[®]
C US
E308859

IP68 CE RoHS


Features

- Ip68 design for indoor or outdoor installations
- Protections: Short circuit / Overload/Over temperature
- Cooling by free air convection
- 100% full load burn-in test
- IP68 waterproof
- Meet the standard of world lighting safety
- Suitable for LED lighting
- Products through CE, RoHS, UL Certification
- Warranty: 5 years

MODEL		MJ-30-2500				
OUTPUT	DC VOLTAGE	12V				
	RATED CURRENT	2.5A				
	CURRENT RANGE	0~2.5A				
	RATED POWER	30W				
	NOTE 2 RIPPLE & NOISE (max.)	200mV				
	NOTE 3 VOLTAGE TOLERANCE	±2%				
	LINEAR REGULATION	±1%				
	LOAD REGULATION	±2%				
INPUT	VOLTAGE RANGE	100-277VAC				
	FREQUENCY RANGE	50 ~ 60Hz				
	POWER FACTOR (Typ.)	PF>0.6/110VAC				
	EFFICIENCY (Typ.)	86%				
	AC CURRENT (Typ.)	0.4/110VAC				
	INRUSH CURRENT (Typ.)	COLD START 100A/110VAC				
PROTECTION	Short circuit	Protection type : recovers automatically after fault condition is removed				
	Overload	overload protected @ 115-140% above peak rating				
	Over temperature	Protection type : Shut down o/p voltage, re-power on to recover				
ENVIRONMENT	WORKING TEMP.	-30 ~ +50°C (Refer to output load derating curve)				
	WORKING HUMIDITY	20 ~ 99% RH non-condensing(Waterproof)				
	STORAGE TEMP., HUMIDITY	-40 ~ +80°C , 10 ~ 99% RH				
SAFETY & EMC	SAFETY STANDARDS	UL				
	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVAC I/P-GND:1.5KVAC				
	EMC Test Standards	EN55015 : 2013;EN61547 : 2009; EN61000-3-2:2014; EN61000-3-3:2013				
NOTE	1. All parameters NOT specially mentioned are measured at 110VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 10uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation.					



 Mechanical Specification



 Others

DIMENSION	5.12*1.77*1.3"
CARTON QUANTITY	40PCS/Carton
CARTON SIZE	15.15*12.2*9.25"
WEIGHT	14.5Kg/G.W

 Derating Curve

