

## Technical Summary

### Part 1 : Dimensions

<b>Width</b>	125	mm
<b>Length</b>	1850	mm
<b>Thickness</b>	14.3	mm
<b>Boards Per Box</b>	6	planks
<b>Box Size</b>	1.3875	sqm

### Part 2 : General Data

<b>Surface Lacquer</b>	EverGuard™ Protection, developed with Teknos Treffert Parquet Lacquer, each board with 10 - 11 Coats, utilising 6 types of lacquer: <ul style="list-style-type: none"> <li>◆ UV PU Insulation Base Coat</li> <li>◆ UV Transparent Sealer Base Coat</li> <li>◆ UV Anti Scratch Sealer Base Coat</li> <li>◆ UV Sealer Low Gloss Base Coat OR Semi-Gloss Base Coat</li> <li>◆ UV Super Matt Top Coat OR Semi-Gloss Top Coat</li> </ul>
<b>Edging</b>	Matte Brushed (light - medium brushing)
<b>Finish</b>	Depending on product selection: <ul style="list-style-type: none"> <li>◆ Semi-Gloss Smooth</li> <li>◆ Matte Brushed</li> </ul>
<b>Installation Method</b>	Floating Click Installation (Recommended) Trowel Glue Installation
<b>Box Weight</b>	19.3kg
<b>Installation Areas</b>	Residential and Commercial

## Technical Summary

### Part 3 : Installation

<b>Floated on Underlay</b>	Yes  Suitable with all EverQuiet® Hard Floor Underlay. Please confirm suitability with other underlays with your installer or retailer.
<b>Trowel Glue</b>	Yes (4 - 6mm trowel)  <i>Note: Floating is the recommended approach of installation, however, adhesive fixed installations are also suitable in some circumstances when the moisture of the environment is well controlled.</i>
<b>Nailed</b>	No

### Part 4 : Warranty

<b>General Residential (Structural)</b>	25	Years
<b>Light Commercial (Structural)</b>	5	Years