

# Technical Summary

## Part 1 : Dimension

|                |        |        |
|----------------|--------|--------|
| Width          | 196    | mm     |
| Length         | 1215   | mm     |
| Thickness      | 8.3    | mm     |
| Boards Per Box | 10     | planks |
| Box Size       | 2.3845 | sqm    |

## Part 2 : General Data

|                            |  |
|----------------------------|--|
| Click Lock System          | Patented Unilin with Wax Seal  |
| Core Type                  | High Density Fiber Composite Core  |
| Wear & Abrasion Resistance | AC3 - Heavy Residential / Light Commercial<br><br>0.3mm Aluminium Oxide Wear Layer                                     |
| Finish                     | Matte  |
| Installation Method        | Floating Installation  |
| Stain Resistant            | Yes  |
| Fade Resistant             | Yes  |
| Slip Resistant             | Yes  |
| Impact Sound Resistance    | Installed upon a 4, 5, 6 Star Acoustic Rated (AAAC scale) underlay is suitable for most apartment strata requirements. |
| Box Weight                 | 17kg   |
| Profile                    | Square Edge  |

## Part 3 : Warranty

|                            |    |       |
|----------------------------|----|-------|
| <b>General Residential</b> | 25 | Years |
| <b>Light Commercial</b>    | 5  | Years |