Technical Summary

Part 1 : Dimensions

Width	125	mm
Length	1850	mm
Thickness	14.3	mm
Boards Per Box	6	planks
Box Size	1.3875	sqm

Part 2 : General Data

Surface Lacquer	EverGuard™ Protection, developed with Teknos Treffert Parquet Lacquer, each board with 10 - 11 Coats, utilising 6 types of lacquer: ✦ UV PU Insulation Base Coat ✦ UV Transparent Sealer Base Coat ✦ UV Anti Scratch Sealer Base Coat ✦ UV Sealer Low Gloss Base Coat OR Semi-Gloss Base Coat ✦ UV Super Matt Top Coat OR Semi-Gloss Top Coat
Edging	Matte Brushed (light - medium brushing)
Finish	Depending on product selection: ✦ Semi-Gloss Smooth ✦ Matte Brushed
Installation Method	Floating Click Installation (Recommended) Trowel Glue Installation
Box Weight	23kg
Installation Areas	Residential and Commercial

Technical Summary

Part 3 : Installation

Floated on Underlay	Yes Suitable with all EverQuiet® Hard Floor Underlay. Please confirm suitability with other underlays with your installer or retailer.
Nailed	No

Part 4 : Warranty

General Residential (Structural)	25	Years
Light Commercial (Structural)	5	Years

Please visit everfloor.com.au for the most up-to-date version of Warranty, Installation, and care and maintenance guidelines.

All technical data and testing are based on random sampling and are for indicative purposes only. Version: August 2025