

Installation Guidelines

⚠ ATTENTION OWNER / INSTALLER

Please carefully read and adhere to the following instructions before installing the flooring. Failure to do so may result in voiding the warranty of the product.

✦ Quality Check

Before installation, thoroughly inspect the flooring material to ensure it meets the requested quality standards. Verify that the material is free from defects and matches the desired specifications.

✦ Quantity Verification

Prior to starting the installation, confirm that the quantity of flooring is accurate and sufficient for the project. Double-check the quantity to avoid any shortages during the installation process.

✦ Colour and Finish Confirmation

Verify that the flooring material matches the specified colour, finish, and sheen level.

✦ Job-site and Substrate Requirements

Must ensure that the job-site environment and sub-surfaces meet or exceed all applicable standards. Refer to the installation instructions section inside the carton for specific requirements. It is crucial to follow the recommendations of the construction and materials industries, as well as local codes.

By carefully following these instructions, you will help ensure a successful installation and maintain the validity of the warranty.

Areas of Attention

Water-Resistance

Luxflor 8mm laminate has 48 hours of surface water-resistance when installed according to these installation guidelines. For clarity, this floor is resistant to all water-accidents for 48 hours, but not floods or leaks for prolonged periods of time.

Please note the floor is not designed for external usage, wet or high-humidity indoor areas e.g. shower, bathrooms, sauna rooms, swimming pools. Underfloor moisture can damage all types of flooring and the floor should not be installed unless the levelling compound is completely dry. If the substrate is concrete, the cement moisture content should be below 2.5% and for wood-based substrates, below 14%.

Do not install this laminate floor in wet areas such as the shower, bathroom, laundry, toilets or areas subject to regular moisture or water.

- ✦ The flooring must be installed on top of a relatively flat subfloor i.e. <2mm variation over 1m for complete effectiveness of the surface moisture seal.
- ✦ The flooring must be installed on top of an underlay with a minimum 200uM moisture barrier with an overlap and security taped with moisture-resistant tape, to prevent accumulation of subfloor moisture.