



Z-6182

Advanced Dual-Laser Omnidirectional Scanner



The Z-6182 is a compact vertical scanner empowered with the unique dual-laser technology, enabling 40 scan lines at a rate of 3,600 scans per second. Along with ZEBEX proprietary Z-SCAN+ hardware decoding technology, the Z-6182 guarantees unbeatable decoding speed and accuracy, the best choice for high-traffic applications, including hypermarket, healthcare, warehouse management and manufacturing process control.

- Aggressive scanning performance
- Instant "two-way object-fly-by" scan reaction
- Large scan field
- Barcode stitching capable
- Built-in EAS antenna and expandability for a RFID reader
- Easy on-site configuration and upgradeability

1. EAS compatible & multi-interface support
2. Optional mounting dock
3. Optional top cover



- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.

OPERATIONAL

Light Source	Dual 650 nm visible laser diodes (VLD)	
Depth of Field	5 mil: 0 – 55 mm	7.5 mil: 0 – 150 mm
	10 mil: 0 – 200 mm	13 mil: 0 – 240 mm
	20 mil: 0 – 320 mm	(Note: DOF may vary depending on environment condition and barcode quality.)
Scan Line	40	
Scan Rate	3,600 scans per second	
Scan Pattern	10 directions of scan field	
Print Contrast	45% @ UPC/EAN 100%	
Indicator	Two-color LED (blue, red)	
Beeper Operation	Programmable tone & volume	
System Interface	Keyboard, RS-232, HID USB, USB Virtual COM, OPOS, JPOS	

PHYSICAL

Dimension	152.5 × 152.0 × 82.0 mm	
Weight	685 g (without cable)	
Cable	Standard 2M straight	

POWER

Input Voltage	9 VDC ±10%	
Power Consumption	4.05 watts	
Operating Current	450 mA typical	

REGULATORY

Laser Class	CDRH Class IIa; IEC 60825 Class 1	
EMC	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI	

ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)	
Storage Temperature	-20°C – 60°C (-4°F – 140°F)	
Humidity	5% – 90% RH (no dewing allowed)	
Light Level	Up to 4,500 Lux (fluorescence)	
Drop Durability	Designed to withstand 1M drops	
Compatibility	EAS compatible	

DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF 2 of 5, IATA Code, MSI, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded
------------	--

