# JS LED® TECHNICAL DATA SHEET







### LED Wall Pack

Model :SZ-WP120/100/80W-HP-ACP (PC)

#### Advantage:

- UL & DLC certificate;
- IP65 Internal driver;
- Adjustable Power and CCT;
- Input voltage 120-277V / 120-347VAC;
- No UV or IR in the beam;
- Easy to install and operate;
- Energy saving, long lifespan;
- Light is soft and uniform, safe to eyes;
- Instant start, NO humming;
- Green and eco-friendly without mercury.


#### Application:


Entrance lighting, courtyard lighting;


Industrial lighting, Outdoor landscape lighting;

Building, The hotel;

Wall lighting area.









# **TECHNICAL DATA SHEET**

# Specifications

Product name	LED Wall Pack		
Part No	SZ-WP120/100/80W-HP-ACP (PC)		
Dimension	288*227*125mm		

#### **Technical Characteristic**

Color temperature	Adjustable CCT:3000K/4000K/5000K
CRI	>80
Lumen	15600LM
Lumen Efficacy	130LM/W
Input Power	Adjustable Power:120W/100W/80W
Viewing Angle	Degree
Input Voltage	120-277VAC 50/60Hz, Optional:120-347V
Driver model	China Brand Driver, (0-10Vdc Dimmer)
Photocel1	Yes
PF	>0.9
Waterproof Rating	IP65

#### **Materials**

LED Type	2835
LED QTY	468PCS
Housing	Aluminum(ADC12) +PC
Housing color	Brown

#### **Others**

Operating Temperature	-40°C TO 45°C
Operating Humidity	20%-90% RH
Storage Temperature	-40°C TO 80°C
Storage Humidity	10%-95%
Application	Outdoor / Indoor
Safety Certification	UL & DLC
Warranty Time	5 Years


# **TECHNICAL DATA SHEET**


# **Light Distribution Testing Parameters**

#### LUMINAIRE PHOTOMETRIC TEST REPORT

UTHDi:0.45% ITHDi:4.22% KDisp:0.000	0 Lamp Flux:12976.5x1 lm	
NAME: SZ-WP120/100/80W-HP-ACP(PC)	TYPE:	WEIGHT:
SPEC.: 100~277V	DIM.: 0.175*0.275	SERIAL No.:
MFR.:	SUR.: 0.15*0.26	Shielding Angle:

	DATA OF LAI	MP		PHOTOME	TRIC DATA Eff: 12	2.55 lm/W
MODEL	SZ-WP120	/100/80W	Imax (cd)	6156	S/MH(C0/180)	1.33
NOMINAL	POWER (W)	120	LOR(%)	100.0	S/MH(C90/270)	2.76
RATED VO	OLTAGE (V)	120	TOTAL FLUX(lm)	12977	η UP,DN(C0-180)	1.6,14.1
NOMINAL	FLUX(lm)	12976.5	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	12.7,71.6
LAMPS IN	NSIDE	1	η up(%)	14.3	CIBSE SHR NOM	1.50
TEST VOI	LTAGE (V)	120	η down(%)	85.7	CIBSE SHR MAX	1.50





## **Package**

Mode1	Net Weight	Size	Qty/Carton	Weight/Carton
SZ-WP120/100/80W-HP-ACP (PC)	3. 6KG	301*169*418MM	2	4.4KG