



ECO Lighting Technology and Solutions



Specification

Name.	CW-200RGB-20
Color	Red, Green, Blue and Yellow
Material	PVC
Diameter	2.2±0.1mm
Qty	200Feet/roll
Conductor stranding	26*0.16mm
Tolerance mm	±0.002
Resistance Ω/km	41.19
Conductor elongation %	10
Insulation thickness mm	0.38
Insulation thinnest mm	0.33
Nominal Voltage V	300V
Standard	UL1007

Aging Test

performance			Insulation	Jacket
Aging test	elongation %	Before aging	100%	/
	Expend intension MPA		10	/
	elongation %		change±20%	/
	Expend intension MPA	70±2℃×7 70±2℃×7 after aging	change±20%	/
Hi-Pot Test		AC V	2000V 5min no strike out	
spark testing			3KV	

LED Accessories

CW-200RGB-20



UL certification

Please visit jsledpower.com for more information

For support please call toll free number 1-800-909-5188

Headquarter Office

1318 Maine Ave.,
Baldwin Park, CA 91706
Tel: (626) 338 - 8291
Fax: (626) 338 - 8391

Texas Branch

8787 W. Bellfort Ave. Suite 900
Houston, TX 77031
Tel: (626) 416 - 8899
Fax: (281) 688- 8989