



LED Linear Strip Fixture

SZ-LS20W-2FT-ACP


Advantage:

- UL & DLC certificate
- 2835 Chip, CRI 80
- Input voltage 120-277VAC
- Easy to install and operate
- Energy saving, long lifespan
- Adjustable CCT and power
- Green and eco-friendly without mercury.



Application:

Office, Supermarkets, Meeting rooms
School, Hospital, Warehouse.



Product Specifications

Product Name	LED Linear Strip Fixture
Light Type	SZ-LS20W-2FT-ACP
Dimension	23.98*2.91*3.27"

Technical Characteristic

Color temperature	Adjustable CCT:3500K/4000K/5000K
CRI	>80
Lumen Efficacy	140LM/W
Input Power	Adjustable Power:10W/15W/20W
Viewing Angle	120 Degree
Input Voltage	120-277V 50/60Hz
Driver model	China Brand driver, (0-10Vdc Dimmer)
PF	>0.9
Optional Accessory	Sensor:Motion sensor Emergency Driver:Max 8W, Recharge time:≥24Hrs, Discharge time :90minutes

Materials

LED Type	2835
LED QTY	280PCS
Housing	IRON
Housing color	White
Cover	PC Milky
Operating Temperature	-4° F~113F,
Operating Humidity	10%-90% RH
Storage Temperature	-22° F~140° F

Others


Storage Humidity	10%-95%
Safety Certification	UL & DLC
Warranty Time	5 Years

Luminaire photometric

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:119.94V I:0.1617A P:19.111W PF:0.9852 Freq:60.01Hz		
UTHDi:0.41% ITHDi:7.09% KDisp:1.000 Lamp Flux:2717.75x1 lm		
NAME: SZ-LS20W-2FT-ACP	TYPE: SZ-LS20W-2FT-ACP	WEIGHT:
SPEC.: 120~277V	DIM.: 0.07*0.6	SERIAL No.: 01
MFR.:	SUR.: 0.07*0.6	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 142.21 lm/W
MODEL	SZ-LS20W-2FT-ACP	Imax (cd)	797.2	S/MH (C0/180)	1.24	
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH (C90/270)	1.18	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	2717.7	η UP,DN(C0-180)	6.4,43.1	
NOMINAL FLUX(lm)	2717.75	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	6.4,44.2	
LAMPS INSIDE	1	η up (%)	12.7	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	120	η down (%)	87.3	CIBSE SHR MAX	1.35	




Package

Model	Net Weight	Size	Qty/Carton	Weight/Carton
SZ-LS20W-2FT-ACP	9.9KG	24.72*9.61*10.79"	9	10.6KG

Installation manual

A. Surface-mounted installation



B. Suspending installation

