

LED Round Slim Panel





MODEL SPECIFICATION

MODEL:	SIZE	WATTAGE	5CCT	LUMENS
SZ-DL9W4-SP-R-CCT-277V	4inch	9W	2700K 3000K 3500K 4000K 5000K	620-710Lm
MODEL:	SIZE	WATTAGE	5CCT	LUMENS
SZ-DL12W6-SP-R-CCT-277V	6inch	12W	2700K 3000K 3500K 4000K 5000K	960-1030 Lm

DESCRIPTION

Ultra slim design, lamp thickness only1.22". Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K

Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms. Available size: 4", 6"

TECHNICAL SPECIFICATION

LISTING

ETL Listed

120-2	VOLTAGE
6	POWER FREQUENCY
;	POWER FACTOR
2700K 3000K 3500K 4000K 500	5CCT
	CRI
1	BEAM ANGLE
PS	MATERIAL
≥50,000l	LIFESPAN
(-4°F~ 113°F) -20~4	OPERATING TEMP
0-10V Dim	DIMMABLE
Suitable for Wet Location	RATING
5 year lim	WARRANTY

FEATURES

- · Baffle trim design
- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many 0-10v Dimmers
- Instant on
- · No flicker

INSTALLATION

No existing recessed housing or junction box required. Suitable for most new constructions. Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most 0-10V dimmers to give user a smooth dimming to choose the desired brightness. Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120-277V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.



LED Round Slim Panel







SIZE & DIMENSION & HOLE CUTOUT

Size	Dimension	Hole Cutout
4inch	134'(34.1mm)	ф4 21/64"(110mm)
6inch	46.689 (175-to Smm) 2.777 (130-to Smm) 1.227 (31-to Smm) 1.347 (24.1 mm)	ф6 19/64"(160mm)

RECOMMENDED DIMMER

	LEGRAND			
RMJS-8T-DV-B	Diva DVSTV	MS-Z101-WH	DVSTV-WH	RH4FBL3PW

ACCESSORIES







Connector