TECHNICAL DATA SHEET



LED Sport Light


Model: SZ-SP800WH-XX-5000K

Advantage:


- UL certificate
- 5050 Chip
- Input voltage 277-480VAC
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.

Application:

Gymnasium, Square plaza, Shipyard, Airport, Wharf, High mast and Contour lighting, etc.









Product Specifications

Product Name	LED Sport Light
Light Type	SZ-SP800WH-XX-5000K
Dimension	26. 95*18. 88*17. 26"

Technical Characteristic

Color temperature	5000K, Optional:5700K
CRI	>70
Lumen	128000LM
Lumen Efficacy	160LM/W
Input Power	800W
Viewing Angle	Optional:15°/25°/40°/60°
Input Voltage	277-480V 50/60Hz, Optional:120-277V, 120-347V
Driver model	SOSEN Brand driver, (0-10Vdc Dimmer, Surge-protective 10KV)
PF	>0.9
Waterproof Rating	IP65
	i .

Materials

LUMILEDS 5050
360PCS
Aluminum (ADC12)
Gray or Black
-40°C TO 45°C
10%-90% RH
-40℃ TO 80℃

Others

Storage Humidity	10%-95%
Application	Outdoor
Safety Certification	UL
Warranty Time	5 Years


TECHNICAL DATA SHEET


Light Distribution Testing Parameters

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:119.61V I:6.6581A P:795.49W PF:0.9989 F	req: 60.01Hz	
UTHDi:0.99% ITHDi:1.45% KDisp:1.000	Lamp Flux:133410x1 lm	WE
NAME: SZ-SP800WH-XX-5000K	TYPE:	WEIGHT:
SPEC.: 120-277V	DIM.: 0.345	SERIAL No.:
MFR.:	SUR.: 0.345	Shielding Angle:

I	DATA OF LAI	MP		PHOTOME	TRIC DATA Eff: 16	7.71 lm/W	
MODEL	SZ-SP800W	и-xx-5000к	Imax (cd)	286524	S/MH(C0/180)	.80) 0.61	
NOMINAL	POWER (W)	800	LOR(%)	100.0	S/MH(C90/270)	0.61	
RATED VO	LTAGE (V)	120	TOTAL FLUX(1m)	133410	η UP,DN(C0-180)	1.2,44.5	
NOMINAL	FLUX (lm)	133410	CIE CLASS	DIRECT	η UP,DN(C180-360)	1.1,53.2	
LAMPS IN	SIDE	1	η up(%)	2.3	CIBSE SHR NOM	0.50	
TEST VOI	TAGE (V)	120	η down(%)	97.7	CIBSE SHR MAX	0.60	






Package

Model	Net Weight	Size	Qty/Carton	Weight/Carton
SZ-SP800WH-XX-5000K	15.4KG	21. 77*20. 31*16. 73"	1	19. 51KG



TECHNICAL DATA SHEET

Product structure characteristics



Installation Diagram (optional)

1. The entire lamp is directly fixed on the lamp posts.

