



**GOLDEN
ENERGY
OFFSHORE**

MV Energy Savannah of Salt 305 RSV Design



TECHNICAL OUTLINE SPECIFICATION

MULTI PURPOSE OFFSHORE VESSEL

Rev.: 26.10.2026

Yard: Building No BH0001A10M @ Qingdao Wuchuan Heavy Industry Co. LTD

Delivery: 15.08.2021

Keel lay date: 20.09.2016

Name of ship: Energy Savannah
Port of registry: Aalesund
Distinctive number or letters: LASC8
IMO Number: 9777307
Maritime Mobile Service Identity (MMSI): 257023000
DNV ID: 34887





MAIN DESCRIPTION	MEASUREMENTS
Type : Multi Purpose Offshore Vessel	Length o.a. : 97,1m
	Length b.p.p. : 87,3m
	Breadth mld. : 22,0m
Classification:	Depth moulded : 9,2m
DnV GL 1A1 Offshore service vessel(+) BIS	Draught max. : 7,0m
BWM(T) Clean(Design, Tier III) COMF(C3, V3)	Design Draught : 5,7m
DK(+)	Freeboard @ max Draught : 2,2m
DYNPOS(AUTR, E) E0 ECA(SOxA)	Light weight : 5890,7t
HELDK(S, H, CAAN)	DWT @ 7,0m : 4117,5t
Ice(C) NAUT(OSV(A)) Recyclable SF SPS	Gross Tonnage : 7092
	Net Tonnage : 2127
	Deck load, Max : 1000T
ERN 99.99.99.99	

CAPACITIES

Work/Cargo Deck area: 1 100m² (52 x 21m)
Inside deck area: WROV hangar 73 m². OBS ROV hangar 36 m²
Deck strength: aft of #3: 25 t/m², #3 - #72: 10t/m².
Height of bulwark on Main Deck: 1200mm

Fresh Water	:	1 147m ³	Pump capacity 2 x 0-150 m ³ /h
FW Maker	:	2 x 18 m ³ /day	
Fuel Oil total	:	1 263m ³	Pump capacity 2 x 150 m ³ /hr
DW	:	3 749m ³	Pump capacity 2 x 0 - 150 m ³ /h
Ballast	:	3 749m ³	Pump capacity 2 x 0 - 150 m ³ /h

MACHINERY -PROPULSION	PERFORMANCE
Main eng.: 4 x HIMSEN 6H32/40 2880 kW, 720rpm, 15663 BHP	Max speed cons, 15kts: 34,5t / day
Harbour gen: 1 x CAT, 968 bkW, 1800 rpm	Service speed cons. 12kts: 17,2 t / day
Main Propulsion : 2 x SHOTTEL SRP 3030 FP each 3000 kW	Eco speed/cons. approx.10kts: 11,2 t / day
Stern tunnel thruster: 1 x 1400kW	
Bow tunnel thrusters: 2 x SHOTTEL STT 7 FP each 2050 kW.	DP max: 13,7 t / day
Bow Azimuth: 1 x SCHOTTEL STT 4 FP 1200 kW	DP min: 6 t / day
	DP Standby: 5 t / day
	Standby on field (non DP) 4 t / day
	Port consumption: 3,4 t / day





DECK/RESCUE EQUIPMENT

Capstans : 2 x 10t
Windlass/Mooring : 1 x Double w/ mooring winch
Deck Crane : 6t / 15m
Provision Crane : 3t / 12m
Life rafts (davit launched): 4 x Viking 25DKF (25pax)
LSA for : 100 persons
Life Jackets : 79
1 off Fast Rescue Craft: Merlin 615
1 off (SOLAS approved) Davit for FRC
2 off 50 persons lifeboat JYN75
2 off Lifeboat Davits Norsafe LH140
1 off Incinerator + 1 off waste compactor

ACCOMMODATION

Total POB: 100 persons
26 off Single bed cabins
33 off Double bed cabins
2 off 4 bed cabins
3 off Lounge
1 off Dayroom
1 off Galley
1 off Messroom (50 persons)
1 off Conference / opr room
1 off Gymnasium
1 off Hospital





SPECIAL DECK EQUIPMENT

150t OFFSHORE CRANE:	Main Line: 150T SWL – 11m Offshore mode Total wire length: 3470 m Drum capacity 3500m Hook travel 3417m / Ø72mm / weight in air 25,4kg 2 T, DAF 1.3, AHC capacity 2m/s, Constant Tension Whip Line: 10T SWL @ 36m- 695m, personnel lift Tugger winches: 2 x 5T SWL w/ Constant Tension Slew sector / speed: 360° / 0 – 0.8rpm Operation limits: Max list 5°, Wind speed: 25 m/s Camera installed on jib tip. Monitor for ROV operation in crane Cabin
25t SECONDARY CRANE:	25t 2 9 m, 2 185m wire, personnel lift
REMOVABLE BULWARK SECTIONS:	SB: 11m aft of Offshore Crane, 14m fwd of the Offshore Crane Port side: 14m aft of AUX crane. Stern section: 14m
ROV LARS SYSTEM: No of sheaves: Deployment Load: Operating speed: Umbilical winches: ROV Power distribution: ROV Hangar side doors:	1+1 (A-Frame + winch) 20Te 1 / 1.3m/s (inner / outer layer) continuously. 20 / 12 TE (inner / outer layer) 2 x 440V, 3 phase 60hz, 630Amp 2 x MacGregor, 4 split hinged doors (2 x lower + 2 x upper each side)
MOONPOOL W2W Gangway	7.2 x 7.2m (Remains to open up on Main Deck) Uptime. Contact chartering@geoff.no to check availability
HELIDECK	21m helicopter deck designed for Sikorsky S-92 (12,6 T). Helideck designed and equipped in accordance with relevant authorities. Helicopter monitoring system
WORKING AIR	Two compressors Capacity 284m ³ /h – 9,1 bar pressure Connection on deck: CEJN 320 Female 5 off outlets on deck: <ul style="list-style-type: none">- Aft of ROV HPPS- By main crane boom rest (PORT)- By Main crane pedestal (PORT)- By Auxillary crane (STBD)- By tank vents area on aft deck (STBD)
FO FOR DECK EQUIPMENT	Capacity: 5m ³ /h – 4 bar Pressure Connection on Deck: 1” Cam-lock and ball valve One deck outlet on port side mezzanine deck – in front of FRC
POWER UTILITY STATIONS	See appendix to short spec: Power connections Deck and ROV hangar - Energy Savannah





NAVIGATION EQUIPMENT

1 off S-Band Kongsberg K-Bridge Radar
2 off DGPS for navigation Sailor 6570
2 off Kongsberg K-Bridge ECDIS
4 off Gyro
1 off Echo Sounder Skipper GDS 102
1 off HMS 900 Helideck Monitoring System
1 off Skipper DL 850 Doppler log
1 off AIS TRON AIS TR-8000
1 off DP system Kongsberg K-POS
4 off MRU
4 off Wind sensors
1 off Kongsberg Spottrack Laser system
1 off Radius 1000 incl 1 x Radius 700 & 1 x Radius 550
1 off DGNSS Kongsberg DPS 232
1 off DGNSS Kongsberg DPS i4
1 off Kongsberg HIPAP 502 aft port, 1 x transponder
1 off Sonardyne Ranger 2 (fwd stbd)
1 spare trunk for HPR / Hydr. Acoustic system

COMMUNICATION EQUIPMENT

General: GMDSS installation in accordance with IMO regulations for vessels operating within Sea Area A3
2 off Sailor 6222 GMDSS VHF with DSC
3 off Sailor SP3520 GMDSS VHF Portable
2 off Sailor 6210 VHF
2 off TRON 60s 1 off TRON 40VDR GMDSS EPIRB
3 off TRON SART20 GMDSS SART
2 off Sailor 6110 mini-C GMDSS Inmarsat-C
8 off Motorola DP 4401 EX (Handheld) UHF
4 off Entel HT833 (Handheld) UHF
Array Satellite System
3 off GSM System Mobile Telephone
Array Sat TV System
2 off Jotron TR-810 Helicopter communication
10 off ClearCom Stations installed

TELEPHONE SWITCH BOARD:

Intercom: Radioson Marine

FIRE FIGHTING SYSTEM:

According to Class requirement
CO2 system in Engine Room, Incinerator room
& Cargo room



**GOLDEN
ENERGY**
OFFSHORE

Golden Energy Offshores SALT 305 RSV series, General.

305 RSV series are state of the art vessels with high capacities and good station keeping capabilities.

The hull form design and the diesel electric propulsion system, ensures exceptional performances with regards to fuel consumption, sea keeping, station keeping, speed, and stability.

Low fuel consumption with low emissions and a ballast treatment plant makes the vessels environmental friendly.

The propulsion system comprises two azimuth type propellers, each driven by an electrical motor.

Two tunnel thrusters and one azimuth are installed in the fore part of the Vessel, one tunnel thruster installed aft.

Compliance with IMO Resolution MSC.266(84) Code of safety for special purpose ships will allow the vessel to have more charterers personnel onboard if required.

A ROV hangar is included in the vessel design, to allow for operation of 2 x WROV systems in sheltered conditions

A helideck certified for Sikorsky S-92 Helicopter has been installed to improve logistic possibilities of personnel and spare parts.

Chartering & Operation Managers:

Golden Energy Offshore Management AS,

St. Olavsplass 1

N-6002 Ålesund, Norway.

Tel: +47 70 10 26 71 / +47 97 42 88 84

Web: www.geoff.no

chartering@geoff.no

