

managers and crews!

- Excellent adhesion and elongation
- Convenient, easy-open 2 gallon pail
- No mixing required
- Excellent for cold weather application
- Rain ready in minutes!
- Permanent, durable repairs

From roof maintenance to duct work repair, with a pail of Enduris Liquid Flashing in your truck, you can rest assured that repairs will be quick, efficient and long-lasting.

Enduris Liquid Flashing is a 100% silicone, single-component liquid sealant for repairing virtually all types of substrates.

A single application can seal and repair cracks and seams, protecting against air and water leaks that can lead to mold, mildew, rot and rust, withstanding the most demanding and extreme environments.

Other potential applications include perimeters of skylights, rain gutters, HVAC units, electrical and plumbing penetrations, and vertical to horizontal transition repairs.



Durable. Weatherproof. Secure.

Waterproof - Quickly attains weather-resistant properties and is unaffected by ponding water.

Exceptional Durability - Excellent elongation. This high-performance 100% silicone formula can withstand the most demanding and extreme environments, with long-term resistance to extreme temperatures, UV rays, rain, and snow.

Outstanding Adhesion to Most Surfaces -

- Common roof substrates such as TPO, EPDM, metal, concrete and more.
- Metal including aluminum or steel for gutters and HVAC units
- Horizontal and vertical concrete and masonry such as brick or cement block materials.

No Mixing, No Primer, Low Odor - Simply snap open the pail and the product is ready to use- enabling time and money savings on labor and extra material costs. Its low odor will be welcomed by applicators, and be of minimal effect to the building interior.

Easy to Use - The material can be applied with a trowel, stiff brush or gloved hand, with sufficient open time for tooling before it cures. High viscosity helps ensure coating remains in place on high pitches, vertical surfaces, or parapets until it fully cures.



Benefit Now and Later



Time and labor savings

With an easy-open pail and no primer required, this product can offer significant cost savings associated with labor, material and time delays. It is re-coatable for situations when a full restoration is needed after a repair.



Cold & Hot weather application

Can be applied throughout the year in temperatures ranging from 0°F to 120°F (-17°C to 49°C), helping to avoid project delays and keeping service departments and crews working.



Contact us for additional information.

siliconesforbuilding.com

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGEMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, ervices, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its fished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right of Supplier covering such use or design in the infringement of any patent or other intellectual property right.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc., or its affiliated companies.

Copyright 2024 Momentive Performance Materials Inc. All rights reserved.

