



Enduris[™] 3500E+ Roof Coating

High Solids Silicone Roof Coating



Licensed Partner

Add Decades to Roof Life in Days

Roofs have it hard. A typical flat roof can experience a 60° C temperature shock from 75°C at the hottest peak to 15° C ambient temperature at night. This constant temperature fluctuation and UV exposure can create tremendous strain over time. Most commonly, roofs fail where dissimilar materials meet at penetrations, seams and edges. Minor structural issues can cause additional challenges such as poor drainage and ponding water.

For over 50 years, professionals have trusted silicones products to deliver durable, long-lasting building solutions. The Enduris Roof Coating system is a fast, efficient and economical alternative to replacement.

Based on GE-heritage technology, the Enduris Roof Coating system is backed by world-class technical support and warranties up to 25 years.

Restore with Silicone

A seamless, stable and energy-efficient coating can dramatically extend roof life expectancy, delaying the need for a costly, time-consuming replacement project.

Silicone is inherently durable and permanently flexible. Unlike carbon-based products like bitumen, acrylics, PU, EPDM, PVC, PMMA etc., silicone is completely UV stable, providing the maximum long-term performance against weather and atmospheric conditions. The entire Enduris Roof Coating system is made from the same 100% silicone, allowing it to expand and contract at the same rate, helping prevent leaks that may result in mold, mildew, wood rot and rust. A white silicone coating also reflects the sun's rays to better control inside temperatures.

Restore with Confidence

Silicone remains stable, flexible and virtually unaffected by daily and seasonal temperature extremes. It will not become brittle or harden as the system ages. The Enduris Roof Coating system provides exceptional, long-term performance.

Ponding water

Whileorganic polymer based coatings tend to fail at the seams, penetrations and edges, especially where water ponds, Enduris Roof Coatings stand up to ponding water.

Life cycle cost

Primerless, single-coat application brings efficiency and cost savings to the installation process. Long-term durability promotes a lower total life cycle cost.

Energy savings

Energy savings versus a darker roof can be as great as 35% on summer cooling costs. Enduris 3500E+ Roof Coating offers excellent color retention and reflectivity with a silicone polymer that is UV stable.

Full compatibility

Using only 100% silicone components that are chemically and adhesively compatible, Enduris 3500E+ Roof Coating helps prevent water leakage, mold/mildew, wood rot and metal rust.

Best-in-class elongation

By remaining flexible with daily and seasonal temperatures throughout the life of the building, this system offers best-inclass elongation, both initially and after decades of exposure.

Certifications

Resistance to expernal fire exposure: Tested and approved for Broof T1, T2, T3 and T4 requirements.

EOTA ETA 18-0472 (W3, S, P2/P1, S1 to S4, TL4, TH4)

CEN/TS 1187

ASTM D6694 (Pass)



RESTORE VIRTUALLY ANY EXISTING ROOF TYPE

Enduris 3500E+ Roof Coating systems are appropriate over most structurally sound existing roofing systems including:

- Single-ply membranes (TPO, EPDM, PVC)
- Bituminous membranes
- Metal
- Concrete
- SPF PU Foam

Contact us for application to additional substrates.



Enduris Roof Coating



Enduris 3500E+ Roof Coating

High-solids, low-VOC, 100% silicone liquid coating applied in a single coat. While a primer is not required, a Bleed Blocker base coat can improve energy savings. Currently available in plastic pails (23 kg), and plastic totes (1225 kg), and in standard colors white, medium gray and black.



Enduris Bitumen Bleed Blocker

Applied as a base coat to asphaltic substrates and surfaces, Enduris Bitumen Bleed Blocker is formulated to seal out oils that can discolor the finish coat. Currently available in 17L metal pails and 709L plastic totes.

Benefit Now and Later



Time and labor savings

With no primer required on coated and uncoated roofing membranes, this system can offer significant cost savings associated with labor, primer and time delays.



Full compatibility

Simplicity & Integrity

From a Trusted Brand

performance, the Enduris 100% silicone roof

compliance to roof restorations and repairs.

Simplified installation promotes safety and

improves efficiency, helping to ensure that

coating system can bring confidence and

With over five decades of product

the job is done right every time.

Can be applied to most existing roof types including bituminous membranes, singleply (TPO, PVC, EPDM), PU SPF foam, concrete and metal.



Cold & hot weather application

Enduris 3500E+ Roof Coating can be rolled or sprayed in temperatures as low as -17°C without freezing and as high as +49°C, helping to extend the roofing season and avoid project delays.



We Stay on Top of It All

In addition to a proven roofing system from a trusted leader, we offer assistance from a project's inception to completion. With decades of experience on some of the world's most innovative structures, the team provides a wealth of knowledge and support to help deliver results including:

1. Project Review

Review of project details to assist with product selection and application based on usage criteria, specifications and customer needs.

2. Drawing Details

Assist in developing drawing details that address project-specific terminations, transitions and penetrations.

3. Project Testing

On-site testing for substrate adhesion or compatibility with other building materials if necessary.

4. Project Warranty[†]

Warranties are offered for long-term assurance.



siliconesforbuilding.com



Partner

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGEMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its fished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the

Before purchasing or using any Momentive products, please visit www.siliconeforbuilding.com/LegalDisclaimer to view our full product and sales disclaimer. Copyright 2025 Momentive Performance Materials Inc. All rights reserved.