

B.

Margin

A favourite for designers, Margin takes office flooring to the edge. Available as square or rectangular tufted tiles in warm trending tones and much-loved high-contrasting colours with charcoal backgrounds, it evokes a sense of dynamic texture and motion. Featuring Belgotex’s unique Stainproof Miracle Fibre, these floors endure the fast pace of business and complement the aesthetic identity of any brand. With 9 carefully curated colours, Margin’s tessellated pattern creates versatile and stylish spaces inspired by organic modernity.

Extended Specifications

Use Classification: (EN 1307)	Medium / General Commercial
Construction:	Tufted Multi Scroll Loop Pile
Product Description:	Tufted Loop Pile Bitumen Tile
Yarn Type:	Stainproof Miracle Fibre – Polypropylene and Stain Proof Solution Dyed Nylon
Yarn Mass: (ISO 8543)	±550 (g/m²) (±15) ±16.22 (oz/yd²) (±0.44)
Pile Height: (ISO 8543)	±5 (mm) (±0.5) ±0.19 (in) (±0.02)
Total Thickness: (ISO 8543)	±6.5 (mm) (±0.5) ±0.25 (in) (±0.02)
Total Mass: (ISO 8543)	±4075 (g/m² **) (±5%) ±120.19 (oz/yd² **) (±5%)
MTS Sizes (tile):	50x50cm/100 × 25cm 19.69x19.69 (in)/39.37 x9.84 (in)
MTS Backing Options:	NexBac (NB)



B.

Extended Specifications

Machine Gauge:	1/10”
Stitch Rate:	36 stitches/10cm ? stitches/3.94 (in)
Fire Classification: (EN1305)	Bfl -s1 / Rating 3(SANS10177-4)
Colour Fastness to light: (NF EN ISO 105-BO2)	> 6.0
Colour Fastness to Rubbing (staining): (ISO 105-X12)	4-5
Colour Fastness to Water (staining): (ISO 105-EO1)	4-5
Electrostatic Propensity: Body voltage: (ISO 6356: 2012)	≤ 2.0 kV
Sound Absorption (NexBac NB): (ISO 354: 2023)	aw: 0.15
Sound Insulation (NexBac NB): (ISO 10140-3: 2021)	25 dB
Thermal Resistance: (ISO 8302: 2001)	0.0740 m².KW
Dimensional Stability: (ISO 986: 2006)	≤ 0.2%
VOC Emissions: (ASTM D5116: 2017) (GBCSA/ GBCA & CRI Specifications)	Passed
Castor Chair Suitability: (NF EN 985 – Method A)	Occasional Use
Warranty:	15 years
Guarantee:	5 years

** Weighted Average



B.



Charmed Tone



Chic Contrast



Contemporary Calm



Muted Grace



Natural Harmony



Subtle Innovation



Timeless Edge



Trendy Take



Urban Flair

Margin




Medium/General Commercial



Institution




Commercial




Planks



Modular



Suitable for Staircases



Underfloor Heating



Eco-Friendly



From Local & Imported Goods



Bill of Quantities

- Belgotex MARGIN 50x50cm / 100x25cm width Medium/General Commercial 6.5mm NexBac tiles are manufactured from Stainproof Miracle Fibre - Polypropylene and Stainproof Solution Dyed Nylon.
- This product is to be in accordance with the SANS 10186 fitting code of practice.
- Belgotex (Fringe) tiles/planks to be installed in the following directions: (Ashlar/Random Ashlar/Brick/Monolithic/Herringbone(planks)/Tessellated).
- Belgotex recommends the use of carpet protector mats where castor wheels are used.
- 15-year warranty and 5-year guarantee.
- Made in South Africa
- Green tag level A Gold rated certification.

Product characteristics may vary due to the nature of manufacturing. To combat colour variance do not install more than one dye lot in a single colour tile/plank installation. Where different dye lots and products are mixed and matched then size variations could take place and tiles might need to be altered during installation. When installing two or more different colours in tiles/planks/shapes then there is no issue mixing dye lots together. Sample swatches have been cut from an overall design; therefore, the decoration and shades may vary. A difference in appearance from the pattern is likely, as the product is not intended to have a uniform appearance.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.