

B.

IG Granit SD

Precision Oriented.

The IQ Granit SD is a durable, static-dissipative vinyl flooring designed for heavy-traffic environments such as laboratories, clean rooms, server rooms and ESD-sensitive areas in hospitals. It offers reliable and stable conductivity while maintaining the exceptional durability characteristic of the IQ flooring range. Crafted to complement the colours of the IQ Granit multi-solution family, it seamlessly integrates with other products and accessories for a cohesive design.

Extended Specifications

Type of Installation:	Fully Flexible Static dissipative non-directional vinyl sheeting with PUR
Use Classification: (EN 1307)	Heavy Commercial
Total Weight: (ISO 23997)	2800 (g/m²) 82.58 (oz/yd²)
Total Thickness: (ISO 24346)	2.0 (mm) 0.07 (in)
Roll Size:(l x w)	23 × 2 (m) 905.51 × 78.74 (in)
Backing Type:	Homogenous Vinyl Floor Covering
Chemical Resistance: (EN ISO 26987)	Excellent Resistance
Electrical Resistance: (EN/IEC 61340-4-1,100 V)	R ≤ 10 ⁹ Ohms*
Fire Classification: (EN 13501-1)	Bfl-s1



An exclusive partnership with 

Belgotex™

B.

Extended Specifications

Slip Resistance: (DIN 51130)	R9
Residual Indentation: (EN ISO 24343-1)	<0.10mm
Thermal Conductivity: (EN 12667)	0.01m² K/W
Electrostatic Propensity: (Body Voltage Test) (EN 1815 Method A)	≤2.0kV
Dimensional Stability: (EN ISO 23999)	≤0.40% for rolls
Colour Fastness: (ISO 105-B02)	≥7
Seam Strength: (EN 684)	Individual values ≥ 240N/50mm
Castor Chair Suitability: (EN ISO 4918)	Suitable
Dynamic Coefficient of Friction:	n/a
Floor Heating System:	Yes, max 27°C
VOC Emissions: (EN 16516)	Platinum (≤10 µg/m³)
Bacterial Resistance: (ISO 846 Part C)	Does not promote growth
Warranty:	20 years
Sustainability:	Floorscore



B.



Granit Grey 0948

IG Granit SD

Heavy Commercial

Commercial

Hospitality

Institution

Anti-Bacterial

Office Chair Castor Wheels

Suitable for Staircases

Underfloor Heating

Natural Look

Bill of Quantities

- Belgotex IQ GRANIT SD 2.0mm Homogenous Heavy Commercial Use Fully Flexible Static dissipative non-directional vinyl sheeting
- 23 × 2 m with 2.0mm wear layer.
- 20 year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification

Note: Belgotex offers customization of this product in colour. Please contact a Belgotex representative for more information.

Product characteristics may vary due to the nature of manufacturing. To combat colour variance do not install more than one dye lot in a single installation. Sample swatches have been cut from an overall design; therefore, the decoration and shades may vary. A difference in appearance from the pattern is likely, as the product is not intended to have a uniform appearance.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.