

# B\_

## Fortitude

Inspired by great African Queens, these four powerful designs share an old-world eloquence boasting timeless appeal. The parquet look has been trending internationally for centuries, and the myriad rich patterns will always be the stylish choice. Fit for loyalty, they’re now ready to rule your great rooms.

### Extended Specifications

|                             |                            |
|-----------------------------|----------------------------|
| Use Classification:         | Heavy Commercial           |
| Type of Installation:       | Dry Back (Stick Down)      |
| Overall Thickness:          | 2.5mm                      |
| Wear Layer Thickness:       | 0.55mm                     |
| Plank Size:                 | 1516.9mm x 228.6mm (l x w) |
| SQM Per Box:                | 3.47sqm                    |
| Quantity of Planks Per Box: | 10                         |
| VOC Tested:                 | Passed                     |
| Certification:              | Global GreenTag            |
| Quantity Per Box:           | 3.47m                      |
| Number of planks:           | 10 planks per box          |
| Chemical Resistance:        | YES (EN 26987)             |
| Fire Index:                 | Bfl-s1 (EN13501)           |
| Slip Resistance:            | DS-R10 (DIN 51130)         |
| Residual Indentation:       | < 0.1mm (EN 24343)         |

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
| Thermal Conductivity:    | 0.091 W/m*K (EN 12664:2001)                             |
| Electrostatic Behaviour: | 0.1 kV (EN 1815)                                        |
| Dimensional Stability:   | ≤0.25% (EN 23999)                                       |
| Colour Fastness:         | m > 6 Grade (ISO 105-B02)                               |
| Sound Absorption:        | Approx. 3dB (EN 10140)                                  |
| Castor Chair:            | Yes, Type W (EN 4918)<br>(Use soft non-staining wheels) |

Note: The pattern design in the Fortitude range do not line up. This is part of the product design, and is not a flaw in the product.





# B.



Amina



Asantewa




Makeda



Nefertiti

# Fortitude




Underfloor  
Heating



Heavy  
Residential



Heavy  
Commercial



Suitable for  
Staircases



## Bill of Quantities

- Belgotex Fortitude 2.5mm heavy commercial dry back stick down LVT.
- 1516.9mm x 228.6mm (l x w) with 0.55mm wear layer.
- 20-year residential warranty and 10-year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.