

## **Vertu<sup>™</sup> TOUCH 10 g Procedure for** Peanuts, Peanut Paste, & Tree Nuts

See table below for consumable kit reorder number

- Use strips at room temperature 20-25 °C (68-77 °F).
- Do not open the strip pouch until ready to use the strip.
- Bring the strip to room temperature if necessary.

To calibrate the Vertu TOUCH reader:

Scan the Afla-V barcode\* for the sample type and lot of strips being used.

[Barcode remains stored in Vertu TOUCH reader for future use.]



While strip test develops, enter the sample ID into Vertu TOUCH reader.

- ► Fully insert the Afla-V HS strip into the Vertu TOUCH (the round opening in first).
- ► Press [Start Measurement] key on touch screen to read result.



- ► Weigh 10 g ± 0.1 g finely ground sample or paste into 250 mL Vertu PREP tube (#600001956).
- Add 50 mL of AQUA Premix to Vertu PREP tube.
- ► Close the lid, shake briefly to suspend all sample into liquid.





- ► Press [Print] to print the result.
- ► Press [Same Barcode] to run the next test using the same lot of strips.
- ► Press [Change Barcode] to change the method or lot of strips being used.



- Set Vertu PREP mixer timer for 30 seconds. Push down and twist to lock in place; the mixer will start and stop automatically.
- Pour the extract into a V-Filter with cup for no more than 5 minutes.





- ► Transfer 100 µL of filtered extract to the Afla-V HS strip by dropping (~1 drop/second) vertically into the sample well.
- ➤ Start the timer and allow the strip to develop for exactly 5 minutes on a flat surface.





Scan barcode to download the Strip Test **Reference Guide** 

For additional information, please visit vicam.com/docs/vertu-strip-test-reference-guide



Strips should be stored at 2-30 °C (36-86 °F) Store AQUA Premix at room temperature.

Sample Type	Barcode*	Range/LOD	Reorder#
Peanuts/peanut paste	I	0-100 ppb/2 ppb	176005240 <mark>I</mark>
Pecans, Brazil Nuts, Walnuts	M	0-40 ppb/2 ppb	176005240 <mark>M</mark>
Pistachios, Almonds, Hazelnuts, Cashews	N	0-40 ppb/2 ppb	176005240 <b>N</b>

**Orders:** 

Tel: +1-877.228.4244 +1-417.725.6588

Email: orders@vicam.com

**Technical Support:** 

+1.800.338.4381

+1.508.482.4935

Email: techservice@vicam.com

Waters™ VICAM...

www.vicam.com



## **Vertu<sup>™</sup> TOUCH 5 g Procedure** for Peanuts & Peanut Paste

Consumable kit reorder number: 176005240I

- Use strips at room temperature 20-25 °C (68-77 °F).
- Do not open the strip pouch until ready to use the strip.
- Bring the strip to room temperature if necessary.

To calibrate the Vertu TOUCH reader:

Scan the Afla-V barcode\* for the sample type and lot of strips being used.

[Barcode remains stored in Vertu TOUCH reader for future use.]



While strip test develops, enter the sample ID into Vertu TOUCH reader.

- ► Fully insert the Afla-V HS strip into the Vertu TOUCH (the round opening in first).
- ► Press [Start Measurement] key on touch screen.



- ► Weigh 5 g ± 0.1 g finely ground sample or paste into 50 mL Vertu PREP tube (#600001929).
- ► Add 25 mL of AQUA Premix to Vertu PREP tube.
- ► Close the lid, shake briefly to suspend all sample into liquid.



► Press [Print] to print the result.

- ► Press [Same Barcode] to run the next test using the same lot of strips.
- ► Press [Change Barcode] to change the method or lot of strips being used.

Vertu TOUCH



- Set Vertu PREP mixer timer for 30 seconds. Push down and twist to lock in place; the mixer will start and stop automatically.
- Pour the extract into a V-Filter with cup for no more than 5 minutes.



- ► Transfer 100 µL of filtered extract to the Afla-V HS strip by dropping (~1 drop/second) vertically into the sample well.
- ➤ Start the timer and allow the strip to develop for exactly 5 minutes on a flat surface.





Scan barcode to download the Strip Test **Reference Guide** 

For additional information, please visit vicam.com/docs/vertu-strip-test-reference-guide



Strips should be stored at 2–30 °C (36–86 °F) Store AQUA Premix at room temperature

 Barcode (I)\*, Peanuts/Peanut Paste; Range 0-100 ppb, Limit of detection: 2 ppb

**Orders:** 

Tel: +1-877.228.4244 +1-417.725.6588

Email: orders@vicam.com

**Technical Support:** 

+1.800.338.4381

+1.508.482.4935

Email: techservice@vicam.com

Waters VICAM

www.vicam.com