

BREWERY

HOSES & ACCESSORIES



TIPCO
TECHNOLOGIES

Focused
Flexible
Solutions

 **TIPCO**
e-Store

Brewery Hoses and Accessories

TIPCO Technologies is proud to offer brewery hose assemblies, hoses, fittings, and accessories from premier brands.

Choosing the right equipment for your brewery, distillery, or winery can be a complex process. Prevent downtime, production mistakes, and inefficiency by working with TIPCO to select the correct hoses and fittings for your operation.

- Select top-of-the-line products from Dixon Valve and Coupling, Continental ContiTech, and TIPCO's line of hose assemblies fabricated with brewery needs in mind.
- FDA-approved hoses, tubing, and fittings.
- Wide selection of hoses and tubing to ensure you pick the right hose depending on the liquid it will transfer.
- Wide selection of sanitary gauges, sight glasses, check valves, and sample valves.
- Selection of sanitary wash-down hoses, hose assemblies, and fittings to ensure cleanliness of your production space.

Questions? TIPCO Technologies has a dedicated team of brewery hose and fitting experts to guide you as you outfit your new brewery and maintain your operation.





TIPCO e-Store



The TIPCO E-Store has more than just online ordering.

- Shop based on your Customer-Specific Pricing
- View Live Inventory Across all TIPCO locations
- View Spec Data and item images
- View Open Orders
- View Order History
- Create Custom Catalogs
- View Invoice History
- Pay Invoices Online
- Request Quotes

All your Brewery needs at your fingertips on **shop.tipcotech.com!**

Index

Continental Elite 5

Brew Master Preferred 5

TIPCO Brewery Build-Out 6

Brewery Pump 6

Brewery Assemblies 7

Protection Rings 9

TIPCO Ready Ship Assemblies 9

TIPCO T-Rack 13

Brewers Hose and Tubing 14

Washdown Equipment

 Washdown Nozzles 21

 Washdown Adapters 22

 Washdown Swivel Fittings 24

 Spray Balls 25

Tri-Clamp Fittings 26

Tri-Clamp Hose Stems 31

Reducers 32

Clamps 33

Clever Clamps 34

Clamp Gaskets 34

Swivels 36

Sample Valves 36

Sanitary Check Valves 36

Butterfly Valves 37

Sight Glasses 38

Pressure Gauges 39



What does it mean to be Continental Elite?



ELITE
DISTRIBUTOR

Only a select few Distributors have earned the status of Continental Elite. TIPCO Technologies has been a premier market leader in industrial hose fabrication and testing for over 135 years. As a top-tier Continental ELITE distributor and a 3rd party verified by UL® Continental STAR fabricator, TIPCO Technologies offers innovative and cost-effective Continental solutions.

By working with TIPCO Technologies, a Continental Elite distributor, for your brewery hose and fitting needs, you are getting a trusted partner with over a century of industry knowledge and product expertise to guide you in your selections.

TIPCO Brewmaster Preferred

As product experts in brewery hoses and fittings, TIPCO has organized our collective knowledge and experience into a way to identify the best products for your brewery operations.

With the Brewmaster Preferred identification, we hope browsing our selected brewery offerings is like having your own dedicated TIPCO product expert by your side.



• TIPCO • BREWERY BUILD-OUT

TIPCO is your partner in your brewery build-out

TIPCO understands all the factors that go into choosing the right brewery pump for your operation.

Do you need help selecting the right brewery pump?
Contact sales@tipcotech.com or 410-356-0003 to have a TIPCO product expert on-site to assist you with your selection.

Brewery Pump Centrifugal Rotary Pump

MB100 Series Centrifugal Pump by Dixon Valve

The MB100 Series centrifugal pump by Dixon Valve could be the right choice for transferring non-viscous liquids at a high volume and a relatively low pressure.

Construction

- All product contact steel surfaces: 316L Stainless Steel
- All non-product contact steel surfaces: 304 Stainless Steel
- Product contact seal elastomers: FKM or EPDM
- Product contact hard seal materials: PTFE, carbon and silicon carbide

Features

- Standard Clamp – Uses a standard 4" tube clamp for easy removal and adjustment of the casing. Eliminates post and tab construction.
- Seal Design – Robust single mechanical seal design with silicon carbide stationary seal-face and carbon rotary seal-face.
- Seal Performance – Efficient seal path promotes seal cooling and provides less restrictions to adequately clean the seal.
- Impeller & Shaft Design – Sealed impeller provides optimal hygienic performance while the split shaft compression collar improves shaft concentricity, reduces vibration, and improves seal life.
- Drop-in replacement for other C-100 series pumps.
- Wet end mounts to a standard 56C frame motor



Brewer Assemblies

Continental Vintner Reserve 250 EPDM Hose Assemblies



Vintner Reserve is primarily for liquid transfer. For handling in-plant and/or tank truck transfer of wine, beer, portable water and other non-oily liquid foodstuffs. The monofilament helix is rust proof and is a crush-resistant alternative to traditional softwall or steel wire reinforced hoses.

Temperature: -40°F / -40°C ~ 220°F / 104°C

Tube: EPDM (Meets FDA, USDA & 3-A Sanitary Standard 18-03)

Reinforcement: Spiral-Plied Fabrics, Monofilament

Cover: EPDM Rubber

Pressure Rating: 250 PSI

Available Sizes

Available in 1 inch, 1-1/2 inch, & 2 inch and 5–50 foot lengths (5 foot increments). Assemblies are professionally fabricated with tri-clamps.

Continental Vintner Lite 150 EPDM Hose Assemblies



Vintner LITE 150 is a versatile hose for multiple applications in the food and beverage industry. The special EPDM tube handles high temperatures and the most demanding cleaning conditions. The monofilament helix is rust-proof and is a crush-resistant alternative to traditional soft wall or steel wire reinforced hoses. Thanks to its lightweight it is an ideal solution for high traffic areas in wineries and breweries.

Temperature: -30°F / -34°C ~ 220°F / 104°C

Tube: EPDM (Meets FDA, USDA & 3-A Sanitary Standard 18-03)

Reinforcement: Spiral-Plied Fabrics with monofilament helix

Cover: EPDM Rubber

Pressure Rating: 150 PSI

Available Sizes

Available in 1 inch, 1-1/2 inch, and 2 inch and 5–50 foot lengths (5 foot increments). Assemblies are professionally fabricated with tri-clamps.

Kuriyama BREWT® Hose Assemblies

The BREWT® from Kuriyama is a versatile hose for applications requiring superb flexibility and light weight, while still maintaining high strength and durability. Its high purity tube will not hold taste or odor, making it perfect for beverage production.



Temperature: -22°F (-30°C) to +226°F (+108°C)

Tube: White Chlorobutyl meeting 3A (18-03) and FDA requirements.

Reinforcement: High tensile textile cords with specially designed embedded helix wires.

Cover: Red smooth NR/EPDM blend for abrasion and ozone resistance.

Pressure Rating: 150 PSI

Available Sizes

Available in 1 inch, 1-1/2 inch, and 2 inch and 5–50 foot lengths (5 foot increments). Assemblies are professionally fabricated with tri-clamps.

Brewer Assemblies

Continental ExtremeFlex® Beverage Assemblies with EZ Clean Cover



Plicord® ExtremeFlex™ Beverage with EZ Clean Cover is primarily for liquid transfer. For beer, wine, distillery, and beverage transfer processing facilities. Ideal for applications requiring flexible and/or tight bend connections. Non-phthalates compound.

Temperature: -30°F / -34°C ~ 220°F / 104°C

Tube: White Chlorobutyl meeting 3A (18-03) and FDA requirements.

Reinforcement: Spiral-Plied Fabrics with Double Galvani

Cover: EZ Clean Cover

Pressure Rating: 250 PSI

Available Sizes

Available in 1 inch, 1-1/2 inch, and 2 inch and 5-50 foot lengths (5 foot increments). Assemblies are professionally fabricated with tri-clamps.



Protection Rings

Continental Natural Rubber/SBR Protection Ring

Temperature Range: -4 to 176 deg F

Protection rings are used with tri-clamp fittings to protect the fitting, floor, and surrounding equipment from damage.

- Protects the sealing surfaces of the fittings during installations and handling of hose assemblies
- Designed to fit common hose outer diameters
- Easy installation
- Increases the lifetime of the hose assembly by ensuring easy hose handling
- Protects the ground at your site
- Prevents water damming

Part Number	Size	Length
CTI PROTECTION RING 1IN	1/4 in	1 in
CTI PROTECTION RING 1.5IN	11/32 in	1-1/2 in
CTI PROTECTION RING 2IN/2.6IN OD	3/8 in	2 in



Ready Ship Hose Assemblies

Assemblies Ready to Ship

At your brewery, you know that availability is the best ability you can have. To meet this expectation, TIPCO has identified the most used hose assemblies in the industry and has strategically stocked them within one day shipping to you. If it's Ready Ship, its ready for your brewery.

TIPCO Ready Ship Assemblies

Beverage and Food Grade Assemblies

Plicord® ExtremeFlex™ Beverage with EZ Clean Cover is primarily for liquid transfer. For beer, wine, distillery and beverage transfer processing facilities. Ideal for applications requiring flexible and/or tight bend connections. Non-phthalates compound.



FDA/USDA Compliant and conforms to 3-A Sanitary Standard 18-03

Assemblies listed are professional fabricated with tri-clamps. Can be custom-made to required specifications.

TIPCO Part Number	Inside Dia. (in)	Length (ft)	Color
EXTREMEFLEX-BEV-BLUE-1.5-TC-TC-10FT	1.5 in	10 ft	Blue
EXTREMEFLEX-BEV-BLUE-1.5-TC-TC-20FT	1.5 in	20 ft	Blue
EXTREMEFLEX-BEV-BLUE-2-TC-TC-5FT	2 in	5 ft	Blue
EXTREMEFLEX-BEV-BLUE-2-TC-TC-10FT	2 in	10 ft	Blue
EXTREMEFLEX-FOOD-2-TC-TC-20FT	2 in	10 ft	Gray
EXTREMEFLEX-FOOD-3-TC-TC-20FT	3 in	20 ft	Gray
EXTREMEFLEX-BEV-GREEN-2-TC-TC-10FT	2 in	10 ft	Green
EXTREMEFLEX-BEV-RED-1-TC-TC-5FT	1 in	5 ft	Red
EXTREMEFLEX-BEV-RED-1.5-TC-TC-5FT	1.5 in	5 ft	Red
EXTREMEFLEX-BEV-RED-1.5-TC-TC-10FT	1.5 in	10 ft	Red
EXTREMEFLEX-BEV-RED-2-TC-TC-5FT	2 in	5 ft	Red
EXTREMEFLEX-BEV-RED-2-TC-TC-10FT	2 in	10 ft	Red
EXTREMEFLEX-BEV-YELLOW-2-TC-TC-10FT	2 in	10 ft	Yellow



Sanitary Hose Assemblies

Part Number	Description	Inside Dia. (in)	Length (ft)
332-2-SSC-SSE-10FT	T-FLEX FDA, Sanitary Hose Assembly, Domestic Stainless Steel CxE	2 in	10 ft
332-2-TC-TC-10FT	T-FLEX FDA, Sanitary Hose Assembly, Stainless Steel TCxTC	2 in	10 ft
WHITE-FLEXWING-2-TC-TC-5FT	White Sanitary Process Hose Assembly, TCxTC	2 in	5 ft
WHITE-FLEXWING-2-TC-TC-10FT	White Sanitary Process Hose Assembly, TCxTC	2 in	10 ft
FLEXTRA-GREY-3-PTC-PTE-10FT	Gray Sanitary Hose Assembly, Domestic Aluminum CxE	3 in	10 ft

TIPCO Ready Ship Assemblies

Washdown Assemblies

TIPCO Technologies Super Sani-Wash™ 3/4 IN FGHT x 1/2 IN Male NPT Swivel Brass

Sanitary Washdown; Non-FDA Compliant, High Temperature Washdown

Tube Material: White - EPDM Synthetic Rubber, FDA Compliant

Cover Material: EPDM Synthetic Rubber with Microban®

Construction: Spiral Textile Reinforcement

Pressure Rating: 300 psi

Method of Attachment: Stainless Steel Crimp Ferrule

Temperature Range: -40 deg F - 210 deg F



Part Number	Inside Diameter	Outside Diameter	Hose Length
SUPER-SANIWASH-3/4FGHTX1/2MPB-25FT	0.75 in	1.17 in	25 ft
SUPER-SANIWASH-3/4FGHTX1/2MPB-50FT	0.75 in	1.17 in	50 ft
SUPER-SANIWASH-3/4FGHTX1/2MPB-75FT	0.75 in	1.17 in	75 ft
SUPER-SANIWASH-3/4FGHTX1/2MPB-100FT	0.75 in	1.17 in	100 ft



TIPCO Technologies Yellow Fortress® 3/4 IN FGHT x 1/2 IN Male NPT Swivel Brass

Sanitary Washdown; Non-FDA Compliant, Oil Resistant, High Temperature Washdown

Tube Material: Black - Nitrile Synthetic Rubber; ARPM Class A (High Oil Resistance (Non-FDA Compliant))

Cover Material: Yellow - Carbryn™ Synthetic Rubber, ARPM class A (High Oil Resistance) with Microban®

Construction: Spiral Synthetic Yarn; Pressure Rating: 300 psi

Method of Attachment: Stainless Steel Crimp Ferrule

Temperature Range: -20 deg F-210 degrees F

Part Number	Inside Diameter	Outside Diameter	Hose Length
FORTRESS-YELLOW-3/4FGHTX1/2MPB-25FT	0.75 in	1.19 in	25 ft
FORTRESS-YELLOW-3/4FGHTX1/2MPB-50FT	0.75 in	1.19 in	50 ft
FORTRESS-YELLOW-3/4GHTX1/2MPB-75FT	0.75 in	1.19 in	75 ft
FORTRESS-YELLOW-3/4GHTX1/2MPB-100FT	0.75 in	1.19 in	100 ft



TIPCO Technologies Blue Fortress® 3/4 IN FGHT x 1/2 IN Male NPT Brass

Sanitary Washdown; FDA Compliant, Oil Resistant, High Temperature Washdown

Tube Material: White - Nitrile Synthetic Rubber (FDA Compliant)

Cover Material: Blue - Carbryn™ Synthetic Rubber, ARPM class A (High Oil Resistance) with Microban®

Construction: Spiral Synthetic Yarn

Part Number	Inside Diameter	Outside Diameter	Hose Length
FORTRESS-BLUE-3/4FGHTX1/2MPB-25FT	0.75 in	1.19 in	25 ft
FORTRESS-BLUE-3/4FGHTX1/2MPB-50FT	0.75 in	1.19 in	50 ft
FORTRESS-BLUE-3/4FGHTX1/2MPB-75FT	0.75 in	1.19 in	75 ft
FORTRESS-BLUE-3/4FGHTX1/2MPB-100FT	0.75 in	1.19 in	100 ft



TIPCO Ready Ship Assemblies

Washdown Assemblies

TIPCO Technologies Super Sani-Wash™ 3/4 IN FGHT x 1/2 IN Male NPT Swivel Stainless Steel

Sanitary Washdown; Non-FDA Compliant, High Temperature Washdown

Tube Material: White - EPDM Synthetic Rubber, FDA Compliant

Cover Material: Microban

Construction: Spiral Textile Reinforcement

Pressure Rating: 300 psi

Method of Attachment: Stainless Steel Crimp Ferrule

Temperature Range: -40 deg F - 210 deg F



Part Number	Inside Diameter	Outside Diameter	Hose Length
SUPER-SANIWASH-3/4FGHTSSX1/2MPSS-25FT	0.75 in	1.17 in	25 ft
SUPER-SANIWASH-3/4FGHTSSX1/2MPSS-50FT	0.75 in	1.17 in	50 ft
SUPER-SANIWASH-3/4FGHTSSX1/2MPSS-75FT	0.75 in	1.17 in	75 ft
SUPER-SANIWASH-3/4FGHTSSX1/2MPSS-100FT	0.75 in	1.17 in	100 ft

TIPCO Technologies Yellow Fortress® 3/4 IN FGHT x 1/2 IN Male NPT Stainless

Sanitary Washdown; Non-FDA Compliant, Oil Resistant, High Temperature Washdown

Tube Material: Black - Nitrile Synthetic Rubber; ARPM Class A (High Oil Resistance (Non-FDA Compliant))

Cover Material: Yellow - Carbryn™ Synthetic Rubber, ARPM class A (High Oil Resistance) with Microban®

Construction: Spiral Synthetic Yarn

Pressure Rating: 300 psi



Part Number	Inside Diameter	Outside Diameter	Hose Length
FORTRESS-YELLOW-3/4FGHTSSX1/2MPSS-25FT	0.75 in	1.19 in	25 ft
FORTRESS-YELLOW-3/4FGHTSSX1/2MPSS-50FT	0.75 in	1.19 in	50 ft
FORTRESS-YELLOW-3/4FGHTSSX1/2MPSS-75FT	0.75 in	1.19 in	75 ft
FORTRESS-YELLOW-3/4FGHTSSX1/2MPSS-100FT	0.75 in	1.19 in	100 ft

TIPCO Technologies Blue Fortress® 3/4 IN FGHT x 1/2 IN Male NPT Stainless Steel

Sanitary Washdown; FDA Compliant, Oil Resistant, High Temperature Washdown

Tube Material: White - Nitrile Synthetic Rubber (FDA Compliant)

Cover Material: Blue - Carbryn™ Synthetic Rubber, ARPM class A (High Oil Resistance) with Microban®

Construction: Spiral Synthetic Yarn




Part Number	Inside Diameter	Outside Diameter	Hose Length
FORTRESS-BLUE-3/4FGHTSSX1/2MPSS-25FT	0.75 in	1.19 in	25 ft
FORTRESS-BLUE-3/4FGHTSSX1/2MPSS-50FT	0.75 in	1.19 in	50 ft
FORTRESS-BLUE-3/4FGHTSSX1/2MPSS-75FT	0.75 in	1.19 in	75 ft
FORTRESS-BLUE-3/4FGHTSSX1/2MPSS-100FT	0.75 in	1.19 in	100 ft

Washdown Equipment

Stainless Steel Hose Racks

The perfect solution for proper hose assembly storage.

- Compact, sleek design for use in any sanitary environment.
- Arched design ensures proper drainage, extending hose working life.
- Eliminates clutter, preventing safety concerns.
- Storage accommodates assemblies, gaskets, and adapters.
- Conforms with FDA and 3A regulations for hose storage.



Brewer's Hose and Tubing

Continental DRINKLINE® Beverage Hose



Drinkline is primarily for liquid transfer. A quality discharge hose designed specifically for the highly demanding service of transferring non-oily liquid products in wineries and breweries.

Temperature Range: -40°F / -40°C ~ 220°F / 104°C

Tube: EPDM (Meets FDA, USDA & 3-A Sanitary Standard 18-03)

Reinforcement: Spiral-Plied Synthetic Fabric

Cover: EPDM Rubber with a wrapped finish


Pressure Rating: 250 PSI



All bulk hose is available for custom assembly solutions. Minimum order quantity may apply.

Part Number	Inside Diameter (in)	Outside Diameter (in)	Length (ft)
CTI DRINKLINE 1 IN	1 in	1.598 in	100 ft
CTI DRINKLINE 1-1/2 IN	1.5 in	2.114 in	100 ft
CTI DRINKLINE 2 IN	2 in	2.772 in	100 ft

Kuriyama BREWT® Beverage Hose



The BREWT® from Kuriyama is a versatile hose for applications requiring superb flexibility and light weight, while still maintaining high strength and durability. Its high purity tube will not hold taste or odor, making it perfect for beverage production.

Temperature: -22°F (-30°C) to +226°F (+108°C)

Tube: White Chlorobutyl meeting 3A (18-03) and FDA requirements.

Reinforcement: High tensile textile cords with specially designed embedded helix wires.

Cover: Red smooth NR/EPDM blend for abrasion and ozone resistance.

Pressure Rating: 150 PSI

Part Number	Inside Diameter (in)	Outside Diameter (in)	Length (ft)	Bend Radius
KUR BREWT100	1 in	1.54 in	100 ft	2 in
KUR BREWT125	1.25 in	1.81 in	100 ft	2.5 in
KUR BREWT150	1.5 in	2.05 in	100 ft	3 in
KUR BREWT200	2 in	2.56 in	100 ft	4 in
KUR BREWT250	2.5 in	3.11 in	100 ft	5 in

Brewer's Hose and Tubing

Continental Vintner® Lite 150 EPDM Hose



Vintner LITE 150 is a versatile hose for multiple applications in the food and beverage industry. The special EPDM tube handles high temperatures and the most demanding cleaning conditions. The monofilament helix is rust-proof and is a crush-resistant alternative to traditional soft wall or steel wire reinforced hoses. Thanks to its lightweight it is an ideal solution for high traffic areas in wineries and breweries.

Temperature: -30°F / -34°C ~ 220°F / 104°C

Tube: EPDM (Meets FDA, USDA & 3-A Sanitary Standard 18-03)

Reinforcement: Spiral-Plied Fabrics with monofilament helix

Cover: EPDM Rubber

Pressure Rating: 150 PSI



Part Number	Inside Diameter (in)	Outside Diameter (in)	Length (ft)	Bend Radius
CTI VINTNER LITE 1 IN	1 in	1.52 in	100 ft	4 in
CTI VINTNER LITE 1-1/2 IN	1.5 in	1.97 in	100 ft	6 in
CTI VINTNER LITE 2 IN	2 in	2.5 in	100 ft	9 in

Continental Vintner® Reserve 250 EPDM Hose



Vintner Reserve is primarily for liquid transfer. For handling in-plant and/or tank truck transfer of wine, beer, portable water and other non-oily liquid foodstuffs. The monofilament helix is rust proof and is a crush-resistant alternative to traditional softwall or steel wire reinforced hoses.

Temperature: -40°F / -40°C ~ 220°F / 104°C

Tube: EPDM (Meets FDA, USDA & 3-A Sanitary Standard 18-03)

Reinforcement: Spiral-Plied Fabrics, Monofilament

Cover: EPDM Rubber

Pressure Rating: 250 PSI

Part Number	Inside Diameter (in)	Outside Diameter (in)	Length (ft)	Bend Radius
CTI VINTNER 1 IN	1 in	1.59 in	100 ft	3 in
CTI VINTNER 1-1/2IN	1.5 in	2.09 in	100 ft	4 in
CTI VINTNER 2 IN	2 in	2.64 in	100 ft	7 in

Brewer's Hose and Tubing

Continental ExtremeFlex® Beverage with EZ Clean Cover



The ExtremeFlex Beverage Hose is primarily for liquid transfer, Beer, Wine, Distillery and beverage (edible liquid) transfer processing facilities.

Temperature: -30°F / -34°C ~ 220°F / 104°C

Tube: White Chlorobutyl meeting 3A (18-03) and FDA requirements.

Reinforcement: Spiral-Plied Fabrics with Double Galvani

Cover: EZ Clean Cover


Pressure Rating: 250 PSI



All bulk hose is available for custom assembly solutions. Minimum order quantity may apply.

Available Colors	Inside Diameter (in)	Outside Diameter (in)	Length (ft)	Bend Radius
Blue, Green, Red	1 in	1.52 in	100 ft	2 in
Blue, Green, Red	1.5 in	2.03 in	100 ft	3 in
Blue, Green, Red, & Yellow	2 in	2.54 in	100 ft	4 in

Continental Purple Snake® Beverage Hose



Purple Snake is primarily for liquid transfer: Purple Snake® in improved quality is the ideal hose for breweries, wine-presses, bottlers and many other installations in the brewing, beverage and spirits industry.

Temperature: -22°F / -30°C ~ 194°F / 90°C

Tube: White Chlorobutyl meeting 3A (18-03) and FDA requirements.

Reinforcement: Synthetic Fabric

Cover: Red EPDM, Fabric Patterned Special Cover, Resistant to Ozone, Weather, UV and Abrasion

Pressure Rating: 232 PSI

Part Number	Inside Diameter (in)	Outside Diameter (in)	Length (ft)	Bend Radius
CTI PURPLE SNAKE 1IN	1 in	1.44 in	100 ft	6.31 in
CTI PURPLE SNAKE 1.5IN	1.5 in	2.19 in	100 ft	9.06 in
CTI PURPLE SNAKE 2IN	2 in	2.75 in	100 ft	11.81 in

Brewer's Hose and Tubing

Continental Super Sani-Wash™ 300 with Microban®



Continental Sani-Wash™ is used for hot water wash-down and cleanup, up to 210°F (99°C). Use this hose in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries. The optional Microban® cover incorporates antimicrobial built-in product protection and the white tube is comprised of FDA compliant materials.

Tube Material: White - EPDM Synthetic Rubber, FDA Compliant

Cover Material: EPDM Synthetic Rubber with Microban®

Construction: Spiral Textile Reinforcement

Pressure Rating: 300 psi

Temperature Range: -40 deg F - 210 deg F



All bulk hose is available for custom assembly solutions. Minimum order quantity may apply.

TIPCO Part Number	Inside Diameter (in)	Outside Diameter (in)
CTI SUPER SANI-WASH 1/2IN	1/2 in	.84 in
CTI SUPER SANI-WASH 3/4IN	3/4 in	1.17 in

Continental Blue Fortress® 300 with Microban®



Fortress is a high-quality hose construction for hot water up to 210°F (99°C) cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries and creameries. Its super abrasion and oil-resistant cover provides maximum protection against the adverse effects of oil and animal fats. The cover of our Blue Fortress® 300 hose incorporates Microban's® antimicrobial built-in product protection.

Tube Material: White - Nitrile Synthetic Rubber (FDA Compliant)

Cover Material: Blue - Carbryn™ Synthetic Rubber, ARPM class A (High Oil Resistance) with Microban®

Construction: Spiral Synthetic Yarn

Pressure Rating: 300 psi



All bulk hose is available for custom assembly solutions. Minimum order quantity may apply.

TIPCO Part Number	Inside Diameter (in)	Outside Diameter (in)
CTI BLUE FORTRESS 300 1/2IN	1/2 in	.90 in
CTI BLUE FORTRESS 300 3/4IN	3/4 in	1.19 in

Brewer's Hose and Tubing

Continental Yellow Fortress® 300 with Microban®



Fortress is a high-quality hose construction for hot water up to 210°F (99°C) cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries and creameries. Its super abrasion and oil-resistant cover provides maximum protection against the adverse effects of oil and animal fats. The cover of our Blue Fortress® 300 hose incorporates Microban's® antimicrobial built-in product protection..

Tube Material: Black - Nitrile Synthetic Rubber; ARPM Class A (High Oil Resistance) (Non-FDA Compliant)

Cover Material: Yellow - Carbryn™ Synthetic Rubber, ARPM class A (High Oil Resistance) with Microban®

Construction: Spiral Synthetic Yarn

Pressure Rating: 300 psi



All bulk hose is available for custom assembly solutions. Minimum order quantity may apply.

TIPCO Part Number	Inside Diameter (in)	Outside Diameter (in)
CTI YELLOW FORTRESS 300WP 1/2	1/2 in	.90 in
CTI YELLOW FORTRESS 300WP-3/4	3/4 in	1.19 in



The TIPCO E-Store has more than just online ordering.

- Shop based on your Customer-Specific Pricing
- View Live Inventory Across all TIPCO locations
- View Spec Data and item images
- View Open Orders
- View Order History
- Create Custom Catalogs
- View Invoice History
- Pay Invoices Online
- Request Quotes

All your Brewery needs at your fingertips on **shop.tipcotech.com!**



Brewer's Hose and Tubing

Kuriyama Kuri Tec® POLYSPRING® K7160 PVC Standard Wall Food and Beverage Vacuum/Transfer Hose

Standard wall food and beverage-grade vacuum/transfer hose with rated working pressures, spiral wire reinforcement prevents kinking or collapsing, crystal clear allows visual confirmation of product flow, glass-smooth interior reduces material buildup. Silicone-free, one-piece lengths, formulated to comply with FDA, Prop. 65, RoHS and REACH requirements, as well as being non-toxic and non-phthalate.

Part Number	Nominal Size	Length	Bend Radius
KUR K7160-08 1/2IN	1/2 in	50 ft	2 in
KUR K7160-10 5/8IN	5/8 in	50 ft	2-1/2 in
KUR K7160-12 3/4IN	3/4 in	100 ft	3 in
KUR K7160-16 1IN	1 in	100 ft	4 in
KUR K7160-20 1-1/4IN X 50FT	1-1/4 in	50 ft	5 in
KUR K7160-24 1-1/2IN	1-1/2 in	100 ft	6 in
KUR K7160-32 2IN	2 in	50 ft	8 in



TIPCO Technologies Reinforced Vinyl Tubing

Formulated to comply with FDA, Prop. 65, RoHS and REACH requirements, as well as being non-toxic and non-phthalate.

Part Number	Inside Dia. (in)	Length (ft)	Working Pressure at 70° (lbs)
TIPCO RVT-1/4IN	1/4 in	300 ft	250
TIPCO RVT-3/8IN	3/8 in	300 ft	225
TIPCO RVT-1/2IN	1/2 in	300 ft	200
TIPCO RVT-5/8IN	5/8 in	300 ft	200
TIPCO RVT-3/4IN	3/4 in	300 ft	150
TIPCO RVT-1IN	1 in	200 ft	125
TIPCO RVT-1.25IN	1-1/4 in	100 ft	100
TIPCO RVT-1.5IN	1-1/2 in	100 ft	100
TIPCO RVT-2IN	2 in	100 ft	75



TIPCO Technologies Susquehanna PVC Water Suction Hose

Clear PVC with white spiral. Highly versatile and durable, smooth interior prevents material blockage, clear wall allows easy inspection.

Part Number	Nominal Size	Length	Pressure Rating	Bend Radius
GLO 901-075 SUSQUEHANNA	3/4 in	100 ft	100 psi	2 in
GLO 901-100 SUSQUEHANNA	1 in	100 ft	106 psi	4-1/2 in
GLO 901-125 SUSQUEHANNA	1-1/4 in	100 ft	99 psi	5 in
GLO 901-150 SUSQUEHANNA	1-1/2 in	100 ft	89 psi	6 in
GLO 901-200 SUSQUEHANNA	2 in	100 ft	79 psi	8 in
GLO 901-250 SUSQUEHANNA	2-1/2 in	100 ft	65 psi	10 in
GLO 901-300 SUSQUEHANNA	3 in	100 ft	65 psi	12 in




Brewer's Hose and Tubing

TIPCO Technologies Clear Vinyl Tubing

Formulated to comply with FDA, Prop. 65, RoHS and REACH requirements, as well as being non-toxic and non-phthalate, this clear, flexible, lightweight tubing provides full-flow viewing and is ideal for handling liquids.

Part Number	Inside Diameter	Nominal Size	Length	Pressure Rating
TIPCO CVT-1/8INX1/4IN	1/8 in	1/4 in	100 ft	65 psi
TIPCO CVT-3/16INX5/16IN	3/16 in	5/16 in	100 ft	55 psi
TIPCO CVT-1/4INX3/8IN	1/4 in	3/8 in	100 ft	50 psi
TIPCO CVT-5/16INX7/16IN	5/16 in	7/16 in	100 ft	45 psi
TIPCO CVT-3/8INX1/2IN	3/8 in	1/2 in	100 ft	40 psi
TIPCO CVT-1/4INX1/2IN	1/4 in	1/2 in	100 ft	70 psi
TIPCO CVT-3/8INX5/8IN	3/8 in	5/8 in	100 ft	60 psi
TIPCO CVT-1/2INX5/8IN	1/2 in	5/8 in	100 ft	25 psi
TIPCO CVT-1/2INX3/4IN	1/2 in	3/4 in	100 ft	45 psi
TIPCO CVT-5/8INX3/4IN	5/8 in	3/4 in	100 ft	20 psi
TIPCO CVT-5/8INX7/8IN	5/8 in	7/8 in	100 ft	40 psi
TIPCO CVT-3/4INX1IN	3/4 in	1 in	100 ft	35 psi
TIPCO CVT-7/8INX1.125IN	7/8 in	1 1/8 in	50 ft	30 psi
TIPCO CVT-1INX1.25IN	1 in	1 1/4 in	100 ft	25 psi
TIPCO CVT-1.25INX1.5IN	1 1/4 in	1 1/2 in	50 ft	20 psi
TIPCO CVT-1.5INX1.75IN	1 1/2 in	1 3/4 in	50 ft	16 psi
TIPCO CVT-1.25INX1.75IN	1 1/4 in	1 3/4 in	50 ft	40 psi
TIPCO CVT-1.5INX2IN	1 1/2 in	2 in	50 ft	35 psi



TIPCO Technologies Black EPDM Air and Water Hose

Construction Tube: EPDM synthetic rubber, ARPM class C (limited oil resistance)

Cover: Red or Black EPDM synthetic rubber

Reinforcement: Spiral synthetic yarn, 2" is braided

Part Number	Nominal Size	Length	Temperature Rating	Pressure Rating
TIPCO BGP 5/8INX200 PSI	5/8 in	500 ft	-40 deg F - 210 deg F	200 psi
TIPCO BGP 3/4INX300 PSI	3/4 in	400 ft	-40 deg F - 210 deg F	300 psi
TIPCO BGP 1INX300PSI	1 in	450 ft	-40 deg F - 210 deg F	300 psi

Part Number	Nominal Size	Length	Temperature Rating	Pressure Rating
TIPCO RGP 5/8INX300PSI	5/8 in	500 ft	-40 deg F - 210 deg F	300 psi
TIPCO RGP 3/4INX300 PSI	3/4 in	500 ft	-40 deg F - 210 deg F	300 psi
TIPCO RGP 1INX200 PSI	1 in	450 ft	-40 deg F - 210 deg F	200 psi



Washdown Equipment

Washdown Nozzles

Continental Dinga Water-Saving Gun, 363 psi, 32 - 203 deg F

Dinga is water-saving nozzle that has a long service life due to its brass or stainless steel design. It's protected against hot, cold, shock, caustic solutions and acid. Dinga also helps save on energy costs. Other features include: chemical-free cleaning capability and the flow can be adjusted from a fine spray to a concentrated jet.

Part Number

CTI DINGA WATER SAVING GUN



Continental

ELITE
DISTRIBUTOR



Super Klean Brass Standard Spray Nozzles, 150 psi, 2.93 - 7.19 gpm

Temperature Rating: 200 degrees F

Part Number	Description
SKL 150B-DB	150 Dark Blue Brass Standard Spray Nozzle, 1/2 in FPT
SKL 150B-R	150 Red Brass Standard Spray Nozzle, 1/2 in FPT
SKL 150B-W	150 White Brass Standard Spray Nozzle, 1/2 in FPT



Super Klean 304 Stainless Steel Standard Spray Nozzles, 150 psi, 2.93 - 7.19 gpm

Temperature Rating: 200 degrees F

Part Number	Description
SKL 150S-R	150 Red Stainless Steel Standard Spray Nozzle, 1/2 in FPT
SKL 150S-W	150 White Stainless Steel Standard Spray Nozzle, 1/2 in FPT
SKL 150S-G	150 Gray Stainless Steel Standard Spray Nozzle, 1/2 in FPT



Super Klean 150 Stainless Steel Standard Spray Nozzle, 2.93 - 7.19 gpm

Features: Front trigger guard and locking trigger mechanism

Pressure Rating: 150 PSI

Material: 304 Stainless Steel

Temperature Rating: 200 degrees F



Part Number	Description
SKL DH150S-W	150 White Stainless Steel Standard Spray Nozzle, 1/2 in FPT
SKL DH150S-DB	150 Dark Blue Stainless Steel Standard Spray Nozzle, 1/2 in FPT
SKL DH150S-R	150 Red Stainless Steel Standard Spray Nozzle, 1/2 in FPT

Super Klean is a trusted nozzle used by 1000 of food plants and factories. Heavy-duty, long-lasting and durable. Durable cover.

Applications: For use in food, beverage and pharmaceutical plants and factories.

Washdown Equipment

Washdown Adapters

Dixon CDA Brass 360

Male GHT x Female NPT Adapter

Dimension Standards: SAE J530

Temperature: 34 - 195 deg F

Part Number	Connection 1	Thread Size 1	Connection 2	Thread Size 2	Hex Size	Dimensions
DXN 5071204C	3/4 in GHT, Male	3/4-11-1/2	1/4 in NPT, Female	1/4-18	1-1/16 in	3/4 in L
DXN 5071206C	3/4 in GHT, Male	3/4-11-1/2	3/8 in NPT, Female	3/8-18	1-1/16 in	3/4 in L
DXN 5071208C	3/4 in GHT, Male	3/4-11-1/2	1/2 in NPT, Female	1/2-14	1-1/16 in	3/4 in L x 1-1/16 in W
DXN 5071212C	3/4 in GHT, Male	3/4-11-1/2	3/4 in NPT, Female	3/4-14	1-3/16 in	1.37 in L x 1.88 in W



Dixon Brass FGHT Swivel x MNPTF Adapter

Part Number	Connection 1	Connection Size 2
DXN 5041204C	3/4 in GHT Swivel, Female	1/4 in NPT, Male
DXN 5041206C	3/4 in GHT Swivel, Female	3/8 in NPT, Male
DXN 5041208C	3/4 in GHT Swivel, Female	1/2 in NPT, Male
DXN 5041212C	3/4 in GHT Swivel, Female	3/4 in NPT, Male



Dixon Brass GHT Adapter

For Use With: Designated Water and Garden Hoses

Pressure Rating: 150 psi

Temperature: 34 - 195 deg F

Dimension Standards: SAE J530

Part Number	Connection 1	Thread Size 1	Connection 2	Thread Size 2	Hex Size	Dimensions
DXN 5021212C	3/4 in GHT	3/4-11-1/2	3/4 in NPT	3/4-14	1-3/16 in	1.56 in L x 1.88 in W



Dixon Brass MGHT x MNPTF Adapter

Part Number	Connection 1	Thread Size 1	Connection 2	Thread Size 2	Hex Size
DXN 5081206C	3/4 in GHT, Male	3/4-11-1/2	3/8 in NPT	3/8-18	1-1/16 in
DXN 5081208C	3/4 in GHT, Male	3/4-11-1/2	1/2 in NPT	1/2-14	1-1/16 in
DXN 5081216C	3/4 in GHT, Male	3/4-11-1/2	1 in NPT	1-11-1/2	1-3/8 in



Washdown Equipment

Washdown Adapters

Dixon 303 Stainless Steel MGHT x MNPT Adapter

Part Number	Connection 1	Thread Size 1	Connection 2	Thread Size 2	Hex Size	Dimensions
DXN 5081208SS	3/4 in GHT, Male	3/4-11-1/2	1/2 in NPT, Male	1/2-14	1-1/16 in	1-1/2 in L



Dixon 303 Stainless Steel FGHT Swivel x MNPTF Adapter

Part Number	Connection 1	Thread Size 1	Connection 2	Thread Size 2	Hex Size
DXN 5041208SS	3/4 in GHT Swivel, Female	3/4-11-1/2	1/2 in NPT, Male	1/2"-14	1-3/16 in
DXN 5041212SS	3/4 in GHT Swivel, Female	3/4-14	3/4 in NPT, Male	3/4-14	1-3/16 in



Dixon 303 Stainless Steel MGHT x FNPT Adapter

Part Number	Connection 1	Thread Size 1	Connection 2	Thread Size 2	Hex Size	Dimensions
DXN 5071208SS	3/4 in GHT, Male	3/4-11-1/2	1/2 in NPT, Female	1/2-14	1-1/16 in	3/4 in L
DXN 5071212SS	3/4 in GHT, Male	3/4-11-1/2	3/4 in NPT, Female	3/4-14	1-3/16 in	1.37 in L



Dixon 303 Stainless Steel FGHT Swivel x FNPT Adapter

Part Number	Connection 1	Thread Size 1	Connection 2	Thread Size 2	Hex Size
DXN 5021212SS	3/4 in GHT Swivel, Female	3/4-11-1/2	3/4 in NPT, Female	3/4"-14	1-3/16 in



Washdown Equipment

Washdown Swivel Fittings

Dixon BNS44 Brass Connector, 1/2 in NPT Swivel x Hose Shank

Connector for Spray Gun

Part Number	Connection
DXN BNS44	1/2 in; NPT Swivel x Hose



The Right Connection®

Dixon BNS64 Brass Connector, 3/4 in Hose Shank x 1/2 in NPT

Part Number	Connection 1	Connection 2	Dimension
DXN BNS64	3/4 in Hose Stem	1/2 in NPT	3-3/4 in L

Dixon 300 Stainless Steel Ball Type Connector

For Use With: Stainless Spray Nozzles

Part Number	Connection Size	Connection Type	Hose ID
DXN SSA44	1/2 x 1/2 in	NPT x Hose Barb	1/2 in
DXN SSA54	1/2 x 5/8 in	NPT x Hose Barb	5/8 in
DXN SSA64	1/2 x 3/4 in	NPT x Hose Barb	3/4 in



Dixon Stainless Steel Straight Swivel Connector

For Use With: Spray Gun

Part Number	Connection 1	Connection 2
DXN BNS44SS	1/2 in NPT	1/2 in Hose Stem
DXN BNS64SS	1/2 in NPT	3/4 in Hose Stem



Washdown Equipment

Spray Balls



Dixon® Stainless Steel Spray Balls

Ideal for cleaning out all types of tanks.

Part Number	Description
DXN SRH360CMP-G150	Dixon® SRH 304 Stainless Steel Rotating Spray Ball, 1-1/2 in Clamp
DXN SRH360CMP-R150	Dixon® SRH 316L Stainless Steel Rotating Spray Ball, 1-1/2 in Clamp
DXN SRH360NPT-G075	Dixon® SRH360NPT-G075 Mirror-Like Rotating Spray Ball, 3/4 in, 304 Stainless Steel
DXN SRH360NPT-R150	Dixon® SRH 316L Stainless Steel Rotating Spray Ball, 1-1/2 in NPT



Dixon® 316L Stainless Steel Stationary 180 deg Top Spray Ball

Part Number	Connection 1	Dimension
DXN STC-180T-R100	1 in	2.54 in OD x 3.04 in H
DXN STC-180T-R150	1-1/2 in	2.97 in OD x 3.54 in H



Dixon® 316L Stainless Steel Stationary 360 deg Spray Ball

Part Number	Connection 1
DXN STC-360-R100	1 in
DXN STC-360-R150	1-1/2 in

Dixon® 316L Stainless Steel Stationary 180 deg Bottom Spray Ball

Part Number	Connection 1	Dimension
DXN STC-180B-R100	1 in	2.54 in OD x 3.04 in H
DXN STC-180B-R150	1-1/2 in	2.97 in OD x 3.54 in H

Tri-Clamp Fittings

Dixon® 16AMP 304 Stainless Steel Solid Clamp End Cap

Part Number	Connection 1	Dimension
DXN 16AMP-G50-75	1/2 - 3/4 in	0.99 in OD x 0.19 in L
DXN 16AMP-G100-150	1 - 1-1/2 in	1.984 in D x 0.25 in L
DXN 16AMP-G200	2 in	2.516 in OD x 1/4 in L
DXN 16AMP-G250	2-1/2 in	3.047 in D x 0.25 in L
DXN 16AMP-G300	3 in	3.579 in D x 0.25 in L
DXN 16AMP-G400	4 in	4.682 in D x 0.312 in L



Tri-Clamp Fittings

Dixon 22MP 304 Stainless Steel Adapter



Part Number	Connection 1	Dimension
DXN 22MP-G100	1 in Clamp	1 in NPT, Female
DXN 22MP-G100375	1 in Clamp	3/8 in NPT, Female
DXN 22MP-G10050	1 in Clamp	1/2 in NPT, Female
DXN 22MP-G10075	1 in Clamp	3/4 in NPT, Female
DXN 22MP-G100125	1 in Clamp	1-1/4 in NPT, Female
DXN 22MP-G100150	1 in Clamp	1-1/2 in NPT, Female
DXN 22MP-G100200	1 in Clamp	2 in NPT, Female
DXN 22MP-G150	1-1/2 in Clamp	1-1/2 in NPT, Female
DXN 22MP-G150375	1-1/2 in Clamp	3/8 in NPT, Female
DXN 22MP-G15050	1-1/2 in Clamp	1/2 in NPT, Female
DXN 22MP-G15075	1-1/2 in Clamp	3/4 in NPT, Female
DXN 22MP-G150100	1-1/2 in Clamp	1 in NPT, Female
DXN 22MP-G150125	1-1/2 in Clamp	1-1/4 in NPT, Female
DXN 22MP-G150200	1-1/2 in Clamp	2 in NPT, Female
DXN 22MP-G200	2 in Clamp	2 in NPT, Female
DXN 22MP-G20050	2 in Clamp	1/2 in NPT, Female
DXN 22MP-G20075	2 in Clamp	3/4 in NPT, Female
DXN 22MP-G200100	2 in Clamp	1 in NPT, Female
DXN 22MP-G200125	2 in Clamp	1-1/4 in NPT, Female
DXN 22MP-G200150	2 in Clamp	1-1/2 in NPT, Female
DXN 22MP-G200250	2 in Clamp	2-1/2 in NPT, Female
DXN 22MP-G200300	2 in Clamp	3 in NPT, Female
DXN 22MP-G250	2-1/2 in Clamp	2-1/2 in NPT, Female
DXN 22MP-G250100	2-1/2 in Clamp	1 in NPT, Female
DXN 22MP-G250150	2-1/2 in Clamp	1-1/2 in NPT, Female
DXN 22MP-G250200	2-1/2 in Clamp	2 in NPT, Female
DXN 22MP-G250300	2-1/2 in Clamp	3 in NPT, Female
DXN 22MP-G300	3 in Clamp	3 in NPT, Female
DXN 22MP-G300150	3 in Clamp	1-1/2 in NPT, Female
DXN 22MP-G300200	3 in Clamp	2 in NPT, Female
DXN 22MP-G400	4 in Clamp	4 in NPT, Female
DXN 22MP-G400200	4 in Clamp	2 in NPT, Female
DXN 22MP-G400600	4 in Clamp	6 in NPT, Female



Tri-Clamp Fittings

Dixon 21MP 304 Stainless Steel Adapter



Part Number	Connection 1	Connection 2	Dimension
DXN 21MP-G100	1 in Clamp	1 in Male NPT	2-1/4 in L
DXN 21MP-G10050	1 in Clamp	1/2 in Male NPT	2.19 in L
DXN 21MP-G10075	1 in Clamp	3/4 in Male NPT	2.19 in L
DXN 21MP-G100125	1 in Clamp	1-1/4 in Male NPT	2.44 in L
DXN 21MP-G100150	1 in Clamp	1-1/2 in Male NPT	2.44 in L
DXN 21MP-G100200	1 in Clamp	2 in Male NPT	2.63 in L
DXN 21MP-G150	1-1/2 in Clamp	1-1/2 in Male NPT	2-1/4 in L
DXN 21MP-G15050	1-1/2 in Clamp	1/2 in Male NPT	2.19 in L
DXN 21MP-G15075	1-1/2 in Clamp	3/4 in Male NPT	2.19 in L
DXN 21MP-G150100	1-1/2 in Clamp	1 in Male NPT	2.44 in L
DXN 21MP-G150125	1-1/2 in Clamp	1-1/4 in Male NPT	2.44 in L
DXN 21MP-G150200	1-1/2 in Clamp	2 in Male NPT	2.63 in L
DXN 21MP-G200	2 in Clamp	2 in Male NPT	2.64 in L
DXN 21MP-G20075	2 in Clamp	3/4 in Male NPT	2.19 in L
DXN 21MP-G200100	2 in Clamp	1 in Male NPT	2.47 in L
DXN 21MP-G200125	2 in Clamp	1/4 in Male NPT	2.47 in L
DXN 21MP-G200150	2 in Clamp	1-1/2 in Male NPT	2.63 in L
DXN 21MP-G250	2-1/2 in Clamp	2-1/2 in Male NPT	2.88 in L
DXN 21MP-G250150	2-1/2 in Clamp	1-1/2 in Male NPT	2.78 in L
DXN 21MP-G250200	2-1/2 in Clamp	2 in Male NPT	2.78 in L
DXN 21MP-G300	3 in Clamp	3 in Male NPT	3.07 in L
DXN 21MP-G300200	3 in Clamp	2 in Male NPT	3 in L
DXN 21MP-G400	4 in Clamp	4 in Male NPT	3.16 in L



Tri-Clamp Fittings



Dixon B7MP 304 Stainless Steel Tee

Part Number	Connection 1	Connection 2	Connection 3
DXN B7MP-G100	1 in Clamp	1 in Clamp	1 in Clamp
DXN B7MP-G150	1-1/2 in Clamp	1-1/2 in Clamp	1-1/2 in Clamp
DXN B7MP-G200	2 in Clamp	2 in Clamp	2 in Clamp
DXN B7MP-G250	2-1/2 in Clamp	2-1/2 in Clamp	2-1/2 in Clamp
DXN B7MP-G300	3 in Clamp	3 in Clamp	3 in Clamp
DXN B7MP-G400	4 in Clamp	4 in Clamp	4 in Clamp



Dixon 304L Reducing 90 degree Clamp Elbow

TIPCO Part Number	Description
DXN B2CM31MPG200150	2"X1.5" 304L Reducing 90° Clamp Elbow
DXN B2CM31MPG250200	2.5"X2" 304L Reducing 90° Clamp Elbow
DXN B2CM31MPG300200	3"X2" 304L Reducing 90° Clamp Elbow
DXN B2CM31MPG300250	3"X2.5" 304L Reducing 90° Clamp Elbow



Dixon 316L Reducing 90 degree Clamp Elbow

TIPCO Part Number	Description
DXN B2CM31MPR200150	2"X1.5" 316L Reducing 90° Clamp Elbow
DXN B2CM31MPR250200	2.5"X2" 316L Reducing 90° Clamp Elbow
DXN B2CM31MPR300200	3"X2" 316L Reducing 90° Clamp Elbow
DXN B2CM31MPR300250	3"X2.5" 316L Reducing 90° Clamp Elbow



Tri-Clamp Fittings



Dixon B2CMP 304 Stainless Steel 90 deg Elbow

Part Number	Connection 1	Connection 2
DXN B2CMP-G100	1 in Clamp	1 in Clamp
DXN B2CMP-G150	1-1/2 in Clamp	1-1/2 in Clamp
DXN B2CMP-G200	2 in Clamp	2 in Clamp
DXN B2CMP-G250	2-1/2 in Clamp	2-1/2 in Clamp
DXN B2CMP-G300	3 in Clamp	3 in Clamp
DXN B2CMP-G400	4 in Clamp	4 in Clamp



Dixon B2KMP 304 Stainless Steel 45 deg Elbow

Part Number	Connection 1	Connection 2
DXN B2KMP-G100	1 in Clamp	1 in Clamp
DXN B2KMP-G150	1-1/2 in Clamp	1-1/2 in Clamp
DXN B2KMP-G200	2 in Clamp	2 in Clamp
DXN B2KMP-G250	2-1/2 in Clamp	2-1/2 in Clamp
DXN B2KMP-G300	3 in Clamp	3 in Clamp
DXN B2KMP-G400	4 in Clamp	4 in Clamp



Dixon B2KMP 316L Stainless Steel 45 deg Elbow

Part Number	Connection 1	Connection 2
DXN B2KMP-R100	1 in Clamp	1 in Clamp
DXN B2KMP-R150	1-1/2 in Clamp	1-1/2 in Clamp
DXN B2KMP-R200	2 in Clamp	2 in Clamp
DXN B2KMP-R250	2-1/2 in Clamp	2-1/2 in Clamp
DXN B2KMP-R300	3 in Clamp	3 in Clamp
DXN B2KMP-R400	4 in Clamp	4 in Clamp



Tri-Clamp Fittings

Dixon B28AMP 316L Stainless Steel 45 deg Lateral

Part Number	Connection 1	Connection 2	Connection 3
DXN B28AMP-R100	1 in Clamp	1 in Clamp	1 in Clamp
DXN B28AMP-R150	1-1/2 in Clamp	1-1/2 in Clamp	1-1/2 in Clamp
DXN B28AMP-R200	2 in Clamp	2 in Clamp	2 in Clamp
DXN B28AMP-R250	2-1/2 in Clamp	2-1/2 in Clamp	2-1/2 in Clamp
DXN B28AMP-R300	3 in Clamp	3 in Clamp	3 in Clamp
DXN B28AMP-R400	4 in Clamp	4 in Clamp	4 in Clamp



Dixon B2WUMP 316L Stainless Steel 180 deg Return Bend

Part Number	Connection 1	Connection 2
DXN B2WUMP-R100	1 in Clamp	1 in Clamp
DXN B2WUMP-R150	1-1/2 in Clamp	1-1/2 in Clamp
DXN B2WUMP-R200	2 in Clamp	2 in Clamp
DXN B2WUMP-R300	3 in Clamp	3 in Clamp
DXN B2WUMP-R400	4 in Clamp	4 in Clamp
DXN B2KMP-R400	4 in Clamp	4 in Clamp



Dixon B7MP 316L Stainless Steel Tee

Part Number	Connection 1	Connection 2	Connection 3	Hex Size
DXN B7MP-R100	1 in Clamp	1 in Clamp	1 in Clamp	1 in
DXN B7MP-R150	1-1/2 in Clamp	1-1/2 in Clamp	1-1/2 in Clamp	1-1/2 in
DXN B7MP-R200	2 in Clamp	2 in Clamp	2 in Clamp	2 in
DXN B7MP-R250	2-1/2 in	2-1/2 in	2-1/2 in	2-1/2 in
DXN B7MP-R300	3 in Clamp	3 in Clamp	3 in Clamp	3 in
DXN B7MP-R400	4 in Clamp	4 in Clamp	4 in Clamp	4 in



Dixon B28BMP 316L Stainless Steel True Wye

Part Number	Connection 1	Connection 2	Connection 3
DXN B28BMP-R100	1 in Clamp	1 in Clamp	1 in Clamp
DXN B28BMP-R150	1-1/2 in Clamp	1-1/2 in Clamp	1-1/2 in Clamp
DXN B28BMP-R200	2 in Clamp	2 in Clamp	2 in Clamp
DXN B28BMP-R250	2-1/2 in Clamp	2-1/2 in Clamp	2-1/2 in Clamp
DXN B28BMP-R300	3 in Clamp	3 in Clamp	3 in Clamp
DXN B28BMP-R400	4 in Clamp	4 in Clamp	4 in Clamp



Tri-Clamp Hose Stems

Dixon 14MPHRL 304 Stainless Steel Brewery Adapter

Part Number	Connection 1	Connection 2	Dimension
DXN 14MPHRL100	1 in Hose Barb	1 in Tri-Clamp	1.045 in Dia. x 3.5 in L
DXN 14MPHRL150	1-1/2 in Hose Barb	1-1/2 in Tri-Clamp	5 in L x 1.545 in W
DXN 14MPHRL200	2 in Hose Barb	2 in Tri-Clamp	5 in L
DXN 14MPHRL250	2-1/2 in Hose Barb	2-1/2 in Tri-Clamp	5-1/2 in L
DXN 14MPHRL300	3 in Hose Barb	3 in Tri-Clamp	5-1/2 in L
DXN 14MPHRL400	4 in Hose Barb	4 in Tri-Clamp	5-1/2 in L

For Use With: Band Clamps



Dixon 14MPHR 304 Stainless Steel Rubber Hose Adapter

Part Number	Connection 1	Connection 2
DXN 14MPHR-G100	1 in Clamp	1 in Hose
DXN 14MPHR-G150	1-1/2 in Clamp	1-1/2 in Hose
DXN 14MPHR-G200	2 in Clamp	2 in Hose
DXN 14MPHR-G250	2-1/2 in Clamp	2-1/2 in Hose
DXN 14MPHR-G300	3 in Clamp	3 in Hose
DXN 14MPHR-G400	4 in Clamp	4 in Hose
DXN 14MPHR-G10075	1 in Clamp	3/4 in Hose
DXN 14MPHR-G15050	1-1/2 in Clamp	1/2 in Hose
DXN 14MPHR-G150625	1-1/2 in Clamp	5/8 in Hose
DXN 14MPHR-G15075	1-1/2 in Clamp	3/4 in Hose
DXN 14MPHR-G150100	1-1/2 in Clamp	1 in Hose
DXN 14MPHR-G200150	2 in Clamp	1-1/2 in Hose



Reducers



Dixon B3114MP 304 Stainless Steel Concentric Reducer

Part Number	Connection 1	Connection 2	Dimension
DXN B3114MP-G150100	1-1/2 in Clamp	1 in Clamp	3 in L
DXN B3114MP-G200100	2 in Clamp	1 in Clamp	5 in L
DXN B3114MP-G200150	2 in Clamp	1-1/2 in Clamp	3 in L
DXN B3114MP-G250150	2-1/2 in Clamp	1-1/2 in Clamp	5 in L
DXN B3114MP-G250200	2-1/2 in Clamp	2 in Clamp	3 in L
DXN B3114MP-G300100	3 in Clamp	1 in Clamp	9 in L
DXN B3114MP-G300150	3 in Clamp	1-1/2 in Clamp	7 in L
DXN B3114MP-G300200	3 in Clamp	2 in Clamp	5 in L
DXN B3114MP-G300250	3 in Clamp	2-1/2 in Clamp	3 in L
DXN B3114MP-G400150	4 in Clamp	1-1/2 in	11-1/8 in L
DXN B3114MP-G400200	4 in Clamp	2 in Clamp	9-1/8 in L
DXN B3114MP-G400250	4 in Clamp	2-1/2 in Clamp	7-1/8 in L
DXN B3114MP-G400300	4 in Clamp	3 in Clamp	5-1/8 in L



Dixon B3214MP 304 Stainless Steel Eccentric Reducer

Part Number	Connection 1	Connection 2
DXN B3214MP-G150100	1-1/2 in Clamp	1 in Clamp
DXN B3214MP-G200100	2 in Clamp	1 in Clamp
DXN B3214MP-G200150	2 in Clamp	1-1/2 in Clamp
DXN B3214MP-G250150	2-1/2 in Clamp	1-1/2 in Clamp
DXN B3214MP-G250200	2-1/2 in Clamp	2 in Clamp
DXN B3214MP-G300100	3 in Clamp	1 in Clamp
DXN B3214MP-G300150	3 in Clamp	1-1/2 in Clamp
DXN B3214MP-G300200	3 in Clamp	2 in Clamp
DXN B3214MP-G300250	3 in Clamp	2-1/2 in Clamp
DXN B3214MP-G400150	4 in Clamp	1-1/2 in Clamp
DXN B3214MP-G400200	4 in Clamp	2 in Clamp
DXN B3214MP-G400250	4 in Clamp	2-1/2 in
DXN B3214MP-G400300	4 in Clamp	3 in Clamp



Clamps

Dixon 304SS High Pressure Bolted Clamp

TIPCO Part Number	Description
DXN 13MHP75	1/2"-3/4" High Pressure Bolted Clamp 304SS
DXN 13MHP250	2.5" High Pressure Bolted Clamp 304SS
DXN 13MHP400	4" High Pressure Bolted Clamp 304SS



Dixon 13MHHM 304 Stainless Steel Single-Pin Heavy-Duty Clamp

Part Number	Nominal Size	Locking Style
DXN 13MHHM100-150	1 - 1-1/2 in	Wing Nut
DXN 13MHHM200	2 in	Wing Nut
DXN 13MHHM250	2-1/2 in	Wing Nut
DXN 13MHHM300	3 in	Wing Nut
DXN 13MHHM400	4 in	Wing Nut



Includes: Cross Hole Wing Nut

Thickness: 3/4 in

Torque Rating: 25 in-lb

Dixon 13MHHM-Q 304 Stainless Steel Single-Pin Squeeze Clamp

Part Number	Nominal Size	Width
DXN 13MHHM-SC100150	1 - 1-1/2 in	4.8 in
DXN 13MHHM-Q200	2 in	5.4 in
DXN 13MHHM-Q250	2-1/2 in	6 in
DXN 13MHHM-Q300	3 in	6.4 in
DXN 13MHHM-Q400	4 in	7.6 in



Thickness: 3/4 in

Torque Rating: 25 in-lb

Locking Style: Wing Nut


Dixon 304 Stainless Steel Sanitary Bolt Clamp

TIPCO Part Number	Clamp Diameter
DXN 13MHP100-150	1 in - 1-1/2 in
DXN 13MHP200	2 in
DXN 13MHP300	3 in
DXN 13MHP600	6 in

Thickness: 1 in

Torque Rating: 20 in-lb

Locking Style: Bolt



Clever Clamp



Dixon 13SCC-SERIES 304 Stainless Steel Clever Clamp™

- Consistent, controlled compression of gasket with every use
- Adjustable for both rubber and PTFE style gaskets
- ASME BPE capable
- Fast installation, no torquing tools required
- Lockout ready design
- Self-locking lever and color-coding options available

TIPCO Part Number	Description
DXN 13SCC-100150	1-1/2" 13SCC-Series Clever Clamp™ 304SS
DXN 13SCC-200	2" 13SCC-Series Clever Clamp™ 304SS
DXN 13SCC-300	3" 13SCC-Series Clever Clamp™ 304SS



Clamp Gaskets

Dixon EPDM Clamp Flanged Gasket

Part Number	Nominal Size	Inside Diameter	Outside Diameter
DXN 40MPF-E100	1 in	7/8 in	1-63/64 in
DXN 40MPF-E150	1-1/2 in	1.37 in	1-63/64 in
DXN 40MPF-E200	2 in	1-7/8 in	2-33/64 in
DXN 40MPF-E250	2-1/2 in	2.37 in	3.047 in
DXN 40MPF-E300	3 in	2-7/8 in	3.579 in
DXN 40MPF-E400	4 in	3.83 in	4.68 in
DXN 40MPF-E600	6 in	5.782 in	6-9/16 in



Dixon Buna-N Black Clamp Flanged Gasket

Part Number	Nominal Size	Inside Diameter	Outside Diameter
DXN 40MPF-U100	1 in	0.87 in	1.984 in
DXN 40MPF-U150	1-1/2 in	1.37 in	1.984 in
DXN 40MPF-U200	2 in	1.87 in	2.516 in
DXN 40MPF-U250	2-1/2 in	2.37 in	3.047 in
DXN 40MPF-U300	3 in	2.87 in	3.579 in
DXN 40MPF-U400	4 in	3.834 in	4.682 in
DXN 40MPF-U600	6 in	5.782 in	6.562 in



Clamp Gaskets


Dixon Black Buna-N Red Dot Color Code Standard Clamp Gasket

Part Number	Nominal Size	Inside Diameter	Outside Diameter	Thickness
DXN 40MP-U100	1 in	0.9 in	1.98 in	0.21 in
DXN 40MP-U150	1-1/2 in	1-25/64 in	1-31/32 in	0.21 in
DXN 40MP-U200	2 in	1-57/64 in	2-1/2 in	0.21 in
DXN 40MP-U250	2-1/2 in	2-3/8 in	3-1/32 in	0.21 in
DXN 40MP-U300	3 in	2-55/64 in	3-37/64 in	0.21 in
DXN 40MP-U400	4 in	3.87 in	4.68 in	0.21 in
DXN 40MP-U600	6 in	5-3/4 in	6-1/2 in	0.21 in



Dixon EPDM Standard Clamp Gasket

Part Number	Nominal Size	Inside Diameter	Outside Diameter	Thickness
DXN 40MP-E100	1 in	0.9 in	1.98 in	0.21 in
DXN 40MP-E150	1-1/2 in	1.4 in	1.98 in	0.21 in
DXN 40MP-E200	2 in	1.9 in	2.52 in	0.21 in
DXN 40MP-E250	2-1/2 in	2.4 in	3.05 in	0.21 in
DXN 40MP-E300	3 in	2.9 in	3.58 in	0.21 in
DXN 40MP-E400	4 in	3.87 in	4.68 in	0.21 in
DXN 40MP-E600	6 in	5.82 in	6.51 in	0.21 in



TIPCO Sealing PTFE Type I Sanitary Gasket

Color: White

Color Code: no dot

Not recommended for use with bolted clamps

Part Number	Nominal Size	Inside Diameter	Outside Diameter
40MP-G100	1 in	0.875 in	1.98 in
40MP-G150	1-1/2 in	1.404 in	1.98 in
40MP-G200	2 in	1.9 in	2.515 in
40MP-G250	2-1/2 in	2.37 in	3.047 in
40MP-G300	3 in	2.9 in	3.579 in
40MP-G400	4 in	3.834 in	4.682 in
40MP-G600	6 in	5.782 in	6.562 in

Swivels

Dixon Swivels

TIPCO Part Number	Description
DXN SJSS150ECC120	1.5" SJSS 316L STYLE 20 SWIVEL CxC, EPDM
DXN SJSS150SCC120	1.5" SJSS 316L STYLE 20 SWIVEL CxC, SILI
DXN SJSS150ECC130	1.5" SJSS 316L STYLE 30 SWIVEL CxC, EPDM
DXN SJSS150SCC130	1.5" SJSS 316L STYLE 30 SWIVEL CxC, SILI



Sample Valves

Dixon Sample Valves

TIPCO Part Number	Description
DXN BSVWBP-G100	1" Butt weld Wine Sample Valve, PTFE
DXN BSVWBS-G100	1" Butt weld Wine Sample Valve, SILI
DXN BSVWCP-G100	1" Clamp Wine Sample Valve, PTFE
DXN BSVWCS-G100	1" Clamp Wine Sample Valve, SILI
DXN BSVWNP-G375	.375" NPT WINE SAMPLE VALVE, PTFE
DXN BSVWNS-G375	.375" NPT WINE SAMPLE VALVE, SILI



Sanitary Check Valves

Dixon B45BY Y 316L Stainless Steel EPDM/CF8M Stainless Steel Seat Y-Ball Check Valve

Part Number	Nominal Size	Width
DXN B45BY-R150	1-1/2 in	7-1/2 in
DXN B45BY-R200	2 in	8-1/2 in
DXN B45BY-R250	2-1/2 in	10 in
DXN B45BY-R300	3 in	11-1/2 in

Temperature Rating: 15 - 200 deg F
Trim Material: EPDM/CF8M Stainless Steel
Connection Type: Clamp



Sanitary Check Valves

Dixon HSC 316L Stainless Steel Spring Check Valve

Part Number	Nominal Size	Length	Height	Width
DXN HSCE075	3/4 in	2.7 in	3.6 in	3.9 in
DXN HSCE100	1 in	3.3 in	3.6 in	3.9 in
DXN B45MP-R150	1-1/2 in	3.4 in	3.8 in	4.4 in
DXN HSCE200	2 in	3.4 in	4.2 in	5.1 in
DXN B45MP-R300	1 in	3.4 in	4.9 in	6.6 in
DXN HSCE400	4 in	4.1 in	5.4 in	7.9 in

Temperature Rating: 15 - 200 deg F

Pressure Rating: 145 psi

Connection Type: Clamp



Butterfly Valves

Dixon® B5116-Series Butterfly Valve with Trigger Handle Clamp End

- Ideal for low pressure, low temperature, and low viscosity
- 100% inspected, 100% tested

Part Number	Description
DXN B5116S150CC-C	1.5" B5116, SILI, CxC, 304
DXN B5116S200CC-C	2" B5116, SILI, CxC, 304



Dixon B5107-Series Butterfly Valve with Pull Handle Clamp End

- Low resistance to flow, bi-directions flow, gentle to media
- Suitable for low and medium viscosity fluids
- Can be serviced in the field
- Self-draining
- 100% inspected

Part Number	Description
DXN B5107E150CC-C	1.5" B5107, EPDM, CxC 316 w/ Pull Handle
DXN B5107E200CC-C	2" B5107, EPDM, CxC 316 w/ Pull Handle
DXN B5107E300CC-C	3" B5107, EPDM, CxC 316 w/ Pull Handle



Sight Glasses

Dixon Borosilicate Glass Compact Sight Glass

Part Number	Connection	Length
DXN B54BMPS-R100	1 in Clamp	3-3/8 in
DXN B54BMPS-R150	1-1/2 in Clamp	3.64 in
DXN B54BMPS-R200	2 in Clamp	3.83 in
DXN B54BMPS-R300	3 in Clamp	4.13 in
DXN B54BMPS-R400	4 in Clamp	4.34 in



Easier to clean than bolted styles
Less cost to repair than bolted styles
Clamp connections standard

Temperature Rating: 200 degrees F
Seal Material: Buna-N
Pressure Rating: 100 psi;

Dixon Polycarbonate Compact Sight Glass

Part Number	Connection	Length
DXN B54BMPLX-R100	1 in Clamp	3-3/8 in
DXN B54BMPLX-R150	1-1/2 in Clamp	3.64 in
DXN B54BMPLX-R200	2 in Clamp	3.83 in
DXN B54BMPLX-R300	3 in Clamp	4.13 in
DXN B54BMPLX-R400	4 in Clamp	4.34 in

Dixon Borosilicate Glass In-Line Clamp x Clamp Sight Glass

Part Number	Tube OD	Pressure Rating
DXN B54BMP-R100	1 in	145 psi
DXN B54BMP-R150	1-1/2 in	145 psi
DXN B54BMP-R200	2 in	145 psi
DXN B54BMP-R250	2-1/2 in	120 psi
DXN B54BMP-R300	3 in	120 psi
DXN B54BMP-R400	4 in	95 psi

Temperature Rating: 200 degrees F
Material: 316 Stainless Steel
Seal Material: Buna-N



Dixon Polycarbonate In-Line Clamp x Clamp Sight Glass

Part Number	Tube OD	Pressure Rating
DXN B54BMP-R100LX	1 in	145 psi
DXN B54BMP-R150LX	1-1/2 in	145 psi
DXN B54BMP-R200LX	2 in	145 psi
DXN B54BMP-R250LX	2-1/2 in	120 psi
DXN B54BMP-R300LX	3 in	120 psi
DXN B54BMP-R400LX	4 in	95 psi

Temperature Rating: 200 degrees F
Material: 316 Stainless Steel
Seal Material: Buna-N

Various end configurations are available:
 clamp, weld, bevel seat, John Perry, I-Line
 and Q-Line

Construction: Sight glass: Polycarbonate,
 Black Nitrile Rubber gaskets
 32Ra sanitary finish, ID and OD

Pressure Gauges

NOSHOK® 25-100-60-psi/bar Dual Scale Dry Pressure Gauge, 2-1/2 in Dial, 0 - 60 psi

Part Number

NOS 25.100/60PSI ABS/BM

Applications: For applications including pumps and compressors, refrigeration controls, utilities and water management



NOSHOK® 25-300-60-psi Natural Single Scale Liquid Filled Pressure Gauge, 2-1/2 in Dial, 0 - 60 psi

Part Number

NOS 25.300/60PSI BR/BM

High-quality, heavy-duty liquid filled gauge
 Vacuum and compound ranges through 0 - 15000 psi
 Copper alloy or 316 stainless steel and brass wetted parts
 Polished brass cover ring
 Lens - with O-ring seal
 Aluminum dial, white background with black scale, UV-resistant



Back Mount Sanitary Gauges, 3.5 in Face, 304 Stainless Steel, 0-250 def F

Part Number	Pressure Rating	Fitting Specification
DXN 3S-B-15U-GFBKSS	0-30 psi	1.5 in clamp
DXN 3S-B-2U-GFBKSS	0-30 psi	2 in clamp
DXN 3S-C-15U-GFBKSS	0-60 psi	1.5 in clamp
DXN 3S-C-2U-GFBKSS	0-60 psi	2 in clamp
DXN 3S-D-15U-GFBKSS	0-100 psi	1.5 in clamp
DXN 3S-D-2U-GFBKSS	0-100 psi	2 in clamp
DXN 3S-E-15U-GFBKSS	0-160 psi	1.5 in clamp
DXN 3S-E-2U-GFBKSS	0-160 psi	2 in clamp
DXN 3S-F-15U-GFBKSS	0-200 psi	1.5 in clamp
DXN 3S-F-2U-GFBKSS	0-200 psi	2 in clamp
DXN 3S-G-15U-GFBKSS	0-300 psi	1.5 in clamp
DXN 3S-G-2U-GFBKSS	0-300 psi	2 in clamp



Bottom Mount Sanitary Gauges, 3.5 in Face, 304 Stainless Steel, 0-250 def F

Part Number	Pressure Rating	Fitting Specification
DXN 3S-B-2U-GFBTSS	0-30 psi	2 in clamp
DXN 3S-C-15U-GFBTSS	0-60 psi	1.5 in clamp
DXN 3S-C-2U-GFBTSS	0-60 psi	2 in clamp
DXN 3S-D-15U-GFBTSS	0-100 psi	1.5 in clamp
DXN 3S-D-2U-GFBTSS	0-100 psi	2 in clamp
DXN 3S-E-15U-GFBTSS	0-160 psi	1.5 in clamp
DXN 3S-E-2U-GFBTSS	0-160 psi	2 in clamp
DXN 3S-F-15U-GFBTSS	0-200 psi	1.5 in clamp
DXN 3S-F-2U-GFBTSS	0-200 psi	2 in clamp
DXN 3S-G-15U-GFBTSS	0-300 psi	1.5 in clamp
DXN 3S-G-2U-GFBTSS	0-300 psi	2 in clamp






People. Partnerships. Innovation.

TIPCO Technologies is your complete fluid solution supplier for all of your industrial, hydraulic, and high-purity applications. As a complete fluid conveyance solution supplier and sealing solutions focused on hose assemblies and custom gaskets, TIPCO is here to supply quality products that meet your needs.

Since 1888, our history of customer satisfaction and speed to market provides you the experience and expertise needed to solve your most challenging hose problems.



Arizona

Deer Valley, AZ (Alternative)
Gilbert, AZ (Alternative)
Phoenix, AZ (Alternative) COMING SOON
Tucson, AZ (Alternative)

California

San Diego, CA (Charter) ISO 9001-2015
Orange, CA (Charter)
Pomona, CA (Charter)

Colorado

Denver, CO (TIPCO)

Delaware

Wilmington, DE (TIPCO)

Georgia

Gainesville, GA (Atlanta Rubber)
Marietta, GA (Atlanta Rubber)

Illinois

Elmhurst, IL (Alliance)

Idaho

Boise, ID (Alternative)

Maryland

Glen Burnie, MD (TIPCO)
Frederick, MD (TIPCO)
Owings Mills, MD (TIPCO)
Pocomoke City, MD (TIPCO)

Nevada

Las Vegas, Nevada (Alternative)

New Jersey

Kenilworth, NJ (Flexline) ISO 9001-2015
Vineland, NJ (TIPCO)

New York

Rochester, NY (Potter)

North Carolina

Stallings, NC (Atlanta Rubber)

Oregon

Albany, OR (A-1 Coupling)
Eugene, OR (A-1 Coupling)
Eugene, OR (Pacific Rubber)
Tualatin, OR (A-1 Coupling)

Pennsylvania

Hanover, PA (TIPCO)

Texas

Corpus Christi, TX (Hose of S. Tx)
Houston, TX (Wilco)
Houston, TX (DW) ISO 9001-2015

Virginia

Chantilly, VA (TIPCO)
Chester, VA (TIPCO)
Lynchburg, VA (TIPCO)
Fredericksburg, VA (TIPCO)
Manassas, VA (TIPCO)
Suffolk, VA (TIPCO)

TIPCO
TECHNOLOGIES | *Focused
Flexible
Solutions*

www.tipcotech.com
sales@tipcotech.com

NAHAD
HOSE SAFETY INSTITUTE
DESIGNATED ✓

Now Available

TIPCO  **e-Store**

Shop online at: www.shop.tipcotech.com