

❄️ 24POL0505DABHEA-120

1.5"x10' 1.5-FNPT x 1-FNPT, CO² +HSEND ASSY

GENUINE Versilon™ POLAR/CO² LIQUID/VAPOR 450 PSIG

w/ BRASS HOSE END ASSY (NUT, ADAPTER, PLUG) E/E

24	POL	05		05	D	AB	HEA	- 120		
Hose I.D. Size (1/16")	Hose Style	Fitting Style End #1	Fitting Type End #1	Fitting Style End #2	Fitting Type End #2	End Materials	Adapter Style	Length (Inches)	Safety Accessory	Additional Cleaning
16 (1")	Saint Gobain	03	D	03	D	AB	FE	12 IN = 1 FT	WC	-02
24 (1-1/2")	Genuine Versilon	05	U	05	U	AS	FEA		WCS	
32 (2")	Polar Hose	77	US (1" Hose) G (2" Hose) UG (1.5" Hose)	77	US (1" Hose) G (2" Hose) UG (1.5" Hose)		HEA GHEA HLA TPA			

Fitting Style

03 = Male NPT
05 = Female NPT
77 = CO2 Swivel

Fitting Modifier

Blank = No Mod
U = Size Step Up
D = Size Step Down
77 Only Mods
US = CGA320 Nut w/ Extra Large Hex (1" **US** hex has the same dim. as 1.5" hex so same wrench can be used.)
G = Grooved for O-Ring
UG = Step Up w/ O-Ring

End Materials

AB = A for aluminum collar, B for Brass Fittings
AS = A for aluminum collar, S for SS Fittings

Adapter Style

FE = Fixed End – (MCGA x MNPT) (05 or 77)
FEA = Fixed End Assy – (CAP + MCGA x MNPT) (05)
HEA = Hose End Assy – (PLUG + FCGA X MNPT) (05)
GHEA = Grooved Hose End Assy w/ O-ring – (PLUG + FGCGA X MNPT) (05)
TPA = Tail Piece Assy – (CGA Plug) (77)
HLA = Hook Loop Assy – (MIK CLAMP + Welded U-Bolt)(any)

Safety Accessory

WC = Safety Whip Sock w/o Shackle
WCS = Safety Whip Sock w/ Shackle

I.E. ❄️ 24POL77D77UABHEA-240WC-02
❄️ 16POL77U77USAB-240

Additional Cleaning

-02 = Cleaned to non-respiratory oxygen use specs