



TIPCO
TECHNOLOGIES | Focused
Flexible
Solutions

The **ONLY U.S. Master Distributor and Certified Assembler of CO₂ Polar[®] Hose Assemblies**

Versilon[®] Polar Hose

CARBON DIOXIDE TRANSFER HOSE


Versilon[®] Polar hose is engineered specifically for the safe and efficient bulk transfer of carbon dioxide (CO₂). Unlike traditional rubber hydraulic hoses, which may degrade upon exposure to CO₂ and cold temperatures, Versilon[®] Polar Hose utilizes a specially formulated EPDM elastomer that resists deterioration and remains flexible in low-temperature environments.

Its stainless steel braid reinforcement enhances strength and durability, while the perforated EPDM cover helps prevent pressure buildup. Versilon[®] Polar hose is lightweight and easy to handle, making it a practical choice for demanding CO₂ applications.

Unlike corrugated metal hoses that can trap solid CO₂ and cause plugging during transfer, Versilon[®] Polar hose features a smooth inner surface, ensuring reliable flow and easier handling in cold conditions.

Typical Applications

- Beverage carbonation
- Food-grade CO₂ transport
- Refrigeration
- Bulk transfer
- Fill stations



Features and Benefits

- Designed specifically for CO₂ bulk transfer
- Remains flexible at low temperatures
- Special low-temp EPDM liner
- Perforated cover protects hose and prevents pressure buildup

Regulatory Compliance

- CGA G-6.6 – Standard for Carbon Dioxide Bulk Transfer Hose
- FDA 21 CFR 177.2600 – (e) repeated use with aqueous food temperatures

TIPCO  e-Store

SHOP.TIPCOTECH.COM

CRYOSALES@TIPCOTECH.COM


SAINT-GOBAIN

Versilon® Polar Hose



Versilon® Polar Hose Specifications

Part Number	Inside Diameter		Outside Diameter		Maximum Working Pressure		Minimum Bend Radius		Weight	
	(in)	(mm)	(in)	(mm)	73°F (psi)*	(MPa)*	(in)	(mm)	(lb/ft)	(kg/m)
7716POLAR	1.000	25.4	1.500	38.1	450	31.03	12.0	304.8	0.64	0.95
7724POLAR	1.500	38.1	2.000	50.8	450	31.03	20.0	508.0	0.93	1.38
7732POLAR	2.000	50.8	2.625	66.8	450	31.03	25.0	635.0	1.54	2.29

*Working pressures are calculated at a 1:4 ratio relative to burst pressure using ASTM D1599.

Construction


Inner Tube:	Black EPDM
Cover:	Perforated Black EPDM
Reinforcement:	SS Braid (1 / 1 / 2)
Color:	Black with Blue Layline
Temperature Rating:	-65°F to +212°F
Maximum Length:	100 ft coil

Fitting Options

- Crimp style fittings
 - Fittings meant for CGA applications
 - Brass, Stainless steel, aluminum



Every Polar Hose expires after four years in service. Save money by keeping the fittings and changing out the hose with our Hose End Adapters.



Grooved Headpiece with O-ring, crimped to the hose: Only avail. in 2in, this head piece is ergonomic (lighter) than a Hose End Assembly and the o-ring adds sustainability and up-time since you can replace the O-ring in the field to extend the life of the hose and assembly.



Every assembly is hydrostatically tested, flushed out, wiped with three UltraClean projectiles, tagged with serial number and then capped and/or plugged to prevent contamination during shipment/storage.

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



SHOP.TIPCOTECH.COM
CRYOSALES@TIPCOTECH.COM



NOTE: The data and details given in this document are correct and up to date. This document is intended to provide information about the product and possible applications. This document is not the product specification and does not provide specific features, nor does it guarantee product performance in specific applications. Saint-Gobain cannot anticipate or control the conditions of the field and for this reason strongly recommends that practical tests are conducted to ensure that the product meets the requirements of a specific application.

Versilon® is a registered trademark of Saint-Gobain Performance Plastics Corporation.