

Catalog # 75C

Item number: Description:

3 Ply 225 3/16 x Bare MOR

International Designation:

N/A

Construction:

Compound Top Cover Black MOR
Color Black
Top Cover Thickness (in) (4.76 mm) 3/16 in

52182

Top Cover Description Smooth

Compound Bottom Cover N/A

Bottom Cover Thickness (in) (0.00 mm) 0.00 in
Bottom Cover Description Bare

Number of Plies 3

Overall Gauge (in) (7.94 mm) 5/16 in

Unit Weight- lb/PIW 0.1750 lbs/PIW

Carcass Type Poly/Nylon
Compound Black MOR
Temperature Range (°F)- High 225 °F

Temperature Range (°F)- Low

Belt Strength:

Tension Rating (PIW) 225 PIW

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% 16.00 in

Tension

Min. Pulley Dia. - Head @ 60 - 79% 14.00 in

Tension

Min. Pulley Dia. - Head @ 59% Tension 10.00 in

or Below

Minimum Pulley Diameter- Tail 10.00 in

Splice Instructions:

Splice Step Size 8.00 in Splice Process Step Hot

Other:

Static Conducting No
Cross Rigid No
High Heat No
Impression Top No
Oil Resistant Yes
Fire Resistant No
FDA Approved No

Suggested Fasteners:

Flexco Plate/Rivet R2
Flexco Hinged #375
Alligator Staple #187
Clipper Lace N/A
Alligator Lace N/A

Special Characteristics:

Stocked at 118in wide, this belt supports high-throughput conveyor systems in Material Recovery Facilities (MRFs). The MOR top cover is designed to handle materials with light to moderate oil content—common in recycling environments dealing with mixed waste streams like plastics, paper, metals, and food packaging.

-25 °F

*****All Values are nominal and subject to change without notice.*****

Beltservice Canada St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA Beltservice de Mexico 800-423-4469 800-777-1314 800-289-2358 800-234-2358 +52 55 53620434 800-727-2358 800-849-2358 800-727-2358 877-210-7423 704-949-2100 215-295-1900 360-567-4280 905-565-9217 314-344-8500 208-342-4681 314-344-8555 916-419-7191 +44 2980 3266



OIL RESISTANT MOR

3 PLY 225 3/16 X BARE MOR



52182

Part Number





