

LIGHTWEIGHT THERMOPLASTICS SPECIFICATIONS

Catalog # **118HAL**

Item number: 50244

Description:

2 Ply Poly CR80 Green RMV LG x FS


International Designation:

E14/2 U0/RMV11 LR Green AS

Construction:

Rubber Modified Vinvl Compound Top Cover (RMV) Top Cover Thickness (in) (1.10 mm) 0.0433 in **Top Cover Description** Longitudinally Grooved Top Cover Shore 35A PU Impregnated Compound Bottom Cover Bottom Cover Thickness (in) (0.00 mm) 0.0000 in **Bottom Cover Description** PU Impregnated **Bottom Cover Shore** N/A Number of Plies 2 Anti Static Yes Overall Gauge (in) (2.50 mm) 0.0984 in 0.0574 lbs/PIW Unit Weight- lb/PIW Material Between Plies N/A Maximum Width (in) 78 in Temperature Range (°F)- High 150 °F 0 °F

Pulley Diameter, Minimum



A) Normal Flex

(50.80 mm) 2.0000 in

B) Back Flex

(66.04 mm) 2.6000 in

Belt Strength:

Pull for 1% Elongation

(14 N/mm) 80 lbs/sq in

Splice Instructions:

Foil No Splice Process Finger Press Temperature (°F) 350 °F Press Pressure (psi) 18 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid

Yes

No

No

No

No

Impression Top Oil Resistant Fire Resistant FDA Approved

Special Characteristics:

208-342-4681

Temperature Range (°F)- Low

#118 HAL features a high friction longitudinally ribbed cover surface designed to handle packages on incline conveyors. The cover compound will also maintain its grip in wet conditions.

*****All Values are nominal and subject to change without notice.****

St. Louis, MO Boise, ID 800-727-2358 800-423-4469

Charlotte, NC 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358

314-344-8555

Philadelphia, PA 800-777-1314

215-295-1900

Sacramento, CA 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280

Beltservice Canada 877-210-7423

905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



314-344-8500

PVC/NBR PROFILE/STICKY TOP COVERS

2 PLY POLY CR80 GREEN RMV LG X FS

INTERNATIONAL DESIGNATION: E14/2 UO/RMV11 LR GREEN AS



50244

Part Number

