



FINAL REPORT

GTI Service Request No.: 525
GTI Project No.: 22480.1.54

Evaluation of Boretrace™

Purchase Order No.:

Signed GTI Testing and Analysis Proposal/Agreement

Report Issued: June 18, 2021

Revision No.: 1

Revision Date: June 25, 2021

Prepared For:

Josh Parman
Chief Operating Officer
Damage Prevention Solutions, LLC
1104 Arvon Rd, Ste A
Arvon, VA 23004
434-202-8710 | 434-906-5121
josh@damageprevention.com

GTI Proposal / Project Manager:

Tony Kosari, M.Sc.
Industrial Testing Manager
847-768-0998
tkosari@gti.energy

GTI Technical Contact:

Jarrold Bullen
Engineer
847-768-0727
jbullen@gti.energy

Project Team: Jarrod Bullen, Steven Blitzstein, Simeon Kateliev

1700 S. Mount Prospect Rd.
Des Plaines, Illinois 60018
www.gti.energy

Legal Notice

This information was prepared by Gas Technology Institute ("GTI") for Damage Prevention Solutions, LLC.

Neither GTI, the members of GTI, the Sponsor(s), nor any person acting on behalf of any of them:

- a. Makes any warranty or representation, express or implied with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately-owned rights. Inasmuch as this project is experimental in nature, the technical information, results, or conclusions cannot be predicted. Conclusions and analysis of results by GTI represent GTI's opinion based on inferences from measurements and empirical relationships, which inferences and assumptions are not infallible, and with respect to which competent specialists may differ.*
- b. Assumes any liability with respect to the use of, or for any and all damages resulting from the use of, any information, apparatus, method, or process disclosed in this report; any other use of, or reliance on, this report by any third party is at the third party's sole risk.*
- c. The results within this report relate only to the items tested as received.*
- d. Statements of conformity resulting from tests performed by GTI will not take into account the reported or understood measurement uncertainty.*
- e. The methods GTI uses are based on the current versions of generally accepted industry standards unless otherwise specified.*
- f. The acceptance criteria for tests and examinations performed by GTI are based on the current versions of generally accepted industry standards unless otherwise specified.*
- g. The customer must communicate to GTI in writing if they do not agree or have alternate requirements or questions. Otherwise, the above-listed GTI statements of conformity shall apply. Requests for alternative requirements will necessitate additional discussion.*

Table of Contents

Legal Notice	2
Table of Contents.....	3
Table of Figures	3
List of Tables	3
List of Acronyms	4
Background.....	5
Field Installations	5
HDD Pull	6
Marker System Evaluation	11
Boretrace™ Evaluation.....	11

Table of Figures

Figure 1. Approximate layout of installation and soil types at GTI Pipe Farm	6
Figure 2. Boretrace™ Attachment Procedure.....	7
Figure 3. Installation attachment of tracer wire products	8
Figure 4. HDD Installation with Boretrace™ tracer wire.....	9
Figure 5. Overhead view of Boretrace™ tracer wire installation	9
Figure 6. Field observed abrasion and material removal	10
Figure 7. Abrasion Point (1)	11
Figure 8. Abrasion Point (2)	12
Figure 9. Abrasion Point (3) with exposed tracer wire	12

List of Tables

Table 1. Sample Submitted by DPS	5
--	---


List of Acronyms

Acronym	Full Form
ASTM	American Society for Testing and Materials
AWG	American Wire Gauge
DPS	Damage Prevention Solutions, LLC
EMS	Electronic Marker System
HDD	Horizontal Directional Drilling
HDPE	High Density polyethylene
SDR	Standard Dimension Ratio

Background

Damage Prevention Solutions, LLC, henceforth referred to as DPS, submitted to GTI the electronic marker system listed in Table 1 for evaluation.

Table 1. Sample Submitted by DPS

Product	Description
Boretrace™	

Additional materials included 500-ft of 2" SDR 11 high-density polyethylene (HDPE) pipe and 12 AWG tracer wire, procured by GTI, and EMS rope provided by 3M. The pipe print line is provided below.

2" IPS SDR11 DURA-LINE POLYPIPE GDB50 GAS PE4710 PE100 CEE ASTM D2513 D06Y19NR5GD 07NOV17

Field Installations

The Boretrace™ marker system was evaluated by performing a Horizontal Directional Drilling (HDD) field installation in GTI's pipe farm, as detailed below. During the one-day installation photographs and video recordings were taken, including aerial shots taken by a drone. The layout of the field and soil types is shown below in Figure 1.




Figure 1. Approximate layout of installation and soil types at GTI Pipe Farm

HDD Pull

HDPE pipe pulled (dry pull) in with Boretrace™.

- Pulled in with 12 AWG tracer wire.
- 4.5" drill head used during pull back.
- 500' of 2" HDPE pipe pulled in through approx. 300' bore.

Boretrace™ was attached to a horizontal directional drill with 20,000 lb. of thrust and pull back capability per the attachment procedure shown in Figure 2. The HDD installation was carried out as a "dry pull", that is, no use of drilling mud, however some water was used to aid the installation. The pipe was pulled through clay soil, gravel and sand at ambient temperature and an estimated depth of 36 – 45 inches. An exemplar photograph of this installation is shown in Figure 5.



DAMAGE PREVENTION SOLUTIONS



WWW.DAMAGEPREVENTION.COM
SALES@DAMAGEPREVENTION.COM
800.254.8718


BORETRACE™ INSTALLATION

**Pipes that are 2" or smaller can typically be pulled without a back reamer due to the typical 4" blade size. Use a back reamer that is 1.5X the pipe diameter on pipes that are larger than 2".*



1. KNOT IT

- Bundle Boretrace film around core material (~5') and tape to form a rope like construct.
- Use a **Figure 8 Loop Knot** or comparable high strength knot to tie the core material to the D-Ring.
- Form a bight out of the bundled Boretrace and cross the bight onto itself.
- Wrap the bight for one full wrap.
- Pull the end of the bight through the loop and pull hand tight.
- Place the knot into the D-Ring and secure.



2. CUT IT

- Use sidecutters to cut tracer wire through film just beyond the knot so no tension is applied to wire curing pull. Do not cut the Polyester core material. Cut as little of the film as possible.

3. TAPE IT

- Duct tape the Boretrace to the pipe.
- Continue to tape the Boretrace to the pipe approximately every 8 feet as it is pulled through.



INNOVATION DRIVEN DAMAGE PREVENTION

660 HUNTERS PLACE, STE 202, CHARLOTTESVILLE, VA 22911 • BILLING | PRODUCTION • 1104 ARVON ROAD, STE A, ARVONIA, VA 23001

Figure 2. Boretrace™ Attachment Procedure

Both the 12 AWG tracer wire and Boretrace™ tracer wire were attached to the bore head as shown in Figure 3 below. Some abrasions were observed after removal from the bore

hole (Figure 6). However, no visible disconnections or catastrophic damage to either the traditional tracer wire or Boretrace™ product was visible. Upon laboratory inspection by DPS, some abrasions were observed on the Boretrace™ product and a single opening in the PE film exposed the tracer wire jacket, but the bare wire was not exposed. Tracer wire continuity was maintained, as described in **Marker System Evaluation**.



Figure 3. Installation attachment of tracer wire products



Figure 4. HDD Installation with Boretrace™ tracer wire



Figure 5. Overhead view of Boretrace™ tracer wire installation



Figure 6. Field observed abrasion and material removal

Marker System Evaluation

On completion of the HDD installation, Boretrace™ samples were sent to DPS for evaluation.

Boretrace™ Evaluation

The Boretrace™ tracer wire samples were evaluated by means of visual inspection and resistance measurements. The following summarizes the findings:

- 1) Three (3) visible film abrasion points were observed (see Figure 7 and Figure 8)
 - One (1) abrasion point where the tracer wire jacket was exposed (Figure 9)
- 2) No visible damage to tracer wire or abrasion to wire jacket
 - Resistance checks across length of tracer wire confirmed no open line
 - Continuity was confirmed



Figure 7. Abrasion Point (1)



Figure 8. Abrasion Point (2)




Figure 9. Abrasion Point (3) with exposed tracer wire

This report shall not be reproduced except in full without the written approval of GTI.

Prepared by:

Jarrod Bullen
Engineer



Reviewed by:

Tony Kosari
Industrial testing Manager



Issued by:

Tony Kosari
Industrial testing Manager



Report Revision History:

Section Changed	Reason for Change	Date
Report header	Requested by client on 24JUN2021	25JUN2021

END OF REPORT