

# Center 384 Hydrogen Gas Leak Detector



## PRODUCT

The Center 384 is the ideal tool for detecting leak-points in piping systems. As the Center 384 detects hydrogen, the smallest of all the elements, It is particularly well-suited at finding the smallest of leaks, leaks that would take traditional soap bubble test a week to form a visible bubble.

## FEATURES

- The Center 384 Trace Gas Leak Detector can detect mixtures of 5% Hydrogen (H<sub>2</sub>) + 95% Nitrogen (N) with extreme sensitivity.
- The unit has both a newly developed heated semi-conductor sensor and a microprocessor control to provide reliable digital signal processing.
- Adjustable leak sensitivity level and multi-color LED visual indicators also offer the users the ease and convenience of operation.
- High/Low leak sensitivity selector
- Low battery indication
- Semiconductor gas sensor
- Detection of hydrogen
- 15" (39cm) flexible stainless probe
- Ambient hydrogen compensation

## SPECIFICATIONS

**Detectable Gases:** Non-critical mixture of 5% Hydrogen (H<sub>2</sub>) + 95% Nitrogen (N)

**Sensitivity:** 5ppm; 2g/year

**Alarm Method:** Buzzer alarm, LED bar Indicator

**Detection Tube Length:** 15 inch (390mm)

**Warm-Up Time:** 45 sec

**Battery:** 1.5V AA x 4

**Dimensions:** 173 x 66 x 56mm

**Weight:** 400g

## ⚠ CAUTION

- ▲ Do NOT exceed 5.7% hydrogen in the mixture with nitrogen.
- ▲ Replace batteries before each use.
- ▲ Replace sensor at least once per year.
- ▲ Store at room temperature in dry location.