ULTRA-CONTROLO

Variable-Area Flowmeters

# Twin High-Flow Flowmeter, 15 + 30 l/min

OXYGEN THERAPY & ASPIRATION

*Variable-Area Flowmeters*

# Twin High-Flow Flowmeter, 15 + 30 l/min

Double variable area flowmeter, available in two versions: composed of a 0-15 l/min flowmeter + a 0-30 l/min flowmeter, or with two 0-30 l/min flowmeters; it can be connected to the plant by means of AFNOR NF S 90-116, DIN 13260-1, UNI 9507, BS 5682, G 1/4" M RH threading.



## Features

- 0-15 + 0-30 l/min combination
- Optional rail clamp

## Standards

- NF S 90-116
- UNI 9507
- EN ISO 15002
- DIN 13260-2
- BS 5682
- EN ISO 15001
- SS 8752430

## Components

- Internal body in chemically nickel-plated aluminium
- External body made of MAKROLON
- AISI 316 stainless steel float
- 1 × inlet with standard probe or G 1/4" M RH thread
- 1 × G 1/4" M RH or M12x1.25 M RH and 9/16" threaded outlet
- Brass adjuster knob with NYLON 6.6 terminal unit
- EPDM or silicone O-Ring
- Internal graduated rotameter column and external MAKROLON 2458 polycarbonate column

| GAS | INLET CONNECTION | OUTLET CONNECTION | SCALE 1 + SCALE 2 | BAR |
|---|---|---|---|---|
| O2 | G 1/4" M RH | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| O2 | UNI 9507 | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| O2 | AFNOR NF S 90-116 | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| O2 | DIN 13260-2 | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| O2 | BS 5682 | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| O2 | SS 8752430 | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| O2 | AFNOR NF S 90-116 | M12x1.25 M | 0-15 l/min + 0-30 l/min | 4.5 |
| Air 400 | G 1/4" M | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| Air 400 | AFNOR NF S 90-116 | G 1/4" M | 0-15 l/min + 0-30 l/min | 4.5 |
| Air 400 | AFNOR NF S 90-116 | M12x1.25 M | 0-15 l/min + 0-30 l/min | 4.5 |

Tel. +351 21 915 4350

www.ultracontrolo.com