



sonus

Trava Ceiling

Sonus Wood

Sonus Organics

With Nature. For People. By Sonus.

A collection born from the belief that natural materials and modern performance belong together. Sonus Organics harnesses nature's own relentless design to create acoustics that are as healthy — for people and planet — as they are beautiful.

Specifications

Product Name	Trava Ceiling
Content	Premium wood veneer, MDF, and an acoustical core with 56% recycled materials
Thickness	1"
Sizes	2'x2' and 2'x4'
Tolerance	1/16"
Weight	1.5lbs per sq ft
Edges	Square and edgebanded
Sound Performance	ASTM C423-17 NRC: 0.80
Fire Performance	Class B
Variations	Slight and consistent variations in color and woodgrain should be expected when using this material. Slight imperfections are within normal manufacturing tolerances and not visible in standard installations.
Maintenance	Vacuum to remove any loose dirt or dust. A damp cloth or compressed air can also be used to dust the material in difficult or large installations. If stains are present, you may saturate a lint-free cloth with a soap and water solution or Murphy's Oil soap.
Warranty	5 years
Unit of Sale	Per sq. ft.

Price



Snap the QR Code or visit sonusna.com to see pricing.


Sonus is the only manufacturer to have published universal pricing because:

- 1) We got nothing to hide.
- 2) We are here for you.


Specifications

Environmental	• Designed as a lower-impact alternative to traditional millwork systems • Veneer production yields up to 3× more material per log, reducing resource consumption • Responsibly sourced wood supports sustainable forest management practices • Recon veneer options replicate rare or exotic species without depleting natural resources • Core materials contain high recycled glass content • Available with formaldehyde-free, low-emitting core options • Manufactured in the USA • Contributes to acoustic comfort and noise reduction • Materials tested for fire performance, mold resistance, and moisture durability
Certifications	• Designed as a lower-impact alternative to traditional millwork systems • Veneer production yields up to 3× more material per log, reducing resource consumption • Responsibly sourced wood supports sustainable forest management practices • Recon veneer options replicate rare or exotic species without depleting natural resources • Core materials contain high recycled glass content • Available with formaldehyde-free, low-emitting core options • Manufactured in the USA • Contributes to acoustic comfort and noise reduction • Materials tested for fire performance, mold resistance, and moisture durability
Product Care & Conditions	The owner is responsible for maintaining suitable climate conditions from product receipt through the entire service life of all Sonus products. Failures caused by excessively dry or humid conditions—including delamination, warping, twisting, and sagging—are not covered by warranty. This includes damage caused by directed air vents or heat sources, HVAC equipment failure, or intentional HVAC shutdowns during weekends or after hours. Environmental Conditions • Store and install products in a climate-controlled interior space, ideally in or near the final installation area. • HVAC systems must operate at normal capacity for at least 72 hours before materials are received and installed. • Maintain temperatures between 50°F and 86°F (10°C–30°C). • Maintain relative humidity between 25% and 55%. • Keep materials out of direct sunlight. Receiving, Storage & Acclimation • Upon delivery, uncrate, unwrap, and inventory all materials. • Allow products to acclimate for a minimum of 48 hours before installation. • Store materials on a clean, dry, flat surface to prevent dust and damage. • Storage exceeding 30 days may void the warranty. Natural Wood Characteristics Natural variations in veneer color, grain, and texture are inherent characteristics of real wood and are not covered by warranty. Natural color changes caused by exposure to sunlight, artificial light, or other UV sources after installation are also not covered by warranty.


Details



1 TRAVA w/ HOOK & SADDLE CLIP - BOTTOM DIMETRIC





2 TRAVA - LAY IN - BOTTOM DIMETRIC




3 TRAVA REGULAR ASSEMBLY - BOTTOM DIMETRIC


Hardware and Installation



Hardware and Installation




1 TRAVA TEGULAR - PLAN VIEW




3 ATTACHMENT DETAIL

Colors and Finishes

Naturals




Recons



Test Results

Absorption Coefficient vs. Freq (Hz)



Freq (Hz)	Absorption Coefficient
-----------	------------------------

160	0.50
-----	------

250	0.71
-----	------

500	0.93
-----	------

800	0.88
-----	------

1250	0.85
------	------

2000	0.81
------	------

3150	0.80
------	------

NRC	0.80
------------	-------------

The Noise Reduction Coefficient (NRC) is calculated as the arithmetic average of the absorption coefficients in the shaded bands only (250, 500, 1250 & 2000 Hz).

ASTM C 423-17: Type F Mounting as defined by ASTM E795 using two pieces of 0.5 in aluminum stock bar placed on floor to lift material with trim pieces to simulate a typical wall installation with mounts.