

SPX ENDURANCE ASHLESS NGEO

ASHLESS STATIONARY GAS ENGINE OIL

SPX Endurance Ashless NGEO is an ashless, dispersant detergent gas engine oil for use in naturally aspirated and turbocharged 2-stroke cycle natural gas engines. Engines operating in this type of service typically are found on crude oil and gas transmission pipelines, electrical power generators, gas compressors, irrigation water pumps, and well drilling rigs.

Advantages

- Ashless formulation helps minimize port deposits
 - Reduced piston deposits
 - Good resistance to oxidation and nitration
 - Protects against scuffing and wear
 - Protects against rust and corrosion
-

Applications

- 2-stroke cycle and some 4-stroke cycle natural gas engines where the manufacturer specifies an ashless gas engine oil

SPX Endurance Ashless NGEO is suitable for use in natural gas engines manufactured by the following OEMs:

- Ajax
 - Climax
 - Colt-Fairbanks Morse
 - Cooper-Bessemer
 - Dresser Clark
 - Dresser Rand (Category I, II)
 - Worthington
-



Industrial



Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



SPX ENDURANCE ASHLESS NGENO

TYPICAL PROPERTIES

SAE Grade	30	40	15W-40
Specific Gravity @ 60°F	0.883	0.892	0.871
Density, lbs/gal @ 60°F	7.36	7.43	7.26
Color, ASTM D1500	3.0	3.0	3.0
Flash Point (COC), °C (°F)	260(500)	254(460)	227(440)
Pour Point, °C (°F)	-30(-22)	-12(10)	-15(5)
Viscosity			
cSt @ 40°C	92.8	137	97.7
cSt @ 100°C	11.0	14.1	13.6
Viscosity Index	103	100	140
Total Base Number (TBN), ASTM D2896	2.3	2.3	2.3
Sulfated Ash, ASTM D874, wt%	<0.1	<0.1	<0.1

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).



Industrial

Web: www.pilotthomas.com
Email: info@spx-usa.com
Tel: 844.785.8326



Page: 2 of 2
Date: 02.17.2026