

SPX SELECT SYN BLEND HM SQ/GF-7

ENGINE OIL FOR HIGH MILEAGE PASSENGER CAR VEHICLES

SPX Select Syn Blend HM SQ/GF-7 is an automotive engine oil formulated with premium base oils and high-performance additives. It provides good wear protection, sludge control, and protection against rust and corrosion. The formulation is compatible with current emission control systems and contains seal conditioning agents to protect components for improved engine durability and life. SPX Select Syn Blend HM SQ/GF-7 is recommended for vehicles where excessive mileage is a concern with respect to engine age and onset wear.

Advantages

- Good resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge, varnish formation, rust, bearing corrosion, and wear
- Includes higher levels of detergency for vehicles with aging engines

Applications

- Gasoline direct-injection, conventional gasoline-fueled passenger cars, trucks, and SUVs
- Four-stroke gasoline engines in other mobile or stationary equipment

Specifications

SPX Select Syn Blend SQ/GF-7 is recommended for use where the manufacturer specifies:

- API SQ
- ILSAC GF-7A
- Chrysler MS-6395
- Ford WSS-M2C960-A1, WSS-M2C945-B1 (SAE 5W-20)
- Ford WSS-M2C961-A1, WSS-M2C946-B1 (SAE 5W-30)
- GM 6094M

TYPICAL PROPERTIES

SAE Grade	5W-20	5W-30	10W-30
Specific Gravity @ 60°F	0.86	0.86	0.87
Density, lbs/gal @ 60°F	7.2	7.2	7.2
Flash Point (COC), °C (°F)	>200(>392)	>200(>392)	>220(>428)
Pour Point, °C (°F)	-45(-49)	-45(-49)	-40(-40)
Viscosity			
cSt @ 40°C	48.7	59.7	67.2
cSt @ 100°C	8.2	9.9	10.9
Viscosity Index	142	152	154
Cold Cranking Viscosity, cP @ (-30)	6000(-30)	5400(-30)	5000(-25)

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



Page: 1 of 1

Date: 11.25.2025



Automotive

