

SPX SELECT FULL SYN SQ/GF-7

FULL SYNTHETIC ENGINE OIL FOR PASSENGER CAR VEHICLES

SPX Select Full Syn SQ/GF-7 is an automotive engine oil formulated with full-synthetic base oil and premium additives. It provides good wear protection, sludge control, and protection against rust and corrosion. The formulation is compatible with current emission control systems and meets standard API and ILSAC specifications.

Advantages

- Formulated to be compatible with emission control system catalysts
- Good resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge, varnish formation, rust, bearing corrosion, and wear

Applications

- Gasoline direct-injection, gasoline-fueled passenger cars, light trucks, and SUVs
- Four-stroke gasoline engines in other mobile or stationary equipment

Specifications

SPX Select Full Syn SQ/GF-7 is recommended for use where the manufacturer specifies:

- API SQ (SAE 0W-16, 0W-20, 5W-20, 5W-30, & 10W-30)
- ILSAC GF-7A, backwards compatible (SAE 0W-20, 5W-20, 5W-30, & 10W-30)
- ILSAC GF-7B, not backwards compatible (SAE 0W-16)
- Chrysler MS-6395 (SAE 0W-20, 5W-20, 5W-30, & 10W-30)
- Ford WSS-M2C962-A1, WSS-M2C947-B1 (SAE 0W-20)
- Ford WSS-M2C960-A1, WSS-M2C945-B1 (SAE 5W-20)
- Ford WSS-M2C961-A1, WSS-M2C946-B1 (SAE 5W-30)
- GM 6094M (SAE 0W-20, 5W-20, 5W-30, & 10W-30)

TYPICAL PROPERTIES

SAE Grade	0W-16	0W-20	5W-20	5W-30	10W-30
Specific Gravity @ 60°F	0.85	0.85	0.86	0.86	0.87
Density, lbs/gal @ 60°F	7.1	7.1	7.2	7.2	7.2
Flash Point (COC), °C (°F)	>200(>392)	>200(>392)	>205(>401)	>205(>401)	>205(>401)
Pour Point, °C (°F)	-47(-53)	-45(-49)	-45(-49)	-45(-49)	-40(-40)
Viscosity					
cSt @ 40°C	38.3	43.2	42.1	57.7	63.0
cSt @ 100°C	7.4	8.3	7.9	10.2	10.2
Viscosity Index	164	171	162	166	149
Cold Cranking Viscosity, cP @ (°C)	4500(-35)	5200(-35)	5300(-35)	5900(-35)	6000(-30)

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



Page: 1 of 1

Date: 11.25.2025



Automotive

