

SALT/DE-ICING SPREADERS

Part No.		Price
	GDS150 SALT/SAND SPREADER Ground drive (270 L capacity)	
	Stainless steel hopper and peripheral components to give spread width of 1.5m - 12m @4 - 15mph*	
GDS150S	Universal spreader, ground drive, 270 L capacity hopper	7635.00
GDS150R	As above plus fitted with mudguards, road wheels & tyres and lights	8110.00
	OPTIONS	
GDS106	Optional flashing beacon for above (supplied fitted)	230.00
GDS158	Tonneau Cover c/w Support	110.00
GDS200-172A	Jack to assist hitching & unhitching	110.00
PDS210	Disc shroud to reduce spread width for GDS/PDS trailed models	150.00
	GDS250 SALT/SAND SPREADER Ground drive (465 L capacity)	
	Stainless steel hopper and peripheral components	
	STANDARD GEARBOX - to give spread width of 1.5m - 10m @5 - 15mph*	
GDS250S	Universal spreader, ground drive, 465 L capacity hopper	8710.00
GDS250R	As above but fitted with mudguards, road wheels & tyres and lights	9140.00
	HIGH SPEED GEARBOX - to give spread width of 3.0m - 14m @5 - 15mph*	
GDS251S	Universal spreader, ground drive, 465 L capacity hopper	8790.00
GDS251R	As above but fitted with mudguards, road wheels & tyres and lights	9220.00
	OPTIONS	
GDS106	Optional flashing beacon for above (supplied fitted)	230.00
GDS108	Tonneau Cover c/w Support	150.00
PDS210	Disc shroud to reduce spread width for GDS/PDS trailed models	150.00
	PDS SALT/SAND SPREADER - Engine or hydraulically driven	
	PDS models feature dual disc speed to give spread widths of 3m - 14m* S/Steel hopper & peripheral components	
PDS354D	De-mount model 585 L capacity hopper, Power Drive Spreader, 5.5hp engine	10375.00
PDS354RB	Trailed model 585 L capacity, type approved to ECWVTA , high speed, Power Drive Spreader, 5.5hp engine. Fitted with suspension, overrun brakes, mudguards, lights & jockey wheel. C/W spare wheel & mounting bracket	12305.00
PDS150D	De-mount model 270 L capacity with 3.5hp engine and dual disc speed to give 3-14m spread widths, control box, Stainless steel components, lashing/lifting points & rubber buffer feet.	8720.00
PDS150T	3 point linkage 270 L capacity hopper, hydraulic drive to give 3 - 14m spread widths	7895.00
PDS150F	Fork lift tine mounted models 270L for machines 1.5 - 3.5T (hydraulically driven)	8110.00
PDS150F1	As above but for machines 3.5T Plus/Telehandlers	8250.00
	OPTIONS	
PDS106	Optional flashing beacon for above (supplied fitted)	230.00
PDS208	Tonneau Cover c/w support for PDS354D and PDS354RB models	160.00
GDS158	Tonneau Cover c/w Support - to fit PDS150 models	110.00
PDS210	Disc shroud to reduce spread width for GDS/PDS trailed models (also fits PDS150T & PDS150F models)	150.00
PDS211	Disc shroud to reduce spread width for PDS150D and PDS354D Demount models	150.00
	Coupling/hitch variations are available on trailed machines to order at extra cost. Please specify when ordering.	
	* Spread width quoted is based on dry rock salt, spread width may vary according to moisture content and material type.	
	DRY SALT SPREADER (120 L capacity)	
LDS120T	Salt spreader, ground drive 120L capacity, for use with DRY BAGGED SALT only	2400.00
	12v DE - ICING SPREADERS	
EBC-TSS85PP	85 Ltr capacity spreader, 12v DC belt driven offset twin speed motor to give 2m and 6m spread widths. Frame allows fitment to flat or vertical surfaces Supplied with control box and power cables.	1350.00
EBC-TSS85PPL	As above - fitted to 3 Point Linkage mounting frame	1710.00
EBC-TSS130PP	130 Ltr capacity spreader, 12v DC belt driven offset twin speed motor to give 2m and 6m spread widths. Frame allows fitment to flat or vertical surfaces Supplied with control box and power cables	1490.00
EBC-TSS130PPL	As above - fitted to 3 Point Linkage mounting frame	1850.00
EBC-TSS300PP	300 Ltr capacity, De-mount spreader, suitable for UTVs, pick ups and flat beds stainless steel hopper. 12v DC belt driven offset twin speed motor to give 2m and 6m spread widths. Supplied with control box and power cables.	2950.00