

PC MAX IV 0530

Motor Oil for Petrol and Diesel Engines

No. 140530

PC MAX IV 0530 is a fully synthetic engine oil for most modern passenger cars and vans. It guarantees long oil changes intervals and high fuel savings. Specially for use with modern exhaust gas after treatment systems such as diesel particle filters.

Typical Values			Advantages
Density at 15°C	g/ml	0,854	- very low friction losses - optimum engine cleanliness - long oil changing intervals - High wear protection - High oxidation stability
CCS at -30 °C	cP	5950	
Pourpoint	°C	<-35	
Viscosity at 40 °C	mm ² /s	72	
Viscosity at 100 °C	mm ² /s	11,9	
Viscosity Index		162	
Base Number	mgKOH/g	8	

Specification

SAE 5W-30;
API SP, SN;
Stellantis FPW9.55535/03;
BMW Longlife 04;
Fiat 9.55535-S3;
Ford M2C 915-A, 929-A, 946-A/B1, 961-A;
MB 229.31, 229.51, 229.52;
GM Dexos 2;
VW 502.00, 505.00, 505.01, 511.00;
Opel/Vauxhall OV0401547-D30;
Renault RN700, RN710, RN17;
Mazda; Toyota; Lexus; Hyundai; Kia