

TRAC I 1540

STOU Universal Oil for Tractors

No. 611540

TRAC I 1540 is a semi-synthetic universal oil for Tractors that have a uniform oil quality for diesel engines, manual transmissions, axle transmissions and hydraulic systems. It is also suitable for use in wet brakes and clutches.

Typical Values			Advantages
Density at 15°C	g/ml	0,868	- optimum engine cleanliness - long oil changing intervals - high wear protection - high oxidation stability
CCS at -20 °C	cP	5550	
Pourpoint	°C	<-25	
Viscosity at 40 °C	mm ² /s	105	
Viscosity at 100 °C	mm ² /s	14	
Viscosity Index		135	
Base Number	mgKOH/g	10,5	

Specification

SAE 15W-40; API CH-4/SJ, GL-4;
Allison C-4; CASE New Holland MAT 3525, MAT 3505, MAT 3509, MAT 3526; Caterpillar TO-2; Fendt Vario; Ford M2C 86-B, 134-D, 159-B/C, 48-C3, 41-B; CASE MS 1204, 1206, 1207, 1209, 1210, 1230; CASE IH Hy-Tran B6; John Deere J20C, J20D, J27D; MAN 271, M-3275; Massey Ferguson M 1127, M 1135, M 1139, M 1143, M 1144, M 1145; MB 228.1, 228.3 (DTFR 15B110); MIL-L-2104 D; JCB Standard 4004; New Holland NH 024 C, NH 030 C, NH 324 B, NH 410 B, NH 420 A, FNH 820092101, FNH 820092102, FNH 820092103, NH 526 C, NH 540 B; Steyer 397.88.0001; ZF TE-ML 05K, 06A, 06B, 06C, 06F, 06R, 07B