

TRAC II 1530

UTTO Universal Oil for Tractors

No. 621530

TRAC II 1530 is a semi-synthetic UTTO tractor multi-purpose oil for hydraulics, gearboxes and wet brakes/clutches. Can also be used in construction machinery where an UTTO oil is specified.

Typical Values			Advantages
Density at 15°C	g/ml	0,868	- no squeaking brakes - excellent temperature behavior - long oil changing intervals - high wear protection - high oxidation stability
CCS at -20 °C	cP	3500	
Pourpoint	°C	<-36	
Viscosity at 40 °C	mm ² /s	75	
Viscosity at 100 °C	mm ² /s	11	
Viscosity Index		136	

Specification

SAE 15W-30; API GL-4;
Allison C-4; CASE New Holland MAT 3525, MAT 3526; SDFG OT 1891; SDF UTTO; Kubota UDT; Caterpillar TO-2; Ford M2C 134-D, 48-C2, 48-C, 86-A/B; John Deere J20C, J20A; Komatsu B06-0002; Massey Ferguson CMS M1135, M1141, M1143, M1145; New Holland NH 410 B, NH 420 A; Volvo VCE WB 101/97305; CASE MS 1204, 1206, 1207, 1209, 1210; CASE IH Hy-Tran B-6; Renault G.A.12, JCB Standard 4000/2000; ZF TE-ML 03E, 03F, 05E, 05F, 06A, 03L, 17E, 21F, 06B, 06D, 06H, 06F, 06M, 06P, 06R, 06T, 06L