

TRAC II 2040

UTTO Universal Oil for Tractors

No. 622040

TRAC II 2040 is a fully synthetic UTTO tractor multi-purpose oil of the highest performance class for hydraulics, transmissions (also CVT) and wet brakes/clutches. Can also be used in construction machinery where an UTTO oil is specified.

Typical Values			Advantages
Density at 15°C	g/ml	0,865	- no squeaking brakes - excellent temperature behavior - long oil changing intervals - high wear protection - high oxidation stability
CCS at -15 °C	cP	4500	
Pourpoint	°C	<-25	
Viscosity at 40 °C	mm ² /s	110	
Viscosity at 100 °C	mm ² /s	14	
Viscosity Index		128	

Specification

SAE 20W-40; API GL-4;
(GL-5 low driving force); Volvo VCE WB 101/97305, 102/97307;
Kubota UDT HD, UDT2; AGCO POWERFLUID 821XL; Allison C-4; Caterpillar TO-2; CASE IH Hy-Tran Plus; CASE MS 1210, 1206, 1207, 1209; CASE New Holland CNH MAT 3540, MAT 3526, MAT 3525, MAT 3509, MAT 3505, MAT 3510; Fendt FNHA-2-C-200.00, FNHA-2-C-201.00, Vario, FWN 81001; Ford M2C 134-C, 86-B, 86-C, 134-D, 41-B, 86-A, 53-A, 134-A/B/C; Komatsu KES 07.866; HCE-102, 102W; Akcela Multi Trans; John Deere J20C, J20A, J20D, 3000, J20B, 21A; TH Kubota UDT Fluid; Massey Ferguson CMS M1145, M1143, M1141, M1135, M1110, M1127; Valtra G2-08, 410A/B/C, XT60; New Holland FNHA-2-C.201.00, WB 410 B/C; Denison UTTO/THF; Renault G.A.12, ZF TE-ML 03E, 05F, 06E, 06K, 06N, 17E, 21F, 02A, 03F, 06R, 21A, 21G, 03L, 06B, 06D, 06F, 06H, 06M, 06P, 06T