

ATF VI US

Automatic Transmission Oil

No. 330061 (RED)

ATF VI US is a fully synthetic oil for automatic transmissions of American vehicle manufacturers. At the longest oil change intervals, it can also be used in hydrostatic drives and power steering.

Typical Values			Advantages
Color	red		- high-wear protection
Density at 15°C	g/ml	0,849	- very low friction losses
Pourpoint	°C	<-45	- optimum transmission cleanliness
Viscosity at 40 °C	mm²/s	31	- long oil changing intervals
Viscosity at 100 °C	mm²/s	6,5	- improved fuel efficiency
Viscosity Index		70	

Specification

Dexron VI;
Allison C-2, C-3, C-4, TES-295, TES-353, TES-389;
Crysler/Dodge/Jeep ATF+, ATF+2, ATF+3, ATF+4; MB 236.12, AS68RC ATF, 05127382AA, 68043742AA, 68157995AA/AB, 68218925 AA, SP-III;
Ford/Lincoln/Mercury XT-10-QLV, XT-2-QDX, XT-2-QSM, XT-5-QM, XT-5-DM, XT-6-QSP, XT-6-DSP, XT-8-QAW, XT-9-QMM5, M2C 922-A1, Type 9602, M2C 138-CJ, M2C 166-H, XT-5-QSM;
GM/GMC/Opel/Saturn AW-1; Dexron VI, IIH, IIG, IIE, IID, TypA, T-IV, ATF Z1, 6032M, HP (GMW 16974)