

ATF VI ASIA

Automatic Transmission Oil

No. 340061 (RED)

ATF VI ASIA is a fully synthetic oil for automatic transmission from Asian vehicle manufacturers. At the longest oil change intervals, it can also be used in hydrostatic drives and power steering.

Typical Values			Advantages
Color	red		- high-wear protection
Density at 15°C	g/ml	0,849	- very low friction losses
Pourpoint	°C	<-45	- optimum transmission cleanliness
Viscosity at 40 °C	mm²/s	31	- long oil changing intervals
Viscosity at 100 °C	mm²/s	6,5	- improved fuel efficiency
Viscosity Index		70	

Specification

Dexron VI;

Honda/Acura ATF DW-1, ATF Z-1, ATF Type 3.0, Type 3.1;

Hyundai/Kia ATF RED-1K, Genuine ATF, JWS 3309/Type T-4, NWS-9638 T-5, UM040 CH20 Red-1, SP, SP-II, SP-III, SP-IV, SPH-IV, SP-IV-M, SP-IV-RR, JWS 3314, SP, WS (NWS-9638);

Idemitsu ATF HP, K17;

Isuzu ATF II, ATF III, Genuine ATF, ATF WSI, SCS; Mazda ATF F-1, FW 6A EL, FW 6AX EL, FZ, JWS 3317, M-V XT-9-QMM5, M-III, Type T-IV, ATF FZ, ATF M-5, 0000-23-ATF - M5, ATF N-1, ATF S-1, JWS 3309;

Mitsubishi ATF-J2, ATF-J3, Dia Queen ATF-PA, SP MS991156, SP-II, SP-III, SP-IV, Dia Queen ATF-MA1, MZ320775, Dia Queen AW, DII/DIII;

Nissan/Infinity 402, Matic-D, Matic-J, Matic-K, Matic-S, Matic-W, Fluid A, 999MP-MTJ00P, 999MP-MTP10P, Matic R, 999MP-MTR00P, 999MP-MTS00P;

Ssangyong DSIH 5M-66, DSIH 5M-66 Rev3, DSIH 5M-52;

Subaru HP, ATF-WS, SOA635040;

Suzuki ATF 3314, ATF 3317, ATF 2384K, ATF 2326, ATF 5D06, Matic D, Matic J, MaticS;

Toyota/Lexus/Scion FZ, Type WS (JWS 3324), JWS 3309, Type T-IV; Daihatsu D3-SP;

JAMA JASO M315 Class 1-A, M315 Class 1-A-LV