

## ATF CVT ASIA

### Automatic Transmission Oil

No. 320046

ATF CVT ASIA is a fully synthetic automatic transmission oil for CVT (Continuously Variable Transmission) transmissions. Specially for Asian vehicles.

| Typical Values      |             |       | Advantages                         |
|---------------------|-------------|-------|------------------------------------|
| Color               | transparent |       | - high-wear protection             |
| Density at 15°C     | g/ml        | 0,848 | - very low friction losses         |
| Pourpoint           | °C          | <-45  | - optimum transmission cleanliness |
| Viscosity at 40 °C  | mm²/s       | 34    | - long oil changing intervals      |
| Viscosity at 100 °C | mm²/s       | 7,0   | - improved fuel efficiency         |
| Viscosity Index     |             | 170   |                                    |

### Specification

Mazda JWS 3320, CVTF 3320;  
Mitsubishi NS-II, SP-III, CVTF-J1, CVTF-J4/J4+, CVTF-ECO J4, MZ320185, MZ102652;  
Nissan NS-I, NS-II, NS-2V, NS-III;  
Subaru ECVT, iCVT, iCVT FG, High Torque CVT, Lineartronic CVTF, Lineartronic CVTF II, Lineartronic High Torque (HT) DVT, i-CVTF, i-CVTF FG, CVT ATF C-30, e-CVTF;  
Suzuki CVTF TC, CVTF 3320, CVT Green 1/2, NS-2, Su CVT Fluid, VTF 3320, TC;  
Toyota CVTF TC, CVTF FE;  
Daihatsu Ammix CVTF DTC, TC, Ammix CVTF DFE, Ammix CVT Fluid DC, Ammix CVT Fluid DFC; Honda ATF-Z1, HCF2, 08200-HCF2, CVT-1, CVT Fluid, DW-1; Hyundai/Kia CVT-J1, SP-III, CVTF SP-CVT1; Idemitsu CVTS-EX1; JASO M 358; Geely CVTF;  
Punch CVTF EZL 799, CVTF EZL 799A, CVTF PN-3H, CVT-PPT, CVT-EX1; Rongda / SAIC / SGMW / WLY SL2100